

# [MS-CSDLBI]: Conceptual Schema Definition File Format with Business Intelligence Annotations

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

| Date       | Revision History | Revision Class | Comments               |
|------------|------------------|----------------|------------------------|
| 07/16/2012 | 1.0              | New            | Released new document. |

# Contents

|                                                    |           |
|----------------------------------------------------|-----------|
| <b>1 Introduction</b>                              | <b>5</b>  |
| 1.1 Glossary                                       | 5         |
| 1.2 References                                     | 6         |
| 1.2.1 Normative References                         | 6         |
| 1.2.2 Informative References                       | 6         |
| 1.3 Overview                                       | 7         |
| 1.4 Relationship to Protocols and Other Structures | 9         |
| 1.5 Applicability Statement                        | 9         |
| 1.6 Versioning and Localization                    | 9         |
| 1.7 Vendor-Extensible Fields                       | 9         |
| <b>2 Structures</b>                                | <b>10</b> |
| 2.1 Complex and Simple Types                       | 11        |
| 2.1.1 TEntityContainer                             | 11        |
| 2.1.1.1 TDirectQueryMode                           | 12        |
| 2.1.2 TCompareOptions                              | 12        |
| 2.1.3 TEntitySet                                   | 13        |
| 2.1.4 TAssociationSet                              | 14        |
| 2.1.4.1 TState                                     | 14        |
| 2.1.5 TEntityType                                  | 15        |
| 2.1.5.1 TEntityContents                            | 16        |
| 2.1.6 TMemberRefs                                  | 17        |
| 2.1.7 TMemberRef                                   | 18        |
| 2.1.8 THierarchy                                   | 18        |
| 2.1.9 TMember                                      | 18        |
| 2.1.9.1 TContextualNameRule                        | 19        |
| 2.1.10 TDocumentation                              | 20        |
| 2.1.11 TLevel                                      | 20        |
| 2.1.12 TProperty                                   | 21        |
| 2.1.12.1 TContents                                 | 22        |
| 2.1.12.2 TDefaultAggregateFunction                 | 22        |
| 2.1.12.3 TGroupingBehavior                         | 23        |
| 2.1.12.4 TStability                                | 23        |
| 2.1.13 TBaseProperty                               | 24        |
| 2.1.13.1 TAlignment                                | 25        |
| 2.1.13.2 TSortDirection                            | 25        |
| 2.1.14 TPropertyRefs                               | 26        |
| 2.1.15 TPropertyRef                                | 26        |
| 2.1.16 TMeasure                                    | 26        |
| 2.1.17 TKpi                                        | 27        |
| 2.1.18 TNavigationProperty                         | 28        |
| <b>3 Structure Examples</b>                        | <b>30</b> |
| 3.1 CSDLBI 1.0 Example                             | 30        |
| 3.2 CSDLBI 1.1 Example                             | 45        |
| <b>4 Security</b>                                  | <b>53</b> |
| 4.1 Security Considerations for Implementers       | 53        |
| 4.2 Index of Security Fields                       | 53        |
| <b>5 Appendix A: Full XML Schema</b>               | <b>54</b> |

|                                            |           |
|--------------------------------------------|-----------|
| 5.1 CSDLBI Schema 1.0.....                 | 54        |
| 5.2 CSDLBI Schema 1.1.....                 | 58        |
| <b>6 Appendix B: Product Behavior.....</b> | <b>64</b> |
| <b>7 Change Tracking.....</b>              | <b>65</b> |
| <b>8 Index .....</b>                       | <b>66</b> |

# 1 Introduction

**Conceptual schema definition language with business intelligence annotations (CSDLBI)** is an XML-based file format that is used to annotate **Entity Data Model (EDM)**-based conceptual models. **Conceptual schema definition language (CSDL)** is a language that is based on XML and that can be used for defining EDM-based conceptual models. For more information on CSDL, see [\[MC-CSDL\]](#). Type names in CSDLBI are generally the same as in CSDL.

This specification describes the structure and semantics of CSDL **annotations** that are used in business intelligence (BI) applications. CSDLBI is used to annotate EDM-based conceptual models with specific information that is useful in BI applications.

Sections 1.7 and 2 of this specification are normative and contain [\[RFC2119\]](#) language. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

### **.NET Framework**

The following terms are defined in [\[MS-OFCGLOS\]](#):

**complex type**  
**hierarchy**  
**simple type**  
**XML namespace**  
**XML schema**

The following terms are defined in [\[MC-CSDL\]](#):

**annotation**  
**association**  
**collection**  
**conceptual schema definition language (CSDL)**  
**entity**  
**Entity Data Model (EDM)**  
**identifier**  
**namespace**  
**property**  
**schema**

The following terms are defined in [\[MS-SSAS\]](#):

**dimension**  
**level**  
**measure**

The following terms are specific to this document:

**conceptual schema definition language with business intelligence annotations (CSDLBI):** A language that is based on XML and that can be used to annotate EDM-based conceptual models with specific information that is useful in business intelligence applications.

## **conceptual schema definition language with business intelligence annotations**

**(CSDLBI) document:** A document that contains a conceptual model that is defined by using the CSDL and CSDLBI code.

**CSDLBI 1.0:** A version of CSDLBI that has a slightly reduced set of capabilities, which are identified in this document. CSDLBI 1.0 documents reference the following [XML namespace](http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions): <http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions>. For more information, see [\[XMLNS3\]](#).

**CSDLBI 1.1:** The version of CSDLBI that is defined immediately following CSDLBI 1.0. CSDLBI 1.1 documents reference the following XML namespace: <http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions>. For more information, see [\[XMLNS3\]](#).

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## **1.2 References**

### **1.2.1 Normative References**

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MC-CSDL] Microsoft Corporation, "[Conceptual Schema Definition File Format](#)".

[MS-SSAS] Microsoft Corporation, "[SQL Server Analysis Services Protocol Specification](#)".

[MSDN-NLS] Microsoft Corporation, "National Language Support (NLS) API Reference", <http://msdn.microsoft.com/en-us/goglobal/bb896001.aspx>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[XML1.0] Bray, T., Paoli, J., Sperberg-McQueen, C.M., and Maler, E., "Extensible Markup Language (XML) 1.0 (Second Edition)", W3C Recommendation, October 2000, <http://www.w3.org/TR/2000/REC-xml-20001006>

[XMLNS3] World Wide Web Consortium, "Namespaces in XML 1.0 (Third Edition)", December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

### **1.2.2 Informative References**

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

## 1.3 Overview

Conceptual schema definition language with business intelligence annotations (CSDLBI) is an XML-based file format that is used to annotate Entity Data Model (EDM)-based conceptual models and is based on standards that are defined in [\[XML1.0\]](#) and [\[XMLSCHEMA1\]](#). Conceptually, a **CSDLBI document** has an overall structure that resembles the following.

```
<Schema>
  <Using/>
  <Using/>

  <ComplexType/>

  <Function/>
  <Function/>

  <EntityContainer>
    <EntitySet>
      <bi:EntitySet/>
    <EntitySet/>

    <EntitySet>
      <bi:EntitySet/>
    <EntitySet/>

    <AssociationSet>
      <End/>
      <End/>
      <bi:AssociationSet/>
    </AssociationSet>

    <AssociationSet>
      <End/>
      <End/>
      <bi:AssociationSet/>
    </AssociationSet>

    <bi:EntityContainer>
      <bi:CompareOptions/>
    </bi:EntityContainer>
  </EntityContainer>

  <EntityType>
    <Key>
      <PropertyRef/>
    </Key>

    <Property>
      <bi:Property>
    </Property>

    <Property>
      <bi:Property>
    </Property>

    <Property>
      <bi:Measure>
```

```

        <bi:Kpi>
            <bi:Goal>
                <bi:PropertyRef/>
            </bi:Goal>
            <bi:Status>
                <bi:PropertyRef/>
            </bi:Status>
        </bi:Kpi>
    </bi:Measure>
</Property>

<NavigationProperty>
    <bi:NavigationProperty/>
</NavigationProperty>

<bi:EntityType>
    <bi:Hierarchy>
        <bi:Level>
            <bi:Source>
                <bi:PropertyRef/>
            </bi:Source>
        </bi:Level>
        <bi:Level>
            <bi:Source>
                <bi:PropertyRef/>
            </bi:Source>
        </bi:Level>
    </bi:Hierarchy>
</bi:EntityType>
</EntityType>

<EntityType>
    <bi:Hierarchy>
        <bi:Level>
            <bi:Source>
                <bi:PropertyRef/>
            </bi:Source>
        </bi:Level>
        <bi:Level>
            <bi:Source>
                <bi:PropertyRef/>
            </bi:Source>
        </bi:Level>
    </bi:Hierarchy>
</bi:EntityType>
</EntityType>

<Association>
    <End/>
    <End/>
</Association>

<Association>
    <End/>
    <End/>
</Association>
</Schema>

```

**Note** The preceding example is not a detailed specification. It is meant to provide only a visual overview.

#### **1.4 Relationship to Protocols and Other Structures**

There are no **schemas**, protocols, or other structures that extend CSDLBI.

#### **1.5 Applicability Statement**

CSDLBI is a file format for defining annotations to CSDL models that support business intelligence (BI) applications.

#### **1.6 Versioning and Localization**

This document describes the following CSDLBI versions for Microsoft® SQL Server® 2012:

- **CSDLBI 1.0**
- **CSDLBI 1.1**

Aspects of CSDLBI 1.1 that do not apply to CSDLBI 1.0 are identified in the text.

#### **1.7 Vendor-Extensible Fields**

CSDLBI has no vendor-extensible fields.

## 2 Structures

Conceptual schema definition language (CSDL) supports application-specific customization and extension through the use of annotations. These annotations allow applications to embed application-specific and vendor-specific information into CSDL. The CSDL format does not specify how to process these custom-defined structures or how to distinguish structures from multiple vendors or layers. Parsers of CSDL can ignore annotations that are not expected or are not understood. Annotations can be of two types: **AnnotationElement**, which is defined in [\[MC-CSDL\]](#) section 2.1.22, and **AnnotationAttribute**, which is defined in [\[MC-CSDL\]](#) section 2.2.7.

Conceptual schema definition language with business intelligence annotations (CSDLBI) is defined by **complex types**, some of which include [simple types](#) and other complex types.

The following CSDL elements are annotated by the corresponding CSDLBI complex types, as shown in the table.

| CSDL element       | CSDLBI complex type |
|--------------------|---------------------|
| EntityContainer    | TEntityContainer    |
| EntitySet          | TEntitySet          |
| AssociationSet     | TAssociationSet     |
| EntityType         | TEntityType         |
| Property           | TProperty           |
| NavigationProperty | TNavigationProperty |

Other CSDLBI complex types that are defined in the CSDLBI schema are included in the definitions of the complex types listed in the preceding table. These complex types are the following:

- TCompareOptions
- TBaseProperty
- TPropertyRefs
- TPropertyRef
- TMember
- TKpi (introduced in CSDLBI 1.1)
- TMemberRefs
- TMemberRef
- THierarchy (introduced in CSDLBI 1.1)
- TLevel (introduced in CSDLBI 1.1)
- TDocumentation

One more complex type that is defined in the CSDLBI schema is **TMeasure**, which is used to define the **Measure** element, a new element that is introduced in the CSDLBI 1.0 schema.

Some of the complex types include simple types. The simple types defined in the CSDLBI schema are the following:

- TState
- TDirectQueryMode
- TContents
- TDefaultAggregateFunction
- TGroupingBehavior
- TStability
- TAlignment
- TSortDirection
- TContextualNameRule
- TEntityContents

The CSDLBI schema defines a total of 18 complex types and 10 simple types. Section [2.1](#) contains a subsection for each of the complex types. Some of the complex types include simple types, and those simple types are defined in subsections under the complex type to which they belong.

An example of a CSDL model that is annotated by using these types is provided in Section [3](#) of this specification.

## 2.1 Complex and Simple Types

This section specifies each complex type that is defined by conceptual schema definition language with business intelligence annotations (CSDLBI). Each [simple type](#) that is part of a complex type is defined in a subsection about that complex type.

### 2.1.1 TEntityContainer

The **TEntityContainer** complex type annotates the **edm:EntityContainer** element that is defined in [\[MC-CSDL\]](#) section 2.1.14. The **EntityContainer** element is conceptually similar to a database or data source. It groups **EntitySet** and **AssociationSet** child elements that represent a data source.

The **TEntityContainer** complex type is defined in the schema as follows.

```
<xs:complexType name="TEntityContainer">
  <xs:sequence>
    <xs:element name="CompareOptions" type="bi:TCompareOptions" />
  </xs:sequence>
  <xs:attribute name="Caption" type="xs:string" use="optional"/>
  <xs:attribute name="Culture" type="xs:string" />
  <xs:attribute name="DirectQueryMode" type="bi:TDirectQueryMode" />
</xs:complexType>
```

The elements and attributes that are defined by **TEntityContainer** are specified in the following tables.

| Element        | Description                                                                                                                                                                                                                |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CompareOptions | Contains language-specific sorting and string comparison options for the model. The contents of the <b>CompareOptions</b> element are defined by the <b>TCompareOptions</b> complex type (section <a href="#">2.1.2</a> ). |

| Attribute       | Description                                                                                                                                                                               |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Caption         | Describes the database or data model.                                                                                                                                                     |
| Culture         | Contains the culture name from the National Language Support (NLS) API reference <a href="#">[MSDN-NLS]</a> .                                                                             |
| DirectQueryMode | Determines which mode is to be used for a query. The contents of the attribute are defined by the <b>TDirectQueryMode</b> <a href="#">simple type</a> (section <a href="#">2.1.1.1</a> ). |

### 2.1.1.1 TDirectQueryMode

The **TDirectQueryMode** [simple type](#) is an enumeration that indicates the type of query that will be conducted in DirectQuery mode. Data stores can opt to cache database information. In that case, the client can query the cache or the backing store, depending on user instructions.

The **TDirectQueryMode** type is defined in the schema as follows.

```
<xs:simpleType name="TDirectQueryMode">
  <xs:restriction base="xs:string">
    <xs:enumeration value="InMemory" />
    <xs:enumeration value="InMemoryWithDirectQuery" />
    <xs:enumeration value="DirectQueryWithInMemory" />
    <xs:enumeration value="DirectQuery" />
  </xs:restriction>
</xs:simpleType>
```

The possible values for **TDirectQueryMode** are specified in the following table.

| Value                   | Meaning                                                                                                                                    |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| InMemory                | Indicates that queries against the model will be conducted against the cache.                                                              |
| InMemoryWithDirectQuery | Indicates that queries against the model are conducted against the cache by default.                                                       |
| DirectQueryWithInMemory | Indicates that queries against the model primarily references the relational data source but can use the cache, if the cache is available. |
| DirectQuery             | Indicates that queries against the model references only the relational data source.                                                       |

### 2.1.2 TCompareOptions

The **TCompareOptions** complex type defines collation **properties** that are applied to the data model. Values for this enumeration match those defined in the [.NET Framework](#) enumeration

**System.Globalization.CompareOptions.** Microsoft® SQL Server® Analysis Services computes the value of **CompareOptions** based on the **Database.Collation** element, which is defined in [\[MS-SSAS\]](#) section 2.2.4.2.2.5.

The **TCompareOptions** type is defined in the schema as follows.

```
<xs:complexType name="TCompareOptions" >
  <xs:attribute name="IgnoreCase" type="xs:boolean" default="false" />
  <xs:attribute name="IgnoreNonSpace" type="xs:boolean" default="false" />
  <xs:attribute name="IgnoreKanaType" type="xs:boolean" default="false" />
  <xs:attribute name="IgnoreWidth" type="xs:boolean" default="false" />
</xs:complexType>
```

The attributes that are defined by the **TCompareOptions** type are specified in the following table.

| Attribute      | Description                                                                                                |
|----------------|------------------------------------------------------------------------------------------------------------|
| IgnoreCase     | Indicates whether the string comparison SHOULD ignore case.                                                |
| IgnoreNonSpace | Indicates whether the string comparison SHOULD ignore nonspacing combining characters, such as diacritics. |
| IgnoreKanaType | Indicates whether the string comparison SHOULD ignore the Kana type.                                       |
| IgnoreWidth    | Indicates whether the string comparison SHOULD ignore the character width.                                 |

### 2.1.3 TEntitySet

The **TEntitySet** complex type annotates the **edm:EntitySet** element that is defined in [\[MC-CSDL\]](#) section 2.1.18. The **EntitySet** element defines a named set that can contain instances of an **entity**. More than one **EntitySet** element for a particular **EntityType** can be defined.

The **TEntitySet** type is defined in the schema as follows.

```
<xs:complexType name="TEntitySet">
  <xs:attribute name="Caption" type="xs:string" use="optional"/>
  <xs:attribute name="CollectionCaption" type="xs:string" use="optional"/>
  <xs:attribute name="ReferenceName" type="xs:string" use="optional"/>
  <xs:attribute name="Hidden" type="xs:boolean" default="false" use="optional"/>
</xs:complexType>
```

The attributes that are defined by **TEntitySet** are specified in the following table.

| Attribute         | Description                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Caption           | Contains a user-friendly display name for the entity. If no caption has been set in the model, no caption is displayed.       |
| CollectionCaption | Contains the plural name for the entity.                                                                                      |
| ReferenceName     | Contains the unmerged and fully qualified name of the entity; that is, the original <b>CubeDimension</b> name before munging. |

| Attribute | Description                                                                                             |
|-----------|---------------------------------------------------------------------------------------------------------|
| Hidden    | Indicates whether the entity is hidden. If the value of this attribute is "true", the entity is hidden. |

## 2.1.4 TAssociationSet

The **TAssociationSet** complex type annotates the **edm:AssociationSet** element that is defined in [\[MC-CSDL\]](#) section 2.1.19. There is one **association** set for every relationship between two entity types (defined by **EntityType** elements). An association set provides a definition for grouping association instances so that they can be mapped to a data source.

The **TAssociationSet** type is defined in the schema as follows.

```
<xs:complexType name="TAssociationSet">
  <xs:attribute name="State" type="bi:TState" default="Active"/>
  <xs:attribute name="Hidden" type="xs:boolean" default="false" />
</xs:complexType>
```

The attributes that are defined by **TAssociationSet** are specified in the following table.

| Attribute | Description                                                                                                                                                                                                                                                                                      |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| State     | Indicates the state of an association set. The contents of the <b>State</b> attribute are defined by the <b>TState simple type</b> (section <a href="#">2.1.4.1</a> ). Where multiple association sets connect two <b>EntitySets</b> , no more than one association set can be marked as active. |
| Hidden    | Indicates whether the association set will be hidden from the client. If the value of this attribute is "true", the association set will be hidden.                                                                                                                                              |

### 2.1.4.1 TState

The **TState simple type** enumerates the states that can be assigned to an association set. The **TState** type is defined in the schema as follows.

```
<xs:simpleType name="TState">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Active" />
    <xs:enumeration value="Inactive" />
  </xs:restriction>
</xs:simpleType>
```

The possible values for **TState** are specified in the following table.

| Value    | Meaning                          |
|----------|----------------------------------|
| Active   | The association set is active.   |
| Inactive | The association set is inactive. |

## 2.1.5 TEntityType

The **TEntityType** complex type annotates the **edm:EntityType** element that is defined in [\[MC-CSDL\]](#) section 2.1.2. The **EntityType** element represents the structure of a top-level concept, such as a customer or order, in a conceptual model. An entity type is a template for instances of entity types in an application.

The **TEntityType** type is defined in the schema as follows.

```
<xs:complexType name ="TEntityType">
  <xs:sequence >
    <xs:element name="DisplayKey" type="bi:TMemberRefs" minOccurs="0"
      maxOccurs="1"/>
    <xs:element name="DefaultDetails" type="bi:TMemberRefs" minOccurs="0"
      maxOccurs="1"/>
    <xs:element name="DefaultImage" minOccurs="0" maxOccurs="1" >
      <xs:complexType >
        <xs:sequence>
          <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1"
            maxOccurs="1" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="DefaultMeasure" minOccurs="0" maxOccurs="1" >
      <xs:complexType >
        <xs:sequence>
          <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1"
            maxOccurs="1" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="SortMembers" type="bi:TMemberRefs" minOccurs="0"
      maxOccurs="1"/>
    <xs:element name="Hierarchy" type ="bi:THierarchy" minOccurs="0"
      maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Contents" type="bi:TEntityContents" default="Regular"
    use="optional"/>
  <xs:attribute name="ReferenceName" type="xs:string" use="optional"/>
</xs:complexType>
```

The elements and attributes that are defined by **TEntityType** are specified in the following tables.

| Element        | Description                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DisplayKey     | A list of references to columns or to role ends that constitutes a strong <b>identifier</b> that uniquely identifies an entity instance. The list SHOULD be unique, but uniqueness is not validated.                                                                                                                                                                                        |
| DefaultDetails | A list of property references that, together, represent the larger set of columns in the table. A single property MUST be a relationship end, a column, or a <b>measure</b> .                                                                                                                                                                                                               |
| DefaultImage   | A reference to a column that contains the image that illustrates the entity. In the UDM, the <b>DefaultImage</b> element is represented by a binary attribute on the <b>dimension</b> attribute. If it is present, <b>DefaultImage</b> MUST contain exactly one <b>MemberRef</b> element whose contents are defined by the <b>TMemberRef</b> complex type (section <a href="#">2.1.7</a> ). |

| Element        | Description                                                                                                                                                                                                                                                                                            |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DefaultMeasure | A reference to a measure that is used as the default representation for multiple instances of the entity. If it is present, <b>DefaultMeasure</b> MUST contain exactly one <b>MemberRef</b> element whose contents are defined by the <b>TMemberRef</b> complex type (section <a href="#">2.1.7</a> ). |
| SortMembers    | A list of properties on which to sort. <b>TSortDirection</b> (section <a href="#">2.1.13.2</a> ) provides a hint to the sort engine about whether the order is ascending or descending.                                                                                                                |
| Hierarchy      | A list of <a href="#">hierarchies</a> ( <b>THierarchy</b> , section <a href="#">2.1.8</a> ).                                                                                                                                                                                                           |

| Attribute     | Description                                                                                                                                                              |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Contents      | The type of data in the entity. The contents of this attribute are defined by the <b>TEntityContents</b> <a href="#">simple type</a> (section <a href="#">2.1.5.1</a> ). |
| ReferenceName | The identifier that references this entity in a Data Analysis Expressions (DAX) query. If the <b>ReferenceName</b> attribute is omitted, the field name is used.         |

### 2.1.5.1 TEntityContents

The **TEntityContents** [simple type](#) enumerates the possible types of data in an entity. The **TEntityContents** type is defined in the schema as follows.

```
<xs:simpleType name="TEntityContents">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Regular"/>
    <xs:enumeration value="Time"/>
    <xs:enumeration value="Geography"/>
    <xs:enumeration value="Organization"/>
    <xs:enumeration value="BillofMaterials"/>
    <xs:enumeration value="Accounts"/>
    <xs:enumeration value="Customers"/>
    <xs:enumeration value="Products"/>
    <xs:enumeration value="Scenario"/>
    <xs:enumeration value="Quantitative"/>
    <xs:enumeration value="Utility"/>
    <xs:enumeration value="Currency"/>
    <xs:enumeration value="Rates"/>
    <xs:enumeration value="Channel"/>
    <xs:enumeration value="Promotion"/>
  </xs:restriction>
</xs:simpleType>
```

The possible values for **TEntityContents** are specified in the following table.

| Value   | Meaning                                                                                  |
|---------|------------------------------------------------------------------------------------------|
| Regular | A dimension whose type has not been set to a special dimension type.                     |
| Time    | A dimension whose attributes represent time periods, such as years, semesters, quarters, |

|                 |                                                                                                                  |
|-----------------|------------------------------------------------------------------------------------------------------------------|
| Value           | Meaning                                                                                                          |
|                 | months, or days.                                                                                                 |
| Geography       | A dimension whose attributes represent geographic information, such as cities or postal codes.                   |
| Organization    | A dimension whose attributes represent organizational information, such as employees or subsidiaries.            |
| BillOfMaterials | A dimension whose attributes represent inventory or manufacturing information, such as parts lists for products. |
| Accounts        | A dimension whose attributes represent a chart of accounts for financial reporting purposes.                     |
| Customers       | A dimension whose attributes represent customer or contact information.                                          |
| Products        | A dimension whose attributes represent product information.                                                      |
| Scenario        | A dimension whose attributes represent planning or strategic analysis information.                               |
| Quantitative    | A dimension whose attributes represent quantitative information.                                                 |
| Utility         | A dimension whose attributes represent miscellaneous information.                                                |
| Currency        | A dimension that contains currency data and metadata.                                                            |
| Rates           | A dimension whose attributes represent currency rate information.                                                |
| Channel         | A dimension whose attributes represent channel information.                                                      |
| Promotion       | A dimension whose attributes represent marketing promotion information.                                          |

The default value is "Regular".

### 2.1.6 TMemberRefs

The **TMemberRefs** complex type defines a **collection** of members in which each member is contained in a **MemberRef** element. The **TMemberRefs** type is defined in the schema as follows.

```
<xs:complexType name="TMemberRefs" >
  <xs:sequence>
    <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1"
      maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

The element that is defined by **TMemberRefs** is specified in the following table.

| Element   | Description              |
|-----------|--------------------------|
| MemberRef | A collection of members. |

### 2.1.7 TMemberRef

The **TMemberRef** complex type identifies the name of the property that is contained in a **MemberRef** element. The **TMemberRef** type is defined in the schema as follows.

```
<xs:complexType name="TMemberRef">
  <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>
```

The attribute that is defined by **TMemberRef** is specified in the following table.

| Attribute | Description                                                       |
|-----------|-------------------------------------------------------------------|
| Name      | The name of the property contained in a <b>MemberRef</b> element. |

### 2.1.8 THierarchy

In CSDLBI 1.1, the **THierarchy** complex type specifies the content of a [hierarchy](#). A hierarchy exposes the same set of attributes as do other members, such as columns, roles, and measures. Therefore, the **THierarchy** type is derived from the base **TMember** type (section [2.1.9](#)).

The **THierarchy** type is defined in the schema as follows.

```
<xs:complexType name="THierarchy">
  <xs:complexContent>
    <xs:extension base="bi:TMember">
      <xs:sequence>
        <xs:element name="Documentation" type="bi:TDocumentation"
          minOccurs="0" maxOccurs="1" />
        <xs:element name="Level" type="bi:TLevel" minOccurs="1"
          maxOccurs="unbounded" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The elements that are defined by **THierarchy** are specified in the following table.

| Element       | Description                                                                                                                                                                                                           |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Documentation | A description of the hierarchy. The contents of this element are defined by the <b>TDocumentation</b> complex type (section <a href="#">2.1.10</a> ).                                                                 |
| Level         | A single <b>level</b> of the hierarchy. The contents of this element are defined by the <b>TLevel</b> type (section <a href="#">2.1.11</a> ). The number of <b>Level</b> elements that can be specified is unlimited. |

### 2.1.9 TMember

The **TMember** complex type is a base type that includes attributes that appear in columns, measures, navigation properties, [hierarchies](#), and levels. The **TMember** type is defined in the schema as follows.

```

<xs:complexType name="TMember" abstract="true">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="Caption" type="xs:string" use="optional"/>
  <xs:attribute name="ContextualNameRule" type="bi:TContextualNameRule"
    default="None" />
  <xs:attribute name="Hidden" type="xs:boolean" default="false" />
  <xs:attribute name="ReferenceName" type="xs:string" use="optional" />
</xs:complexType>

```

The attributes that are defined by **TMember** are specified in the following table.

| Attribute                    | Description                                                                                                                                                                          |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name                         | The name given to the member (a column, measure, navigation property, hierarchy, or level) that is defined by the implementation of the <b>TMember</b> type.                         |
| Caption <sup>&lt;1&gt;</sup> | The display name for the member.                                                                                                                                                     |
| ContextualNameRule           | The naming format that is used to disambiguate members. The contents of this attribute are defined by the <b>TContextualNameRule simple type</b> (section <a href="#">2.1.9.1</a> ). |
| Hidden                       | A boolean value that indicates whether the member will be hidden from the client. If the value of this attribute is "true", the member will be hidden.                               |
| ReferenceName                | The identifier used to reference the member in a DAX query. If the <b>ReferenceName</b> attribute is omitted, the field name is used.                                                |

### 2.1.9.1 TContextualNameRule

The **TContextualNameRule simple type** enumerates the naming formats that can be used to disambiguate members. **TContextualNameRule** provides a hint to client applications for creating unambiguous names for **CalculationProperty**, which is defined in [\[MS-SSAS\]](#) section 2.2.4.2.2.10.1.

The **TContextualNameRule** type is defined in the schema as follows.

```

<xs:simpleType name="TContextualNameRule">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="Context" />
    <xs:enumeration value="Merge" />
  </xs:restriction>
</xs:simpleType>

```

The possible values for **TContextualNameRule** are specified in the following table.

| Value   | Meaning                                                                                                                      |
|---------|------------------------------------------------------------------------------------------------------------------------------|
| None    | Use the attribute name.                                                                                                      |
| Context | Use the incoming relationship name.                                                                                          |
| Merge   | Concatenate the incoming relationship name and the <b>CalculationProperty</b> name, in accordance with the language grammar. |

### 2.1.10 TDocumentation

The **TDocumentation** complex type defines the contents of the **Documentation** element, which provides information about an object that is defined in the parent element that contains the **Documentation** element.

The **TDocumentation** type is defined in the schema as follows.

```
<xs:complexType name="TDocumentation">
  <xs:sequence>
    <xs:element name="Summary" type="xs:string" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>
```

The element that is defined by **TDocumentation** is specified in the following table.

| Element | Description                                 |
|---------|---------------------------------------------|
| Summary | A description of a parent element's object. |

### 2.1.11 TLevel

The **TLevel** complex type specifies a [hierarchy](#) level. The **TLevel** type is derived from the base **TMember** type (section [2.1.9](#)).

The **TLevel** type is defined in the schema as follows.

```
<xs:complexType name="TLevel">
  <xs:complexContent>
    <xs:extension base="bi:TMember">
      <xs:sequence>
        <xs:element name="Source" minOccurs="0" maxOccurs="1">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1"
                maxOccurs="1" />
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The elements that are defined by **TLevel** are specified in the following table.

| Element            | Description                                                                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Source             | A container element for the <b>PropertyRef</b> element.                                                                                                  |
| Source.PropertyRef | A property reference that points back to an instance property. Caption, description, name, and reference name can be drawn from the referenced property. |

## 2.1.12 TProperty

The **TProperty** complex type annotates the **edm:Property** element that is defined in [\[MC-CSDL\]](#) section 2.1.3. The **TProperty** type is an extension of the **TBaseProperty** type (section [2.1.13](#)) that adds attributes that appear only in instance columns.

The **TProperty** type is defined in the schema as follows.

```
<xs:complexType name="TProperty">
  <xs:complexContent>
    <xs:extension base="bi:TBaseProperty">
      <xs:sequence >
        <xs:element name="OrderBy" type="bi:TPropertyRefs" minOccurs="0"
          maxOccurs="1"/>
      </xs:sequence>
      <xs:attribute name="Contents" type="bi:TContents" use="optional"
        default="Regular"/>
      <xs:attribute name="DefaultAggregateFunction"
        type="bi:TDefaultAggregateFunction" default="Default" />
      <xs:attribute name="GroupingBehavior" type="bi:TGroupingBehavior"
        default="GroupOnValue"/>
      <xs:attribute name="Stability" type="bi:TStability" default="Stable"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The element and attributes that are defined by **TProperty** are specified in the following tables.

| Element | Description                                                                                                                                                                                                                                                                                        |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OrderBy | A reference to another property within the model that defines the sort order for that property's values. The values for the two properties SHOULD have a 1-to-1 mapping; otherwise, the sort behavior is undefined. If <b>OrderBy</b> is omitted, the properties are sorted based on their values. |

| Attribute                | Description                                                                                                                                                                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Contents                 | The type of data in a column. This value is drawn from <b>DimensionAttribute</b> , which is defined in <a href="#">[MS-SSAS]</a> section 2.2.4.2.2.8.1. The contents of this attribute are defined by the <b>TContents simple type</b> (section <a href="#">2.1.12.1</a> ).                                              |
| DefaultAggregateFunction | A value indicating the default aggregate function, if any, that is typically used to summarize properties. The contents of this attribute are defined by the <b>TDefaultAggregateFunction simple type</b> (section <a href="#">2.1.12.2</a> ).                                                                           |
| GroupingBehavior         | A value that specifies how query results are grouped. This value is drawn from <b>DimensionAttribute</b> , which is defined in <a href="#">[MS-SSAS]</a> section 2.2.4.2.2.8.1. The attribute's contents are defined by the <b>TGroupingBehavior simple type</b> (section <a href="#">2.1.12.3</a> ).                    |
| Stability                | An attribute that specifies the stability of a declared property between refresh operations. The <b>Stability</b> attribute is set on columns that contain a row number or other volatile value (such as NOW()). This attribute is emitted only for an unstable value. The contents of this attribute are defined by the |

|           |                                                                    |
|-----------|--------------------------------------------------------------------|
| Attribute | Description                                                        |
|           | <b>TStability</b> simple type (section <a href="#">2.1.12.4</a> ). |

### 2.1.12.1 TContents

The **TContents** [simple type](#) is a string that contains the possible types of data in a column. The **TContents** value is derived from the **DimensionAttributeTypeEnumType** simple type that is included in the definition of the **DimensionAttribute** complex type, as specified in [\[MS-SSAS\]](#) section 2.2.4.2.2.8.1. If the enumeration value in **DimensionAttributeTypeEnumType** is "ExtendedType", then the **TContents** value is derived from the **ExtendedType** element of **DimensionAttribute**. The client is not required to respond to these values.

The **TContents** type is defined in the schema as follows.

```
<xs:simpleType name="TContents">
  <xs:restriction base="xs:string" />
</xs:simpleType>
```

### 2.1.12.2 TDefaultAggregateFunction

The **TDefaultAggregateFunction** [simple type](#) enumerates the aggregate functions that can be used by reporting tools to summarize attribute values. The **TDefaultAggregateFunction** type is defined in the schema as follows.

```
<xs:simpleType name="TDefaultAggregateFunction" >
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default" />
    <xs:enumeration value="None" />
    <xs:enumeration value="Sum" />
    <xs:enumeration value="Count" />
    <xs:enumeration value="Average" />
    <xs:enumeration value="Min" />
    <xs:enumeration value="Max" />
    <xs:enumeration value="DistinctCount" />
  </xs:restriction>
</xs:simpleType>
```

The possible values for **TDefaultAggregateFunction** are specified in the following table.

| Value   | Meaning                                                                          |
|---------|----------------------------------------------------------------------------------|
| Default | Automatically selects the appropriate aggregate function based on the data type. |
| None    | Does not use aggregate functions.                                                |
| Sum     | Uses the aggregate function <b>Sum</b> .                                         |
| Count   | Uses the aggregate function <b>Count</b> .                                       |
| Average | Uses the aggregate function <b>Average</b> .                                     |

| Value         | Meaning                                            |
|---------------|----------------------------------------------------|
| Min           | Uses the aggregate function <b>Min</b> .           |
| Max           | Uses the aggregate function <b>Max</b> .           |
| DistinctCount | Uses the aggregate function <b>DistinctCount</b> . |

### 2.1.12.3 TGroupingBehavior

The **TGroupingBehavior** [simple type](#) enumerates the options that are available for building queries within a [hierarchy](#). The **TGroupingBehavior** type is defined in the schema as follows.

```
<xs:simpleType name="TGroupingBehavior" >
  <xs:restriction base="xs:string" >
    <xs:enumeration value="GroupOnValue" />
    <xs:enumeration value="GroupOnEntityKey" />
  </xs:restriction>
</xs:simpleType>
```

The possible values for **TGroupingBehavior** are specified in the following table.

| Value            | Meaning              |
|------------------|----------------------|
| GroupOnValue     | Group by value.      |
| GroupOnEntityKey | Group by entity key. |

The following example illustrates the meaning of these two values. For example, to show the total payroll deductions for Brian Smith, and the value used is "GroupOnValue", the result shows the payroll deductions of all Brian Smiths that are in the database totaled together. If the value "GroupOnEntityKey" is used, the result shows the payroll deductions for each Brian Smith in the database.

### 2.1.12.4 TStability

The **TStability** [simple type](#) enumerates the acceptable values for specifying the stability of a declared property between refresh operations. The **TStability** type is defined in the schema as follows.

```
<xs:simpleType name="TStability">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Stable" />
    <xs:enumeration value="RowNumber" />
    <xs:enumeration value="Volatile" />
  </xs:restriction>
</xs:simpleType>
```

The possible values for **TStability** are specified in the following table.

| Value | Meaning |
|-------|---------|
|-------|---------|

| Value     | Meaning                                                            |
|-----------|--------------------------------------------------------------------|
| Stable    | The property remains constant between refresh operations.          |
| RowNumber | The property contains a row number.                                |
| Volatile  | The property might not remain constant between refresh operations. |

### 2.1.13 TBaseProperty

The **TBaseProperty** complex type is an extension of the **TMember** type (section [2.1.9](#)) that adds attributes that appear only in columns and measures.

The **TBaseProperty** type is defined in the schema as follows.

```
<xs:complexType name="TBaseProperty" abstract="true">
  <xs:complexContent>
    <xs:extension base="bi:TMember">
      <xs:attribute name="Alignment" type="bi:TAlignment" use="optional"/>
      <xs:attribute name="FormatString" type="xs:string" use="optional"/>
      <xs:attribute name="Units" type="xs:string" use="optional" />
      <xs:attribute name="SortDirection" type="bi:TSortDirection"
        default="Default"/>
      <xs:attribute name="IsRightToLeft" type="xs:boolean" default="false"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The attributes that are defined by **TBaseProperty** are specified in the following table.

| Attribute     | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alignment     | A value that indicates how the field values SHOULD be aligned in a tabular presentation. If the <b>Alignment</b> attribute is omitted, the default determines the alignment based on the field's data type. The contents of this attribute are defined by the <b>TAlignment</b> <a href="#">simple type</a> (section <a href="#">2.1.13.1</a> ).                                                                                                               |
| FormatString  | A .NET format string that defines the default client formatting for date and time values. If the <b>FormatString</b> attribute is omitted, the following .NET format string values are assumed: <ul style="list-style-type: none"> <li>▪ Integer fields: "g"</li> <li>▪ Decimal datatype fields: "#,0.00"</li> <li>▪ Double datatype fields: "#,0.00"</li> <li>▪ Date and time fields: "d"</li> </ul> For all other types of fields, no format string applies. |
| Units         | The symbol that is applied to field values to express units. If the <b>Units</b> attribute is omitted, the units are assumed to be unknown.                                                                                                                                                                                                                                                                                                                    |
| SortDirection | A value that indicates how the field values are typically sorted. If the <b>SortDirection</b> attribute is omitted, the default value assigns a sort direction based on the field's data type. The contents of this attribute are defined by the <b>TSortDirection</b> simple type                                                                                                                                                                             |

| Attribute     | Description                                                                                                                                                                         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               | (section <a href="#">2.1.13.2</a> ).                                                                                                                                                |
| IsRightToLeft | A boolean value that indicates whether the field contains text that MAY be read from right to left. If the <b>IsRightToLeft</b> attribute is omitted, the model setting is assumed. |

### 2.1.13.1 TAlignment

The **TAlignment** [simple type](#) enumerates the types of justification that can be used within a column. The **TAlignment** type is defined in the schema as follows.

```
<xs:simpleType name="TAlignment">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default" />
    <xs:enumeration value="Left" />
    <xs:enumeration value="Right" />
    <xs:enumeration value="Center" />
  </xs:restriction>
</xs:simpleType>
```

The possible values for type **TAlignment** are specified in the following table.

| Value   | Meaning                                                                          |
|---------|----------------------------------------------------------------------------------|
| Default | Automatically sets the appropriate justification corresponding to the data type. |
| Left    | Sets the justification to left-aligned.                                          |
| Right   | Sets the justification to right-aligned.                                         |
| Center  | Sets the justification to center-aligned.                                        |

### 2.1.13.2 TSortDirection

The **TSortDirection** [simple type](#) enumerates sort directions. The **TSortDirection** type is defined in the schema as follows.

```
<xs:simpleType name="TSortDirection">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default" />
    <xs:enumeration value="Ascending" />
    <xs:enumeration value="Descending" />
  </xs:restriction>
</xs:simpleType>
```

The possible values for **TSortDirection** are specified in the following table.

| Value   | Meaning                                                        |
|---------|----------------------------------------------------------------|
| Default | The default sort direction. The default is based on data type. |

| Value      | Meaning                        |
|------------|--------------------------------|
| Ascending  | The ascending sort direction.  |
| Descending | The descending sort direction. |

#### 2.1.14 TPropertyRefs

The **TPropertyRefs** complex type defines a collection of properties, with each property contained in a **PropertyRef** element. The **TPropertyRefs** type is defined in the schema as follows.

```
<xs:complexType name="TPropertyRefs" >
  <xs:sequence>
    <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1"
      maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

The element that is defined by **TPropertyRefs** is specified in the following table.

| Element     | Description                 |
|-------------|-----------------------------|
| PropertyRef | A collection of properties. |

#### 2.1.15 TPropertyRef

The **TPropertyRef** complex type identifies the name of the property that is contained in a **PropertyRef** element. The **PropertyRef** name MUST match the name of one of the **Property** elements within the same **EntityType**.

The **TPropertyRef** type is defined in the schema as follows.

```
<xs:complexType name="TPropertyRef">
  <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>
```

The attribute that is defined by **TPropertyRef** is specified in the following table.

| Attribute | Description                                                               |
|-----------|---------------------------------------------------------------------------|
| Name      | The name of a property that is contained in a <b>PropertyRef</b> element. |

#### 2.1.16 TMeasure

The **TMeasure** complex type is an extension of the **TProperty** type (section [2.1.12](#)), adding components that appear only in measures. The **TMeasure** type is defined in the schema as follows.

```
<xs:complexType name="TMeasure">
  <xs:complexContent>
```

```

<xs:extension base="bi:TProperty">
  <xs:sequence>
    <xs:element name="Kpi" type="bi:TKpi" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
  <xs:attribute name="IsSimpleMeasure" type="xs:boolean" default="true"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

The element and attribute that are defined by **TMeasure** are specified in the following tables.

| Element | Description                                                                                                                                    |
|---------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Kpi     | A key performance indicator (KPI). The contents of this element are defined by the <b>TKpi</b> complex type (section <a href="#">2.1.17</a> ). |

| Attribute       | Description                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IsSimpleMeasure | A boolean value that indicates whether the formula that is used in the measure is one of the simple aggregations (Sum, Count, Min, Max, Avg, DistinctCount). The value "true" means that one of the simple aggregations is used. The actual value is derived from the <b>IsSimpleMeasure</b> element in the model specified in <a href="#">[MS-SSAS]</a> section 2.2.4.2.2.10.2. |

### 2.1.17 TKpi

In CSDLBI 1.1, the **TKpi** complex type defines a calculation that can be used as a KPI. In a business intelligence data model, a KPI is based on a measure. The definition of the KPI contains all the metadata that is associated with measures, as well as information needed for the presentation of the KPI values.

The **TKpi** type does not specify the formula that is contained in the measure definition; rather, it specifies the additional metadata that is associated with measures that are used as KPIs. After a measure is designated as a KPI, it SHOULD be exposed only as a KPI.

The **TKpi** type lists attributes that SHOULD be included only with a **TMeasure** type (section [2.1.16](#)).

The **TKpi** type is defined in the schema as follows.

```

<xs:complexType name="TKpi">
  <xs:sequence>
    <xs:element name="Documentation" type="bi:TDocumentation" minOccurs="0"
      maxOccurs="1" />
    <xs:element name="Goal" minOccurs="1" maxOccurs="1" >
      <xs:complexType>
        <xs:sequence>
          <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1"
            maxOccurs="1" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Status" minOccurs="1" maxOccurs="1" >

```

```

<xs:complexType >
  <xs:sequence>
    <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1"
      maxOccurs="1" />
  </xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
<xs:attribute name="StatusGraphic" type="xs:string" use="required"/>
</xs:complexType>

```

The elements and attribute that are defined by **TKpi** are specified in the following tables.

| Element                                    | Description                                                                                                                                                                                                                                                                                               |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Documentation<br><a href="#">&lt;2&gt;</a> | An element that contains information about the KPI. The contents of this element are defined by the <b>TDocumentation</b> complex type (section <a href="#">2.1.10</a> ).                                                                                                                                 |
| Goal                                       | An element that contains the reference to the column that contains the KPI goal value. This element <b>MUST</b> contain exactly one <b>PropertyRef</b> element. The contents of this element are defined by the <b>TPropertyRef</b> complex type (section <a href="#">2.1.15</a> ).                       |
| Status                                     | An element that contains the reference to a column that contains the value as the status indicator in a KPI. This element <b>MUST</b> contain exactly one <b>PropertyRef</b> element. The contents of this element are defined by the <b>TPropertyRef</b> complex type (section <a href="#">2.1.15</a> ). |

| Attribute     | Description                                                                                                            |
|---------------|------------------------------------------------------------------------------------------------------------------------|
| StatusGraphic | A reference to an image that indicates negative, neutral, or positive progress against the targets defined in the KPI. |

### 2.1.18 TNavigationProperty

The **TNavigationProperty** complex type annotates the **edm:NavigationProperty** element, which is defined in [\[MC-CSDL\]](#) section 2.1.4. The **TNavigationProperty** type is an extension of the **TMember** type (section [2.1.9](#)), adding an attribute that appears only in navigation properties.

The **TNavigationProperty** type is defined in the schema as follows.

```

<xs:complexType name="TNavigationProperty">
  <xs:complexContent>
    <xs:extension base="bi:TMember">
      <xs:attribute name="CollectionCaption" type="xs:string" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The attribute that is defined by **TNavigationProperty** is specified in the following table.

| Attribute | Description |
|-----------|-------------|
|-----------|-------------|

| Attribute         | Description                                                                                                                                                                     |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CollectionCaption | Plural name for referring to a set of instances of the navigation property. If the <b>CollectionCaption</b> attribute is omitted, the <b>TMember.Caption</b> attribute is used. |

### 3 Structure Examples

The following samples of CSDLBI code are annotated structures that are populated with values that represent common use cases. The examples illustrate the structures that are specified in this document, but do not cover all possible usage scenarios. These samples are not intended to replace this specification but only to clarify and enhance the specification.

#### 3.1 CSDLBI 1.0 Example

```
<Schema xmlns="http://schemas.microsoft.com/ado/2008/09/edm"
xmlns:edm_annotation="http://schemas.microsoft.com/ado/2009/02/edm/annotation"
xmlns:bi="http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions" bi:Version="1.0"
Namespace="Sandbox">
  <EntityContainer Name="Sandbox">
    <Documentation>
      <Summary>DescriptionRolePlayingDimensionsDB</Summary>
    </Documentation>
    <EntitySet Name="DimCustomer" EntityType="Sandbox.DimCustomer">
      <Documentation>
        <Summary>Description_Dimension_DimCustomer</Summary>
      </Documentation>
      <bi:EntitySet />
    </EntitySet>
    <EntitySet Name="DimEmployee" EntityType="Sandbox.DimEmployee">
      <bi:EntitySet />
    </EntitySet>
    <EntitySet Name="DimGeography" EntityType="Sandbox.DimGeography">
      <bi:EntitySet />
    </EntitySet>
    <EntitySet Name="DimProduct" EntityType="Sandbox.DimProduct">
      <bi:EntitySet />
    </EntitySet>
    <EntitySet Name="DimProductCategory" EntityType="Sandbox.DimProductCategory">
      <bi:EntitySet />
    </EntitySet>
    <EntitySet Name="DimProductSubcategory"
EntityType="Sandbox.DimProductSubcategory">
      <bi:EntitySet />
    </EntitySet>
    <EntitySet Name="DimStore" EntityType="Sandbox.DimStore">
      <bi:EntitySet />
    </EntitySet>
    <EntitySet Name="DimTime" EntityType="Sandbox.DimTime">
      <bi:EntitySet />
    </EntitySet>
    <EntitySet Name="FactInternetSales" EntityType="Sandbox.FactInternetSales">
      <bi:EntitySet />
    </EntitySet>
    <AssociationSet Name="DimCustomer_DimGeography_Geography"
Association="Sandbox.DimCustomer_DimGeography_Geography">
      <End EntitySet="DimCustomer" />
      <End EntitySet="DimGeography" />
      <bi:AssociationSet />
    </AssociationSet>
    <AssociationSet Name="DimProduct_DimProductSubcategory_Subcategory"
Association="Sandbox.DimProduct_DimProductSubcategory_Subcategory">
      <End EntitySet="DimProduct" />
```

```

        <End EntitySet="DimProductSubcategory" />
        <bi:AssociationSet />
    </AssociationSet>
    <AssociationSet Name="DimProductSubcategory_DimProductCategory_Category"
Association="Sandbox.DimProductSubcategory_DimProductCategory_Category">
        <End EntitySet="DimProductSubcategory" />
        <End EntitySet="DimProductCategory" />
        <bi:AssociationSet />
    </AssociationSet>
    <AssociationSet Name="DimStore_DimGeography_Geography2"
Association="Sandbox.DimStore_DimGeography_Geography2">
        <End EntitySet="DimStore" />
        <End EntitySet="DimGeography" />
        <bi:AssociationSet State="Inactive" />
    </AssociationSet>
    <AssociationSet Name="FactInternetSales_DimCustomer_Customer2"
Association="Sandbox.FactInternetSales_DimCustomer_Customer2">
        <End EntitySet="FactInternetSales" />
        <End EntitySet="DimCustomer" />
        <bi:AssociationSet />
    </AssociationSet>
    <AssociationSet Name="FactInternetSales_DimCustomer_Customer_2"
Association="Sandbox.FactInternetSales_DimCustomer_Customer_2">
        <End EntitySet="FactInternetSales" />
        <End EntitySet="DimCustomer" />
        <bi:AssociationSet State="Inactive" />
    </AssociationSet>
    <AssociationSet Name="FactInternetSales_DimTime_Time"
Association="Sandbox.FactInternetSales_DimTime_Time">
        <End EntitySet="FactInternetSales" />
        <End EntitySet="DimTime" />
        <bi:AssociationSet State="Inactive" />
    </AssociationSet>
    <AssociationSet Name="FactInternetSales_DimTime_Time_2"
Association="Sandbox.FactInternetSales_DimTime_Time_2">
        <End EntitySet="FactInternetSales" />
        <End EntitySet="DimTime" />
        <bi:AssociationSet State="Inactive" />
    </AssociationSet>
    <AssociationSet Name="FactInternetSales_DimTime_Time_3"
Association="Sandbox.FactInternetSales_DimTime_Time_3">
        <End EntitySet="FactInternetSales" />
        <End EntitySet="DimTime" />
        <bi:AssociationSet />
    </AssociationSet>
    <AssociationSet Name="FactInternetSales_DimStore_Store2"
Association="Sandbox.FactInternetSales_DimStore_Store2">
        <End EntitySet="FactInternetSales" />
        <End EntitySet="DimStore" />
        <bi:AssociationSet />
    </AssociationSet>
    <AssociationSet Name="FactInternetSales_DimEmployee_Employee"
Association="Sandbox.FactInternetSales_DimEmployee_Employee">
        <End EntitySet="FactInternetSales" />
        <End EntitySet="DimEmployee" />
        <bi:AssociationSet />
    </AssociationSet>
    <AssociationSet Name="FactInternetSales_DimProduct_Product2"
Association="Sandbox.FactInternetSales_DimProduct_Product2">
        <End EntitySet="FactInternetSales" />

```

```

        <End EntitySet="DimProduct" />
        <bi:AssociationSet />
    </AssociationSet>
    <bi:EntityContainer Caption="CaptionRolePlayingDimensionsDB" Culture="ja-JP">
        <bi:CompareOptions IgnoreCase="true" IgnoreKanaType="true" IgnoreWidth="true"
/>

    </bi:EntityContainer>
</EntityContainer>
<EntityType Name="DimCustomer">
    <Key>
        <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
        <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>
    <Property Name="CustomerKey" Type="Int64" Nullable="false">
        <Documentation>
            <Summary>Description_Dimension_CustomerKey</Summary>
        </Documentation>
        <bi:Property Caption="Caption_Dimension_CustomerKey" Hidden="true">
            <bi:OrderBy>
                <bi:PropertyRef Name="GeographyKey" />
            </bi:OrderBy>
        </bi:Property>
    </Property>
    <Property Name="GeographyKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="CustomerAlternateKey" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="Title" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property ContextualNameRule="Context" Alignment="Left" Units="money"
SortDirection="Ascending" IsRightToLeft="true" DefaultAggregateFunction="Max" />
    </Property>
    <Property Name="FirstName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="MiddleName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="LastName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="NameStyle" Type="Boolean">
        <bi:Property />
    </Property>
    <Property Name="BirthDate" Type="DateTime">
        <bi:Property />
    </Property>
    <Property Name="MaritalStatus" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>

```

```

        <Property Name="Suffix" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="Gender" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="EmailAddress" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="YearlyIncome" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="TotalChildren" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="NumberChildrenAtHome" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="EnglishEducation" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SpanishEducation" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="FrenchEducation" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="EnglishOccupation" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SpanishOccupation" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="FrenchOccupation" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="HouseOwnerFlag" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="NumberCarsOwned" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="AddressLine1" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="AddressLine2" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>

```

```

        <Property Name="Phone" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="DateFirstPurchase" Type="DateTime">
        <bi:Property />
    </Property>
    <Property Name="CommuteDistance" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <NavigationProperty Name="Geography"
Relationship="Sandbox.DimCustomer_DimGeography_Geography" FromRole="Customer"
ToRole="Geography">
        <Documentation>
            <Summary>DESCRIPTION_RelationshipEnd_Cust_Geog</Summary>
        </Documentation>
        <bi:NavigationProperty Caption="CAPTION_RelationshipEnd_Cust_Geog"
ContextualNameRule="Context" />
    </NavigationProperty>
    <bi:EntityType Contents="Customers">
        <bi:DisplayKey>
            <bi:MemberRef Name="Geography" />
            <bi:MemberRef Name="Title" />
        </bi:DisplayKey>
        <bi:DefaultDetails>
            <bi:MemberRef Name="Title" />
            <bi:MemberRef Name="Geography" />
        </bi:DefaultDetails>
        <bi:DefaultImage>
            <bi:MemberRef Name="Title" />
        </bi:DefaultImage>
        <bi:SortMembers>
            <bi:MemberRef Name="Title" />
        </bi:SortMembers>
    </bi:EntityType>
</EntityType>
<EntityType Name="DimEmployee">
    <Key>
        <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
        <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>
    <Property Name="EmployeeKey" Type="Int64" Nullable="false">
        <bi:Property />
    </Property>
    <Property Name="ParentEmployeeKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="EmployeeNationalIDAlternateKey" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="ParentEmployeeNationalIDAlternateKey" Type="String"
MaxLength="Max" Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SalesTerritoryKey" Type="Int64">

```

```

        <bi:Property />
    </Property>
    <Property Name="FirstName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="LastName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="MiddleName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="NameStyle" Type="Boolean">
        <bi:Property />
    </Property>
    <Property Name="Title" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="HireDate" Type="DateTime">
        <bi:Property />
    </Property>
    <Property Name="BirthDate" Type="DateTime">
        <bi:Property />
    </Property>
    <Property Name="LoginID" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="EmailAddress" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="Phone" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="MaritalStatus" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="EmergencyContactName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="EmergencyContactPhone" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SalariedFlag" Type="Boolean">
        <bi:Property />
    </Property>
    <Property Name="Gender" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="PayFrequency" Type="Int64">
        <bi:Property />

```

```

</Property>
<Property Name="BaseRate" Type="Decimal" Precision="19" Scale="4">
  <bi:Property />
</Property>
<Property Name="VacationHours" Type="Int64">
  <bi:Property />
</Property>
<Property Name="SickLeaveHours" Type="Int64">
  <bi:Property />
</Property>
<Property Name="CurrentFlag" Type="Boolean">
  <bi:Property />
</Property>
<Property Name="SalesPersonFlag" Type="Boolean">
  <bi:Property />
</Property>
<Property Name="DepartmentName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
  <bi:Property />
</Property>
<Property Name="StartDate" Type="DateTime">
  <bi:Property />
</Property>
<Property Name="EndDate" Type="DateTime">
  <bi:Property />
</Property>
<Property Name="Status" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
  <bi:Property />
</Property>
<bi:EntityType />
</EntityType>
<EntityType Name="DimGeography">
  <Key>
    <PropertyRef Name="RowNumber" />
  </Key>
  <Property Name="RowNumber" Type="Int64" Nullable="false">
    <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
  </Property>
  <Property Name="GeographyKey" Type="Int64" Nullable="false">
    <bi:Property />
  </Property>
  <Property Name="City" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="StateProvinceCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="StateProvinceName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="CountryRegionCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>

```

```

        <Property Name="EnglishCountryRegionName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SpanishCountryRegionName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="FrenchCountryRegionName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="PostalCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SalesTerritoryKey" Type="Int64">
        <bi:Property />
    </Property>
    <bi:EntityType />
</EntityType>
<EntityType Name="DimProduct">
    <Key>
        <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
        <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>
    <Property Name="ProductKey" Type="Int64" Nullable="false">
        <bi:Property />
    </Property>
    <Property Name="ProductAlternateKey" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="ProductSubcategoryKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="WeightUnitMeasureCode" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SizeUnitMeasureCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="EnglishProductName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SpanishProductName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="FrenchProductName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="StandardCost" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />

```

```

    </Property>
    <Property Name="FinishedGoodsFlag" Type="Boolean">
      <bi:Property />
    </Property>
    <Property Name="Color" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="SafetyStockLevel" Type="Int64">
      <bi:Property />
    </Property>
    <Property Name="ReorderPoint" Type="Int64">
      <bi:Property />
    </Property>
    <Property Name="ListPrice" Type="Decimal" Precision="19" Scale="4">
      <bi:Property />
    </Property>
    <Property Name="Size" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="SizeRange" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="Weight" Type="Double">
      <bi:Property />
    </Property>
    <Property Name="DaysToManufacture" Type="Int64">
      <bi:Property />
    </Property>
    <Property Name="ProductLine" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="DealerPrice" Type="Decimal" Precision="19" Scale="4">
      <bi:Property />
    </Property>
    <Property Name="Class" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="Style" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="ModelName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="EnglishDescription" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="FrenchDescription" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="ChineseDescription" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">

```

```

        <bi:Property />
    </Property>
    <Property Name="ArabicDescription" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="HebrewDescription" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="ThaiDescription" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="StartDate" Type="DateTime">
        <bi:Property />
    </Property>
    <Property Name="EndDate" Type="DateTime">
        <bi:Property />
    </Property>
    <Property Name="Status" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <NavigationProperty Name="Subcategory"
Relationship="Sandbox.DimProduct_DimProductSubcategory_Subcategory" FromRole="Product"
ToRole="Subcategory">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <bi:EntityType />
</EntityType>
<EntityType Name="DimProductCategory">
    <Key>
        <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
        <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>
    <Property Name="ProductCategoryKey" Type="Int64" Nullable="false">
        <bi:Property />
    </Property>
    <Property Name="ProductCategoryAlternateKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="EnglishProductCategoryName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SpanishProductCategoryName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="FrenchProductCategoryName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <bi:EntityType />
</EntityType>
<EntityType Name="DimProductSubcategory">
    <Key>

```

```

        <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
        <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>
    <Property Name="ProductSubcategoryKey" Type="Int64" Nullable="false">
        <bi:Property />
    </Property>
    <Property Name="ProductSubcategoryAlternateKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="EnglishProductSubcategoryName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SpanishProductSubcategoryName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="FrenchProductSubcategoryName" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="ProductCategoryKey" Type="Int64">
        <bi:Property />
    </Property>
    <NavigationProperty Name="Category"
Relationship="Sandbox.DimProductSubcategory_DimProductCategory_Category"
FromRole="Subcategory2" ToRole="Category">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <bi:EntityType />
</EntityType>
<EntityType Name="DimStore">
    <Key>
        <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
        <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>
    <Property Name="StoreKey" Type="Int64" Nullable="false">
        <bi:Property />
    </Property>
    <Property Name="Geography_Key" Type="Int64">
        <bi:Property Caption="Geography Key" ReferenceName="Geography Key" />
    </Property>
    <Property Name="StoreName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="Number_of_Employees" Type="Int64">
        <bi:Property Caption="Number of Employees" ReferenceName="Number of Employees"
/>

    </Property>
    <Property Name="Sales" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <NavigationProperty Name="Geography2"
Relationship="Sandbox.DimStore_DimGeography_Geography2" FromRole="Store" ToRole="Geography2">
        <bi:NavigationProperty ContextualNameRule="Merge" />

```

```

    </NavigationProperty>
    <bi:EntityType />
</EntityType>
<EntityType Name="DimTime">
  <Key>
    <PropertyRef Name="RowNumber" />
  </Key>
  <Property Name="RowNumber" Type="Int64" Nullable="false">
    <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
  </Property>
  <Property Name="TimeKey" Type="Int64" Nullable="false">
    <bi:Property />
  </Property>
  <Property Name="FullDateAlternateKey" Type="DateTime">
    <bi:Property />
  </Property>
  <Property Name="DayNumberOfWeek" Type="Int64">
    <bi:Property />
  </Property>
  <Property Name="EnglishDayNameOfWeek" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="SpanishDayNameOfWeek" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="FrenchDayNameOfWeek" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="DayNumberOfMonth" Type="Int64">
    <bi:Property />
  </Property>
  <Property Name="DayNumberOfYear" Type="Int64">
    <bi:Property />
  </Property>
  <Property Name="WeekNumberOfYear" Type="Int64">
    <bi:Property />
  </Property>
  <Property Name="EnglishMonthName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="SpanishMonthName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="FrenchMonthName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>
  <Property Name="MonthNumberOfYear" Type="Int64">
    <bi:Property />
  </Property>
  <Property Name="CalendarQuarter" Type="Int64">
    <bi:Property />
  </Property>

```

```

        <Property Name="CalendarYear" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="CalendarSemester" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="FiscalQuarter" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="FiscalYear" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="FiscalSemester" Type="Int64">
        <bi:Property />
    </Property>
    <bi:EntityType />
</EntityType>
<EntityType Name="FactInternetSales">
    <Key>
        <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
        <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>
    <Property Name="ProductKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="OrderDateKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="DueDateKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="ShipDateKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="CustomerKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="PromotionKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="CurrencyKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="SalesTerritoryKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="SalesOrderNumber" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SalesOrderLineNumber" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="RevisionNumber" Type="Int64">
        <bi:Property />

```

```

</Property>
<Property Name="OrderQuantity" Type="Int64">
  <bi:Property />
</Property>
<Property Name="UnitPrice" Type="Decimal" Precision="19" Scale="4">
  <bi:Property />
</Property>
<Property Name="ExtendedAmount" Type="Decimal" Precision="19" Scale="4">
  <bi:Property />
</Property>
<Property Name="UnitPriceDiscountPct" Type="Double">
  <bi:Property />
</Property>
<Property Name="DiscountAmount" Type="Double">
  <bi:Property />
</Property>
<Property Name="ProductStandardCost" Type="Decimal" Precision="19" Scale="4">
  <bi:Property />
</Property>
<Property Name="TotalProductCost" Type="Decimal" Precision="19" Scale="4">
  <bi:Property />
</Property>
<Property Name="SalesAmount" Type="Decimal" Precision="19" Scale="4">
  <bi:Property />
</Property>
<Property Name="TaxAmt" Type="Decimal" Precision="19" Scale="4">
  <bi:Property />
</Property>
<Property Name="Freight" Type="Decimal" Precision="19" Scale="4">
  <bi:Property />
</Property>
<Property Name="CarrierTrackingNumber" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
  <bi:Property />
</Property>
<Property Name="CustomerPONumber" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
  <bi:Property />
</Property>
<Property Name="EmployeeKey" Type="Int64">
  <bi:Property />
</Property>
<Property Name="BillingCustomerKey" Type="Int64">
  <bi:Property />
</Property>
<Property Name="StoreKey" Type="Int64">
  <bi:Property />
</Property>
<Property Name="TotalSales" Type="Int64">
  <Documentation>
    <Summary>DescriptionRolePlayingDimensionsDB</Summary>
  </Documentation>
  <bi:Measure Caption="CaptionRolePlayingDimensionsDB"
ContextualNameRule="Context" Alignment="Right"
FormatString="&quot;,$&quot;#,0.00; (&quot;,$&quot;#,0.00); &quot;,$&quot;#,0.00" Units="money"
SortDirection="Ascending" IsRightToLeft="true" IsSimpleMeasure="true" />
</Property>

```

```

        <NavigationProperty Name="Customer2"
Relationship="Sandbox.FactInternetSales_DimCustomer_Customer2" FromRole="Sales"
ToRole="Customer2">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <NavigationProperty Name="Customer_2"
Relationship="Sandbox.FactInternetSales_DimCustomer_Customer_2" FromRole="Sales2"
ToRole="Customer_2">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <NavigationProperty Name="Time"
Relationship="Sandbox.FactInternetSales_DimTime_Time" FromRole="Sales3" ToRole="Time">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <NavigationProperty Name="Time_2"
Relationship="Sandbox.FactInternetSales_DimTime_Time_2" FromRole="Sales4" ToRole="Time_2">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <NavigationProperty Name="Time_3"
Relationship="Sandbox.FactInternetSales_DimTime_Time_3" FromRole="Sales5" ToRole="Time_3">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <NavigationProperty Name="Store2"
Relationship="Sandbox.FactInternetSales_DimStore_Store2" FromRole="Sales6" ToRole="Store2">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <NavigationProperty Name="Employee"
Relationship="Sandbox.FactInternetSales_DimEmployee_Employee" FromRole="Sales7"
ToRole="Employee">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <NavigationProperty Name="Product2"
Relationship="Sandbox.FactInternetSales_DimProduct_Product2" FromRole="FactInternetSales"
ToRole="Product2">
        <bi:NavigationProperty ContextualNameRule="Merge" />
    </NavigationProperty>
    <bi:EntityType>
        <bi:DefaultDetails>
            <bi:MemberRef Name="TotalSales" />
        </bi:DefaultDetails>
        <bi:DefaultMeasure>
            <bi:MemberRef Name="TotalSales" />
        </bi:DefaultMeasure>
    </bi:EntityType>
</EntityType>
<Association Name="DimCustomer_DimGeography_Geography">
    <End Role="Customer" Type="Sandbox.DimCustomer" Multiplicity="*" />
    <End Role="Geography" Type="Sandbox.DimGeography" Multiplicity="0..1" />
</Association>
<Association Name="DimProduct_DimProductSubcategory_Subcategory">
    <End Role="Product" Type="Sandbox.DimProduct" Multiplicity="*" />
    <End Role="Subcategory" Type="Sandbox.DimProductSubcategory" Multiplicity="0..1"
/>
</Association>
<Association Name="DimProductSubcategory_DimProductCategory_Category">
    <End Role="Subcategory2" Type="Sandbox.DimProductSubcategory" Multiplicity="*" />
    <End Role="Category" Type="Sandbox.DimProductCategory" Multiplicity="0..1" />
</Association>
<Association Name="DimStore_DimGeography_Geography2">
    <End Role="Store" Type="Sandbox.DimStore" Multiplicity="*" />

```

```

        <End Role="Geography2" Type="Sandbox.DimGeography" Multiplicity="0..1" />
    </Association>
    <Association Name="FactInternetSales_DimCustomer_Customer2">
        <End Role="Sales" Type="Sandbox.FactInternetSales" Multiplicity="*" />
        <End Role="Customer2" Type="Sandbox.DimCustomer" Multiplicity="0..1" />
    </Association>
    <Association Name="FactInternetSales_DimCustomer_Customer_2">
        <End Role="Sales2" Type="Sandbox.FactInternetSales" Multiplicity="*" />
        <End Role="Customer_2" Type="Sandbox.DimCustomer" Multiplicity="0..1" />
    </Association>
    <Association Name="FactInternetSales_DimTime_Time">
        <End Role="Sales3" Type="Sandbox.FactInternetSales" Multiplicity="*" />
        <End Role="Time" Type="Sandbox.DimTime" Multiplicity="0..1" />
    </Association>
    <Association Name="FactInternetSales_DimTime_Time_2">
        <End Role="Sales4" Type="Sandbox.FactInternetSales" Multiplicity="*" />
        <End Role="Time_2" Type="Sandbox.DimTime" Multiplicity="0..1" />
    </Association>
    <Association Name="FactInternetSales_DimTime_Time_3">
        <End Role="Sales5" Type="Sandbox.FactInternetSales" Multiplicity="*" />
        <End Role="Time_3" Type="Sandbox.DimTime" Multiplicity="0..1" />
    </Association>
    <Association Name="FactInternetSales_DimStore_Store2">
        <End Role="Sales6" Type="Sandbox.FactInternetSales" Multiplicity="*" />
        <End Role="Store2" Type="Sandbox.DimStore" Multiplicity="0..1" />
    </Association>
    <Association Name="FactInternetSales_DimEmployee_Employee">
        <End Role="Sales7" Type="Sandbox.FactInternetSales" Multiplicity="*" />
        <End Role="Employee" Type="Sandbox.DimEmployee" Multiplicity="0..1" />
    </Association>
    <Association Name="FactInternetSales_DimProduct_Product2">
        <End Role="FactInternetSales" Type="Sandbox.FactInternetSales" Multiplicity="*"
/>
        <End Role="Product2" Type="Sandbox.DimProduct" Multiplicity="0..1" />
    </Association>
</Schema>

```

### 3.2 CSDLBI 1.1 Example

```

<Schema xmlns="http://schemas.microsoft.com/ado/2008/09/edm"
xmlns:edm_annotation="http://schemas.microsoft.com/ado/2009/02/edm/annotation"
xmlns:bi="http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions" bi:Version="1.1"
Namespace="Sandbox">
    <EntityContainer Name="Sandbox">
        <EntitySet Name="Bike" EntityType="Sandbox.Bike">
            <bi:EntitySet Hidden="true" />
        </EntitySet>
        <EntitySet Name="BikeSales" EntityType="Sandbox.BikeSales">
            <bi:EntitySet />
        </EntitySet>
        <EntitySet Name="BikeSubcategory" EntityType="Sandbox.BikeSubcategory">
            <bi:EntitySet />
        </EntitySet>
        <EntitySet Name="CalendarQuarter" EntityType="Sandbox.CalendarQuarter">
            <bi:EntitySet />
        </EntitySet>
        <EntitySet Name="Country" EntityType="Sandbox.Country">
            <bi:EntitySet />
        </EntitySet>
    </EntityContainer>

```

```

</EntitySet>
<EntitySet Name="Currency" EntityType="Sandbox.Currency">
  <bi:EntitySet />
</EntitySet>
<EntitySet Name="SalesChannel" EntityType="Sandbox.SalesChannel">
  <bi:EntitySet />
</EntitySet>
<AssociationSet Name="Bike_BikeSubcategory_BikeSubcategory_ProductSubcategoryKey"
Association="Sandbox.Bike_BikeSubcategory_BikeSubcategory_ProductSubcategoryKey">
  <End EntitySet="Bike" />
  <End EntitySet="BikeSubcategory" />
  <bi:AssociationSet Hidden="true" />
</AssociationSet>
<AssociationSet Name="BikeSales_Bike_Bike_ProductKey"
Association="Sandbox.BikeSales_Bike_Bike_ProductKey">
  <End EntitySet="BikeSales" />
  <End EntitySet="Bike" />
  <bi:AssociationSet />
</AssociationSet>
<AssociationSet Name="BikeSales_CalendarQuarter_CalendarQuarter_CalendarQuarter"
Association="Sandbox.BikeSales_CalendarQuarter_CalendarQuarter_CalendarQuarter">
  <End EntitySet="BikeSales" />
  <End EntitySet="CalendarQuarter" />
  <bi:AssociationSet />
</AssociationSet>
<AssociationSet Name="BikeSales_Country_Country_CountryCode"
Association="Sandbox.BikeSales_Country_Country_CountryCode">
  <End EntitySet="BikeSales" />
  <End EntitySet="Country" />
  <bi:AssociationSet />
</AssociationSet>
<AssociationSet Name="BikeSales_Currency_Currency_CurrencyKey"
Association="Sandbox.BikeSales_Currency_Currency_CurrencyKey">
  <End EntitySet="BikeSales" />
  <End EntitySet="Currency" />
  <bi:AssociationSet />
</AssociationSet>
<AssociationSet Name="BikeSales_SalesChannel_SalesChannel_SalesChannelCode"
Association="Sandbox.BikeSales_SalesChannel_SalesChannel_SalesChannelCode">
  <End EntitySet="BikeSales" />
  <End EntitySet="SalesChannel" />
  <bi:AssociationSet State="Inactive" />
</AssociationSet>
<bi:EntityContainer Caption="CSDLTest" Culture="en-US">
  <bi:CompareOptions IgnoreCase="true" />
</bi:EntityContainer>
</EntityContainer>
<EntityType Name="Bike">
  <Key>
    <PropertyRef Name="RowNumber" />
  </Key>
  <Property Name="RowNumber" Type="Int64" Nullable="false">
    <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
  </Property>
  <Property Name="ProductKey" Type="Int64" Nullable="false">
    <bi:Property />
  </Property>
  <Property Name="ProductAlternateKey" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">

```

```

        <bi:Property />
    </Property>
    <Property Name="ProductSubcategoryKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="ProductName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="StandardCost" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="FinishedGoodsFlag" Type="Boolean">
        <bi:Property />
    </Property>
    <Property Name="Color" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property ContextualNameRule="Context" Alignment="Left" Units="counts"
SortDirection="Descending" IsRightToLeft="true" DefaultAggregateFunction="Max" />
    </Property>
    <Property Name="ListPrice" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="Size" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SizeRange" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="Weight" Type="Double">
        <bi:Property />
    </Property>
    <Property Name="DealerPrice" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="Class" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="Style" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="ModelName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="Description" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="WeightUnitMeasureCode" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SizeUnitMeasureCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>

```

```

    </Property>
    <Property Name="SafetyStockLevel" Type="Int64">
      <bi:Property />
    </Property>
    <Property Name="ReorderPoint" Type="Int64">
      <bi:Property />
    </Property>
    <Property Name="DaysToManufacture" Type="Int64">
      <bi:Property />
    </Property>
    <Property Name="ProductLine" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <NavigationProperty Name="BikeSubcategory_ProductSubcategoryKey"
Relationship="Sandbox.Bike_BikeSubcategory_BikeSubcategory_ProductSubcategoryKey"
FromRole="Bike_ProductSubcategoryKey" ToRole="BikeSubcategory_ProductSubcategoryKey">
      <bi:NavigationProperty />
    </NavigationProperty>
    <bi:EntityType>
      <bi:DisplayKey>
        <bi:MemberRef Name="Color" />
      </bi:DisplayKey>
      <bi:DefaultDetails>
        <bi:MemberRef Name="Color" />
      </bi:DefaultDetails>
      <bi:SortMembers>
        <bi:MemberRef Name="Color" />
      </bi:SortMembers>
      <bi:Hierarchy Name="Product_Hierarchy" Caption="Product Hierarchy"
ReferenceName="Product Hierarchy">
        <bi:Documentation>
          <bi:Summary>DESCRIPTION_ProductModelCateg_Hierarchies</bi:Summary>
        </bi:Documentation>
        <bi:Level Name="ProductLine">
          <bi:Source>
            <bi:PropertyRef Name="ProductLine" />
          </bi:Source>
        </bi:Level>
        <bi:Level Name="ModelName">
          <bi:Source>
            <bi:PropertyRef Name="ModelName" />
          </bi:Source>
        </bi:Level>
      </bi:Hierarchy>
    </bi:EntityType>
  </EntityType>
  <EntityType Name="BikeSales">
    <Key>
      <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
      <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>
    <Property Name="SalesOrderNumber" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
      <bi:Property />
    </Property>
    <Property Name="SalesOrderLineNumber" Type="Int64">

```

```

        <bi:Property />
    </Property>
    <Property Name="RevisionNumber" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="ProductKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="CountryCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="CurrencyKey" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="CalendarQuarter" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="SalesChannelCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="OrderQuantity" Type="Int64">
        <bi:Property />
    </Property>
    <Property Name="UnitPrice" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="ExtendedAmount" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="UnitPriceDiscountPct" Type="Double">
        <bi:Property />
    </Property>
    <Property Name="DiscountAmount" Type="Double">
        <bi:Property />
    </Property>
    <Property Name="ProductStandardCost" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="TotalProductCost" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="SalesAmount" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="TaxAmt" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="Freight" Type="Decimal" Precision="19" Scale="4">
        <bi:Property />
    </Property>
    <Property Name="CarrierTrackingNumber" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="CustomerPONumber" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">

```

```

        <bi:Property />
    </Property>
    <Property Name="CustomerAccountNumber" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
        <bi:Property />
    </Property>
    <Property Name="Sum_of_TotalProductCost" Type="Decimal" Precision="19" Scale="4">
        <bi:Measure Caption="Sum of TotalProductCost" ReferenceName="Sum of
TotalProductCost" FormatString="\$#,0.00; (\$#,0.00); \$#,0.00" />
    </Property>
    <Property Name="Sum_of_SalesAmount" Type="Decimal" Precision="19" Scale="4">
        <Documentation>
            <Summary>KPI Description</Summary>
        </Documentation>
        <bi:Measure Caption="Sum of SalesAmount" ReferenceName="Sum of SalesAmount"
FormatString="\$#,0.00; (\$#,0.00); \$#,0.00">
            <bi:Kpi StatusGraphic="Three Circles Colored">
                <bi:KpiGoal>
                    <bi:PropertyRef Name="v_Sum_of_SalesAmount_Goal" />
                </bi:KpiGoal>
                <bi:KpiStatus>
                    <bi:PropertyRef Name="v_Sum_of_SalesAmount_Status" />
                </bi:KpiStatus>
            </bi:Kpi>
        </bi:Measure>
    </Property>
    <NavigationProperty Name="Bike_ProductKey"
Relationship="Sandbox.BikeSales_Bike_Bike_ProductKey" FromRole="BikeSales_ProductKey"
ToRole="Bike_ProductKey">
        <bi:NavigationProperty />
    </NavigationProperty>
    <NavigationProperty Name="CalendarQuarter_CalendarQuarter"
Relationship="Sandbox.BikeSales_CalendarQuarter_CalendarQuarter_CalendarQuarter"
FromRole="BikeSales_CalendarQuarter" ToRole="CalendarQuarter_CalendarQuarter">
        <bi:NavigationProperty />
    </NavigationProperty>
    <NavigationProperty Name="Country_CountryCode"
Relationship="Sandbox.BikeSales_Country_Country_CountryCode" FromRole="BikeSales_CountryCode"
ToRole="Country_CountryCode">
        <bi:NavigationProperty />
    </NavigationProperty>
    <NavigationProperty Name="Currency_CurrencyKey"
Relationship="Sandbox.BikeSales_Currency_Currency_CurrencyKey"
FromRole="BikeSales_CurrencyKey" ToRole="Currency_CurrencyKey">
        <bi:NavigationProperty />
    </NavigationProperty>
    <NavigationProperty Name="SalesChannel_SalesChannelCode"
Relationship="Sandbox.BikeSales_SalesChannel_SalesChannel_SalesChannelCode"
FromRole="BikeSales_SalesChannelCode" ToRole="SalesChannel_SalesChannelCode">
        <bi:NavigationProperty />
    </NavigationProperty>
    <bi:EntityType />
</EntityType>
<EntityType Name="BikeSubcategory">
    <Key>
        <PropertyRef Name="RowNumber" />
    </Key>
    <Property Name="RowNumber" Type="Int64" Nullable="false">
        <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
    </Property>

```

```

        <Property Name="ProductSubcategoryKey" Type="Int64" Nullable="false">
            <bi:Property />
        </Property>
        <Property Name="Subcategory" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
            <bi:Property />
        </Property>
        <bi:EntityType />
    </EntityType>
    <EntityType Name="CalendarQuarter">
        <Key>
            <PropertyRef Name="RowNumber" />
        </Key>
        <Property Name="RowNumber" Type="Int64" Nullable="false">
            <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
        </Property>
        <Property Name="CalendarQuarter2" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false" Nullable="false">
            <bi:Property Caption="CalendarQuarter" ReferenceName="CalendarQuarter" />
        </Property>
        <bi:EntityType />
    </EntityType>
    <EntityType Name="Country">
        <Key>
            <PropertyRef Name="RowNumber" />
        </Key>
        <Property Name="RowNumber" Type="Int64" Nullable="false">
            <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
        </Property>
        <Property Name="CountryCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false" Nullable="false">
            <bi:Property />
        </Property>
        <Property Name="CountryName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
            <bi:Property />
        </Property>
        <bi:EntityType />
    </EntityType>
    <EntityType Name="Currency">
        <Key>
            <PropertyRef Name="RowNumber" />
        </Key>
        <Property Name="RowNumber" Type="Int64" Nullable="false">
            <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
        </Property>
        <Property Name="CurrencyKey" Type="Int64" Nullable="false">
            <bi:Property />
        </Property>
        <Property Name="CurrencyAlternateKey" Type="String" MaxLength="Max"
Unicode="true" FixedLength="false">
            <bi:Property />
        </Property>
        <Property Name="CurrencyName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
            <bi:Property />
        </Property>
        <bi:EntityType />
    </EntityType>

```

```

<EntityType Name="SalesChannel">
  <Key>
    <PropertyRef Name="RowNumber" />
  </Key>
  <Property Name="RowNumber" Type="Int64" Nullable="false">
    <bi:Property Hidden="true" Contents="RowNumber" Stability="RowNumber" />
  </Property>
  <Property Name="SalesChannelCode" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false" Nullable="false">
    <bi:Property />
  </Property>
  <Property Name="SalesChannelName" Type="String" MaxLength="Max" Unicode="true"
FixedLength="false">
    <bi:Property />
  </Property>
  <bi:EntityType />
</EntityType>
<Association Name="Bike_BikeSubcategory_BikeSubcategory_ProductSubcategoryKey">
  <End Role="Bike_ProductSubcategoryKey" Type="Sandbox.Bike" Multiplicity="*" />
  <End Role="BikeSubcategory_ProductSubcategoryKey" Type="Sandbox.BikeSubcategory"
Multiplicity="0..1" />
</Association>
<Association Name="BikeSales_Bike_Bike_ProductKey">
  <End Role="BikeSales_ProductKey" Type="Sandbox.BikeSales" Multiplicity="*" />
  <End Role="Bike_ProductKey" Type="Sandbox.Bike" Multiplicity="0..1" />
</Association>
<Association Name="BikeSales_CalendarQuarter_CalendarQuarter_CalendarQuarter">
  <End Role="BikeSales_CalendarQuarter" Type="Sandbox.BikeSales" Multiplicity="*"
/>
  <End Role="CalendarQuarter_CalendarQuarter" Type="Sandbox.CalendarQuarter"
Multiplicity="0..1" />
</Association>
<Association Name="BikeSales_Country_Country_CountryCode">
  <End Role="BikeSales_CountryCode" Type="Sandbox.BikeSales" Multiplicity="*" />
  <End Role="Country_CountryCode" Type="Sandbox.Country" Multiplicity="0..1" />
</Association>
<Association Name="BikeSales_Currency_Currency_CurrencyKey">
  <End Role="BikeSales_CurrencyKey" Type="Sandbox.BikeSales" Multiplicity="*" />
  <End Role="Currency_CurrencyKey" Type="Sandbox.Currency" Multiplicity="0..1" />
</Association>
<Association Name="BikeSales_SalesChannel_SalesChannel_SalesChannelCode">
  <End Role="BikeSales_SalesChannelCode" Type="Sandbox.BikeSales" Multiplicity="*"
/>
  <End Role="SalesChannel_SalesChannelCode" Type="Sandbox.SalesChannel"
Multiplicity="0..1" />
</Association>
</Schema>

```

## **4 Security**

### **4.1 Security Considerations for Implementers**

There are no known security considerations that are not covered in the preceding sections.

### **4.2 Index of Security Fields**

None.

## 5 Appendix A: Full XML Schema

For ease of implementation, the following are the full [XML schemas](#) for this protocol.

### 5.1 CSDLBI Schema 1.0

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="bi"
  targetNamespace="http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions"
  elementFormDefault="qualified"
  xmlns:bi="http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions"
  xmlns:edm="http://schemas.microsoft.com/ado/2008/09/edm"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">

  <xs:import namespace="http://schemas.microsoft.com/ado/2008/09/edm"
    schemaLocation="System.Data.Resources.CSDLSchema_2.xs"/>

  <xs:element name="EntityContainer" type="bi:TEntityContainer"/>
  <xs:element name="EntitySet" type="bi:TEntitySet"/>
  <xs:element name="AssociationSet" type="bi:TAssociationSet"/>
  <xs:element name="EntityType" type="bi:TEntityType"/>
  <xs:element name="Property" type="bi:TProperty"/>
  <xs:element name="NavigationProperty" type="bi:TNavigationProperty"/>
  <xs:element name="Measure" type="bi:TMeasure"/>
  <xs:element name="SourceDescription" type="xs:string" />

  <xs:complexType name="TEntityContainer">
    <xs:sequence>
      <xs:element name="CompareOptions" type="bi:TCompareOptions" />
    </xs:sequence>
    <xs:attribute name="Caption" type="xs:string" use="optional"/>
    <xs:attribute name="Culture" type="xs:string" />
    <xs:attribute name="DirectQueryMode" type="bi:TDirectQueryMode" />
  </xs:complexType>

  <xs:simpleType name="TDirectQueryMode">
    <xs:restriction base="xs:string">
      <xs:enumeration value="InMemory" />
      <xs:enumeration value="InMemoryWithDirectQuery" />
      <xs:enumeration value="DirectQueryWithInMemory" />
      <xs:enumeration value="DirectQuery" />
    </xs:restriction>
  </xs:simpleType>

  <xs:complexType name="TCompareOptions" >
    <xs:attribute name="IgnoreCase" type="xs:boolean" default="false" />
    <xs:attribute name="IgnoreNonSpace" type="xs:boolean" default="false" />
    <xs:attribute name="IgnoreKanaType" type="xs:boolean" default="false" />
    <xs:attribute name="IgnoreWidth" type="xs:boolean" default="false" />
  </xs:complexType>

  <xs:complexType name="TEntitySet">
    <xs:attribute name="Caption" type="xs:string" use="optional"/>
    <xs:attribute name="CollectionCaption" type="xs:string" use="optional"/>
    <xs:attribute name="ReferenceName" type="xs:string" use="optional"/>
    <xs:attribute name="Hidden" type="xs:boolean" default="false" use="optional"/>
  </xs:complexType>
```

```

<xs:complexType name="TAssociationSet">
  <xs:attribute name="State" type="bi:TState" default="Active"/>
  <xs:attribute name="Hidden" type="xs:boolean" default="false" />
</xs:complexType>

<xs:simpleType name="TState">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Active" />
    <xs:enumeration value="Inactive" />
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="TEntityType">
  <xs:sequence >
    <xs:element name="DisplayKey" type="bi:TMemberRefs" minOccurs="0" maxOccurs="1" />
    <xs:element name="DefaultDetails" type="bi:TMemberRefs" minOccurs="0" maxOccurs="1"/>
    <xs:element name="DefaultImage" minOccurs="0" maxOccurs="1" >
      <xs:complexType >
        <xs:sequence>
          <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1" maxOccurs="1" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="DefaultMeasure" minOccurs="0" maxOccurs="1" >
      <xs:complexType >
        <xs:sequence>
          <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1" maxOccurs="1" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="SortMembers" type="bi:TMemberRefs" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
  <xs:attribute name="Contents" type="bi:TEntityContents" default="Regular"
use="optional"/>
  <xs:attribute name="ReferenceName" type="xs:string" use="optional"/>
</xs:complexType>

<xs:simpleType name="TEntityContents">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Regular"/>
    <xs:enumeration value="Time"/>
    <xs:enumeration value="Geography"/>
    <xs:enumeration value="Organization"/>
    <xs:enumeration value="BillOfMaterials"/>
    <xs:enumeration value="Accounts"/>
    <xs:enumeration value="Customers"/>
    <xs:enumeration value="Products"/>
    <xs:enumeration value="Scenario"/>
    <xs:enumeration value="Quantitative"/>
    <xs:enumeration value="Utility"/>
    <xs:enumeration value="Currency"/>
    <xs:enumeration value="Rates"/>
    <xs:enumeration value="Channel"/>
    <xs:enumeration value="Promotion"/>
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="TMemberRefs" >
  <xs:sequence>

```

```

        <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1" maxOccurs="unbounded"
/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="TMemberRef">
    <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="TMember" abstract="true">
    <xs:attribute name="Caption" type="xs:string" use="optional"/>
    <xs:attribute name="ContextualNameRule" type="bi:TContextualNameRule" default="None" />
        <xs:attribute name="Hidden" type="xs:boolean" default="false" />
    <xs:attribute name="ReferenceName" type="xs:string" use="optional" />
</xs:complexType>

<xs:simpleType name="TContextualNameRule">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None" />
        <xs:enumeration value="Context" />
        <xs:enumeration value="Merge" />
    </xs:restriction>
</xs:simpleType>

<xs:complexType name="TDocumentation">
    <xs:sequence>
        <xs:element name="Summary" type="xs:string" minOccurs="0" maxOccurs="1" />
    </xs:sequence>
</xs:complexType>

<xs:complexType name="TProperty">
    <xs:complexContent>
        <xs:extension base="bi:TBaseProperty">
            <xs:sequence >
                <xs:element name="OrderBy" type="bi:TPropertyRefs" minOccurs="0" maxOccurs="1"/>
            </xs:sequence>
            <xs:attribute name="Contents" type="bi:TContents" use="optional" default="Regular"/>
            <xs:attribute name="DefaultAggregateFunction" type="bi:TDefaultAggregateFunction"
default="Default" />
            <xs:attribute name="GroupingBehavior" type="bi:TGroupingBehavior"
default="GroupOnValue"/>
            <xs:attribute name="Stability" type="bi:TStability" default="Stable"/>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

<xs:simpleType name="TContents">
    <xs:restriction base="xs:string" />
</xs:simpleType>

<xs:simpleType name="TDefaultAggregateFunction" >
    <xs:restriction base="xs:string">
        <xs:enumeration value="Default" />
        <xs:enumeration value="None" />
        <xs:enumeration value="Sum" />
        <xs:enumeration value="Count" />
        <xs:enumeration value="Average" />
        <xs:enumeration value="Min" />
        <xs:enumeration value="Max" />
    </xs:restriction>
</xs:simpleType>

```

```

    <xs:enumeration value="DistinctCount" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="TGroupingBehavior" >
  <xs:restriction base="xs:string" >
    <xs:enumeration value="GroupOnValue" />
    <xs:enumeration value="GroupOnEntityKey" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="TStability">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Stable" />
    <xs:enumeration value="RowNumber" />
    <xs:enumeration value="Volatile" />
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="TBaseProperty" abstract="true">
  <xs:complexContent>
    <xs:extension base="bi:TMember">
      <xs:attribute name="Alignment" type="bi:TAlignment" use="optional"/>
      <xs:attribute name="FormatString" type="xs:string" use="optional"/>
      <xs:attribute name="Units" type="xs:string" use="optional" />
      <xs:attribute name="SortDirection" type="bi:TSortDirection" default="Default"/>
      <xs:attribute name="IsRightToLeft" type="xs:boolean" default="false"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:simpleType name="TAlignment">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default" />
    <xs:enumeration value="Left" />
    <xs:enumeration value="Right" />
    <xs:enumeration value="Center" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="TSortDirection">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default" />
    <xs:enumeration value="Ascending" />
    <xs:enumeration value="Descending" />
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="TPropertyRefs" >
  <xs:sequence>
    <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="TPropertyRef">
  <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>

```

```

<xs:complexType name ="TMeasure">
  <xs:complexContent>
    <xs:extension base="bi:TProperty">
      <xs:attribute name="IsSimpleMeasure" type="xs:boolean" default="true"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name ="TNavigationProperty">
  <xs:complexContent>
    <xs:extension base="bi:TMember">
      <xs:attribute name="CollectionCaption" type="xs:string" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

</xs:schema>

```

## 5.2 CSDLBI Schema 1.1

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="bi"
  targetNamespace="http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions"
  elementFormDefault="qualified"
  xmlns:bi="http://schemas.microsoft.com/sqlbi/2010/10/edm/extensions"
  xmlns:edm="http://schemas.microsoft.com/ado/2008/09/edm"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">

  <xs:import namespace="http://schemas.microsoft.com/ado/2008/09/edm"
  schemaLocation="System.Data.Resources.CSDLSchema_2.xs"/>

  <xs:element name="EntityContainer" type="bi:TEntityContainer"/>
  <xs:element name="EntitySet" type="bi:TEntitySet"/>
  <xs:element name="AssociationSet" type="bi:TAssociationSet"/>
  <xs:element name="EntityType" type="bi:TEntityType"/>
  <xs:element name="Property" type="bi:TProperty"/>
  <xs:element name="NavigationProperty" type="bi:TNavigationProperty"/>
  <xs:element name="Measure" type="bi:TMeasure"/>
  <xs:element name="SourceDescription" type="xs:string" />

  <xs:complexType name ="TEntityContainer">
    <xs:sequence>
      <xs:element name="CompareOptions" type="bi:TCompareOptions" />
    </xs:sequence>
    <xs:attribute name="Caption" type="xs:string" use="optional"/>
    <xs:attribute name="Culture" type="xs:string" />
    <xs:attribute name="DirectQueryMode" type="bi:TDirectQueryMode" />
  </xs:complexType>

  <xs:simpleType name="TDirectQueryMode">
    <xs:restriction base="xs:string">
      <xs:enumeration value="InMemory" />
      <xs:enumeration value="InMemoryWithDirectQuery" />
      <xs:enumeration value="DirectQueryWithInMemory" />
      <xs:enumeration value="DirectQuery" />
    </xs:restriction>
  </xs:simpleType>

```

```

<xs:complexType name="TCompareOptions" >
  <xs:attribute name="IgnoreCase" type="xs:boolean" default="false" />
  <xs:attribute name="IgnoreNonSpace" type="xs:boolean" default="false" />
  <xs:attribute name="IgnoreKanaType" type="xs:boolean" default="false" />
  <xs:attribute name="IgnoreWidth" type="xs:boolean" default="false" />
</xs:complexType>

<xs:complexType name="TEntitySet">
  <xs:attribute name="Caption" type="xs:string" use="optional"/>
  <xs:attribute name="CollectionCaption" type="xs:string" use="optional"/>
  <xs:attribute name="ReferenceName" type="xs:string" use="optional"/>
  <xs:attribute name="Hidden" type="xs:boolean" default="false" use="optional"/>
</xs:complexType>

<xs:complexType name="TAssociationSet">
  <xs:attribute name="State" type="bi:TState" default="Active"/>
  <xs:attribute name="Hidden" type="xs:boolean" default="false" />
</xs:complexType>

<xs:simpleType name="TState">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Active" />
    <xs:enumeration value="Inactive" />
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="TEntityType">
  <xs:sequence >
    <xs:element name="DisplayKey" type="bi:TMemberRefs" minOccurs="0" maxOccurs="1" />
    <xs:element name="DefaultDetails" type="bi:TMemberRefs" minOccurs="0" maxOccurs="1"/>
    <xs:element name="DefaultImage" minOccurs="0" maxOccurs="1" >
      <xs:complexType >
        <xs:sequence>
          <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1" maxOccurs="1" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="DefaultMeasure" minOccurs="0" maxOccurs="1" >
      <xs:complexType >
        <xs:sequence>
          <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1" maxOccurs="1" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="SortMembers" type="bi:TMemberRefs" minOccurs="0" maxOccurs="1" />
    <xs:element name="Hierarchy" type="bi:THierarchy" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Contents" type="bi:TEntityContents" default="Regular" use="optional"/>
  <xs:attribute name="ReferenceName" type="xs:string" use="optional"/>
</xs:complexType>

<xs:simpleType name="TEntityContents">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Regular"/>
    <xs:enumeration value="Time"/>
    <xs:enumeration value="Geography"/>
  </xs:restriction>
</xs:simpleType>

```

```

    <xs:enumeration value="Organization"/>
    <xs:enumeration value="BillOfMaterials"/>
    <xs:enumeration value="Accounts"/>
    <xs:enumeration value="Customers"/>
    <xs:enumeration value="Products"/>
    <xs:enumeration value="Scenario"/>
    <xs:enumeration value="Quantitative"/>
    <xs:enumeration value="Utility"/>
    <xs:enumeration value="Currency"/>
    <xs:enumeration value="Rates"/>
    <xs:enumeration value="Channel"/>
    <xs:enumeration value="Promotion"/>
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="TMemberRefs" >
  <xs:sequence>
    <xs:element name="MemberRef" type="bi:TMemberRef" minOccurs="1" maxOccurs="unbounded"
  />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="TMemberRef">
  <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="THierarchy">
  <xs:complexContent>
    <xs:extension base="bi:TMember">
      <xs:sequence>
        <xs:element name="Documentation" type="bi:TDocumentation" minOccurs="0"
maxOccurs="1" />
        <xs:element name="Level" type="bi:TLevel" minOccurs="1" maxOccurs="unbounded" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="TMember" abstract="true">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="Caption" type="xs:string" use="optional"/>
  <xs:attribute name="ContextualNameRule" type="bi:TContextualNameRule" default="None" />
  <xs:attribute name="Hidden" type="xs:boolean" default="false" />
  <xs:attribute name="ReferenceName" type="xs:string" use="optional" />
</xs:complexType>

<xs:simpleType name="TContextualNameRule">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="Context" />
    <xs:enumeration value="Merge" />
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="TDocumentation">
  <xs:sequence>
    <xs:element name="Summary" type="xs:string" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="TLevel">
  <xs:complexContent>
    <xs:extension base="bi:TMember">
      <xs:sequence>
        <xs:element name="Source" minOccurs="0" maxOccurs="1" >
          <xs:complexType >
            <xs:sequence>
              <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1"
                maxOccurs="1" />
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="TProperty">
  <xs:complexContent>
    <xs:extension base="bi:TBaseProperty">
      <xs:sequence >
        <xs:element name="OrderBy" type="bi:TPropertyRefs" minOccurs="0" maxOccurs="1"/>
      </xs:sequence>
      <xs:attribute name="Contents" type="bi:TContents" use="optional" default="Regular"/>
      <xs:attribute name="DefaultAggregateFunction" type="bi:TDefaultAggregateFunction"
default="Default" />
      <xs:attribute name="GroupingBehavior" type="bi:TGroupingBehavior"
default="GroupOnValue"/>
      <xs:attribute name="Stability" type="bi:TStability" default="Stable"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:simpleType name="TContents">
  <xs:restriction base="xs:string" />
</xs:simpleType>

<xs:simpleType name="TDefaultAggregateFunction" >
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default" />
    <xs:enumeration value="None" />
    <xs:enumeration value="Sum" />
    <xs:enumeration value="Count" />
    <xs:enumeration value="Average" />
    <xs:enumeration value="Min" />
    <xs:enumeration value="Max" />
    <xs:enumeration value="DistinctCount" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="TGroupingBehavior" >
  <xs:restriction base="xs:string" >
    <xs:enumeration value="GroupOnValue" />
    <xs:enumeration value="GroupOnEntityKey" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="TStability">

```

```

    <xs:restriction base="xs:string">
      <xs:enumeration value="Stable" />
      <xs:enumeration value="RowNumber" />
      <xs:enumeration value="Volatile" />
    </xs:restriction>
  </xs:simpleType>

  <xs:complexType name="TBaseProperty" abstract="true">
    <xs:complexContent>
      <xs:extension base="bi:TMember">
        <xs:attribute name="Alignment" type="bi:TAlignment" use="optional"/>
        <xs:attribute name="FormatString" type="xs:string" use="optional"/>
        <xs:attribute name="Units" type="xs:string" use="optional" />
        <xs:attribute name="SortDirection" type="bi:TSortDirection" default="Default"/>
        <xs:attribute name="IsRightToLeft" type="xs:boolean" default="false"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

  <xs:simpleType name="TAlignment">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Default" />
      <xs:enumeration value="Left" />
      <xs:enumeration value="Right" />
      <xs:enumeration value="Center" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="TSortDirection">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Default" />
      <xs:enumeration value="Ascending" />
      <xs:enumeration value="Descending" />
    </xs:restriction>
  </xs:simpleType>

  <xs:complexType name="TPropertyRefs" >
    <xs:sequence>
      <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1"
maxOccurs="unbounded" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="TPropertyRef">
    <xs:attribute name="Name" type="xs:string" use="required" />
  </xs:complexType>

  <xs:complexType name="TMeasure">
    <xs:complexContent>
      <xs:extension base="bi:TProperty">
        <xs:sequence>
          <xs:element name="Kpi" type="bi:TKpi" minOccurs="0" maxOccurs="1" />
        </xs:sequence>
        <xs:attribute name="IsSimpleMeasure" type="xs:boolean" default="true"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

  <xs:complexType name="TKpi">

```

```

    <xs:sequence >
      <xs:element name="Documentation" type="bi:TDocumentation" minOccurs="0" maxOccurs="1"
/>
      <xs:element name="Goal" minOccurs="1" maxOccurs="1" >
        <xs:complexType >
          <xs:sequence>
            <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1" maxOccurs="1"
/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="Status" minOccurs="1" maxOccurs="1" >
        <xs:complexType >
          <xs:sequence>
            <xs:element name="PropertyRef" type="bi:TPropertyRef" minOccurs="1" maxOccurs="1"
/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
    <xs:attribute name="StatusGraphic" type="xs:string" use="required"/>
  </xs:complexType>

  <xs:complexType name="TNavigationProperty">
    <xs:complexContent>
      <xs:extension base="bi:TMember">
        <xs:attribute name="CollectionCaption" type="xs:string" use="optional"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
</xs:schema>

```

## 6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® SQL Server® 2012 Service Pack 1 (SP1) Community Technology Preview 3 (CTP3)

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.9:](#) The **Caption** attribute is not included in SQL Server 2012 SP1 CTP3.

[<2> Section 2.1.17:](#) The **Documentation** element is not serialized in SQL Server 2012 SP1 CTP3.

## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 8 Index

### A

[Applicability statement](#) 9

### C

[Change tracking](#) 65

[Complex and simple types](#) 11

[CSDLBI 1.0 example](#) 30

[CSDLBI 1.1 example](#) 45

[CSDLBI Schema 1.0](#) 54

[CSDLBI Schema 1.1](#) 58

### F

[Full XML schema](#) 54

### G

[Glossary](#) 5

### I

[Index of security fields](#) 53

[Informative references](#) 6

[Introduction](#) 5

### L

[Localization – versioning and](#) 9

### N

[Normative references](#) 6

### O

[Overview](#) 7

### P

[Product behavior](#) 64

### R

[References](#) 6

[References – informative](#) 6

[References – normative](#) 6

[Relationship to protocols and other structures](#) 9

### S

[Security](#) 53

[Security considerations for implementers](#) 53

[Security fields - index of](#) 53

[Simple types – complex and](#) 11

[Structure examples](#) 30

[Structures](#) 10

### T

[Tracking changes](#) 65

### V

[Vendor-extensible fields](#) 9

[Versioning and localization](#) 9