

# [MS-RDLRS]:

## Report Definition Language Report State File Format

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
11/3/2011	1.0	New	Released new document.
1/19/2012	1.0	None	No changes to the meaning, language, or formatting of the technical content.
2/23/2012	2.0	Major	Updated and revised the technical content.
3/27/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
5/24/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
6/29/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
7/16/2012	3.0	Major	Updated and revised the technical content.
10/8/2012	3.0	None	No changes to the meaning, language, or formatting of the technical content.
10/23/2012	3.0	None	No changes to the meaning, language, or formatting of the technical content.
3/26/2013	4.0	Major	Updated and revised the technical content.
6/11/2013	4.1	Minor	Clarified the meaning of the technical content.
8/8/2013	4.1	None	No changes to the meaning, language, or formatting of the technical content.
12/5/2013	4.1	None	No changes to the meaning, language, or formatting of the technical content.
2/11/2014	5.0	Major	Updated and revised the technical content.
5/20/2014	6.0	Major	Updated and revised the technical content.
5/10/2016	7.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>5</b>
1.1	Glossary .....	5
1.2	References .....	5
1.2.1	Normative References .....	5
1.2.2	Informative References .....	6
1.3	Overview .....	6
1.3.1	Document Structure.....	6
1.3.1.1	XML Namespace .....	6
1.4	Relationship to Protocols and Other Structures .....	6
1.5	Applicability Statement .....	7
1.6	Versioning and Localization .....	7
1.7	Vendor-Extensible Fields .....	7
<b>2</b>	<b>Structures .....</b>	<b>8</b>
2.1	Common Report State Types .....	8
2.1.1	Boolean.....	8
2.1.2	Byte.....	8
2.1.3	DateTime.....	8
2.1.4	Decimal.....	8
2.1.5	Double .....	8
2.1.6	Guid.....	8
2.1.7	Single .....	8
2.1.8	SByte.....	8
2.1.9	Int16 .....	9
2.1.10	Int32 .....	9
2.1.11	Int64 .....	9
2.1.12	String.....	9
2.1.13	Time .....	9
2.1.14	EntityReference.....	9
2.1.15	PropertyReference .....	9
2.2	ReportState.....	10
2.3	ReportSections .....	10
2.4	ReportSection.....	11
2.5	ReportFilters.....	11
2.6	SectionFilters.....	11
2.7	Filters .....	11
2.8	Filter .....	12
2.9	PrimitiveType .....	14
2.10	FilterCondition .....	14
2.11	SimpleFilterCondition.....	15
2.12	CompoundFilterCondition .....	17
2.13	ReportItems .....	17
2.14	DataRegion .....	18
2.15	TypeUsage .....	18
2.16	QueryExpressionBinding .....	18
2.17	QueryExpressionList .....	19
2.18	QueryExpression .....	19
2.19	QueryCalculateExpression .....	20
2.20	QueryFieldExpression .....	20
2.21	QueryFunctionExpression .....	21
2.22	QueryLiteralExpression .....	22
2.23	QueryMeasureExpression .....	23
2.24	QueryNullExpression.....	23
2.25	QueryProjectExpression .....	23
2.26	QueryScanExpression .....	24

2.27	QueryVariableReferenceExpression.....	24
2.28	QdmEntityPlaceholderExpression.....	24
2.29	QueryHierarchyLevelExpression .....	25
2.30	QueryTypeCastExpression .....	25
2.31	ReportSlicerState .....	26
<b>3</b>	<b>Structure Examples .....</b>	<b>27</b>
3.1	Report State.....	27
<b>4</b>	<b>Security .....</b>	<b>31</b>
4.1	Security Considerations for Implementers .....	31
4.2	Index of Security Fields .....	31
<b>5</b>	<b>Appendix A: Full XML Schema.....</b>	<b>32</b>
5.1	RDL Report State Schema .....	32
5.1.1	RDL Report State Schema for Version 2011/01.....	32
5.1.2	RDL Report State Schema for Version 2012/01.....	37
5.1.3	RDL Report State Schema for Version 2013/01.....	38
5.2	Serialization Schema .....	39
<b>6</b>	<b>Appendix B: Product Behavior .....</b>	<b>40</b>
<b>7</b>	<b>Change Tracking.....</b>	<b>41</b>
<b>8</b>	<b>Index.....</b>	<b>43</b>

# 1 Introduction

The Report Definition Language (RDL) Report State file format is the file format for Report State document. This document represents the metadata for defining **filters** in a **report** that is in the RDL file format and storing information about interactions with those filters.

Sections 1.7 and 2 of this specification are normative. All other sections and examples in this specification are informative.

## 1.1 Glossary

This document uses the following terms:

**conceptual schema definition language (CSDL) document:** A document that contains a conceptual model that is described by using the CSDL code.

**data region:** A region of a table that encompasses the range of cells that contains the table records. A data region does not include the header row (1), insert row, or total row of a table.

**entity:** An instance of an EntityType element that has a unique identity and an independent existence. An entity is an operational unit of consistency.

**filter:** A set of criteria that controls the set of records that is returned as a result set.

**globally unique identifier (GUID):** A term used interchangeably with universally unique identifier (UUID) in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [RFC4122](#) or [C706](#) must be used for generating the **GUID**. See also universally unique identifier (UUID).

**report:** An object that is a combination of three kinds of information: data or other kinds of information about how to obtain the data (queries) as well as the structure of the data; layout or formatting information that describes how the data is presented; and properties of the report, such as author of the report, report parameters, and images included in the report.

**report definition:** The blueprint for a report before the report is processed or rendered. A report definition contains information about the query and layout for the report.

**report item:** An object that exists on a report layout.

**report section:** A section within a report layout.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [RFC2119](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[MC-CSDL] Microsoft Corporation, "[Conceptual Schema Definition File Format](#)".

[MS-RDL] Microsoft Corporation, "[Report Definition Language File Format](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[XML10/5] Bray, T., Paoli, J., Sperberg-McQueen, C.M., et al., Eds., "Extensible Markup Language (XML) 1.0 (Fifth Edition)", W3C Recommendation, November 2008, <http://www.w3.org/TR/2008/REC-xml-20081126/>

[XMLSCHEMA1/2] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures Second Edition", W3C Recommendation, October 2004, <http://www.w3.org/TR/2004/REC-xmlschema-1-20041028/>

[XMLSCHEMA2/2] Biron, P., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes Second Edition", W3C Recommendation, October 2004, <http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>

## 1.2.2 Informative References

None.

## 1.3 Overview

The Report Definition Language Report State File Format document [MS-RDLRS] specifies the file format for Report State. A Report State document, that is, a document in the Report State file format, represents the metadata for defining filters in a report and storing information about interactions with those filters. A Report State document is an XML file, as specified in [\[XML10/5\]](#).

### 1.3.1 Document Structure

The root element of a Report State document is a [ReportState](#) element. Report State documents describe metadata about filters that apply to **report sections** and/or **data regions**.

#### 1.3.1.1 XML Namespace

The namespace URI for RDL Report State is as follows:

**<http://schemas.microsoft.com/sqlserver/reporting/yyyy/mm/reportstate>**

The date component (yyyy/mm) indicates the date of the release of that version of RDL Report State. The date component is used throughout this specification to identify the following specific versions of RDL Report State:

- 2011/01: [\[MSFT-RDLRS201101\]](#)
- 2012/01: [\[MSFT-RDLRS201201\]](#)
- 2013/01: [\[MSFT-RDLRS201301\]](#)

## 1.4 Relationship to Protocols and Other Structures

Report State documents represent filter metadata for a report definition language (RDL) [\[MS-RDL\]](#) file. Several cross-references exist between [MS-RDL] and the structures that are defined in this specification:

- [ReportSection](#) structures within a Report State document correspond to report section structures in an RDL file.
- [DataRegion](#) structures within a Report State document refer to data regions defined in an RDL file.
- Some items in an RDL file can contain a [ReportSlicerState](#) structure.

Report State files and structures are interpreted in the context of a **conceptual schema definition language (CSDL) document**. Some structures defined in this specification include references to **entity** containers, entity sets, or properties that are defined in a CSDL document, as specified in [\[MC-CSDL\]](#).

## 1.5 Applicability Statement

The Report State file format is applicable for use in representing the filter metadata for a **report definition**. Report State documents do not exist in isolation. Report State documents accompany report definition language (RDL) documents, as specified in [\[MS-RDL\]](#), to describe filter metadata.

## 1.6 Versioning and Localization

This document specifies the structures for the following versions of Report Definition Language Report State (RDLRS): [<1>](#)

- 2011/01 [\[MSFT-RDLRS201101\]](#)
- 2012/01 [\[MSFT-RDLRS201201\]](#)
- 2013/01 [\[MSFT-RDLRS201301\]](#)

There are no localization-dependent structures in the Report State file format.

## 1.7 Vendor-Extensible Fields

The Report State file format contains no vendor-extensible fields or structures.

## 2 Structures

### 2.1 Common Report State Types

#### 2.1.1 Boolean

If the Report State format specifies an element or attribute as type **Boolean**, it MUST be a valid **Boolean** value, as specified in [\[XMLSCHEMA2/2\]](#) section 3.2.2 for **xs:Boolean**.

#### 2.1.2 Byte

If the Report State format specifies an element or attribute as type **Byte**, it MUST be a valid **unsignedByte** value, as specified in [\[XMLSCHEMA2/2\]](#) section 3.3.24 for **xs:unsignedByte**.

#### 2.1.3 DateTime

If the Report State format specifies an element or attribute as type **DateTime**, it MUST be a valid date and time-of-day value as specified in [\[XMLSCHEMA2/2\]](#) section 3.2.7 for **xs:dateTime**.

#### 2.1.4 Decimal

If the Report State format specifies an element or attribute as type **Decimal**, it MUST be a valid **decimal** value, as specified in [\[XMLSCHEMA2/2\]](#) section 3.2.3 for **xs:decimal**.

#### 2.1.5 Double

If the Report State format specifies an element or attribute as type **Double**, it MUST be a valid **double** value, as specified in [\[XMLSCHEMA2/2\]](#) section 3.2.5 for **xs:double**.

#### 2.1.6 Guid

The **guid** simple type is from namespace <http://schemas.microsoft.com/2003/10/Serialization/>.

The **guid** simple type represents a **globally unique identifier (GUID)**.

The following is the XSD for the **guid** simple type.

```
<xs:simpleType name="guid">
  <xs:restriction base="xs:string">
    <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-
      [\da-fA-F]{4}-[\da-fA-F]{12}"/>
  </xs:restriction>
</xs:simpleType>
```

#### 2.1.7 Single

If the Report State format specifies an element or attribute as type **Single**, it MUST be a valid **single** value, as specified in [\[XMLSCHEMA2/2\]](#) section 3.2.4 for **xs:float**.

#### 2.1.8 SByte

If the Report State format specifies an element or attribute as type **SByte**, it MUST be a valid **byte** value as specified in [\[XMLSCHEMA2/2\]](#) section 3.3.19 for **xs:byte**.



### 2.1.9 Int16

If the Report State format specifies an element or attribute as type **Int16**, it MUST be a valid **short** value as specified in [\[XMLSCHEMA2/2\]](#) section 3.3.18 for **xs:short**.

### 2.1.10 Int32

If the Report State format specifies an element or attribute as type **Int32**, it MUST be a valid **int** value as specified in [\[XMLSCHEMA2/2\]](#) section 3.3.17 for **xs:int**.

### 2.1.11 Int64

If the Report State format specifies an element or attribute as type **Int64**, it MUST be a valid **long** value as specified in [\[XMLSCHEMA2/2\]](#) section 3.3.16 for **xs:long**.

### 2.1.12 String

If the Report State format specifies an element or attribute as type **String**, it MUST be a valid **string** value as specified in [\[XMLSCHEMA2/2\]](#) section 3.2.1 for **xs:string**.

### 2.1.13 Time

The **Time** simple type is from namespace <http://schemas.microsoft.com/2003/10/Serialization/>.

The **Time** simple type specifies time duration.

The following is the XSD for the **Time** simple type.

```
<xs:element name="duration" nillable="true" type="tns:duration"/>
<xs:simpleType name="duration">
  <xs:restriction base="xs:duration">
    <xs:pattern
      value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?"/>
    <xs:minInclusive value="-P10675199DT2H48M5.4775808S"/>
    <xs:maxInclusive value="P10675199DT2H48M5.4775807S"/>
  </xs:restriction>
</xs:simpleType>
```

### 2.1.14 EntityReference

If the Report State format defines an element or attribute as type **EntityReference**, it MUST be a valid string as specified in [\[XMLSCHEMA2/2\]](#). Additionally, the string MUST be of the format *EntityContainerName.EntitySetName*.

- *EntityContainerName* refers to the value of the **Name** attribute on an **EntityContainer** element in a CSDL document [\[MC-CSDL\]](#).
- *EntitySetName* refers to the value of the **Name** attribute of an **EntitySet** element in a CSDL document that is contained within the specified **EntityContainer** [\[MC-CSDL\]](#).

### 2.1.15 PropertyReference

If the Report State format defines an element or attribute as type **PropertyReference**, it MUST be a valid string as specified in [\[XMLSCHEMA2/2\]](#). Additionally, the string refers to the name of a property defined on an **EntitySet** element in a CSDL document [\[MC-CSDL\]](#).

## 2.2 ReportState

The **ReportState** element describes the state created through user interactions with a report [\[MS-RDL\]](#).

**FilterAreaVisibility:** Specifies an element that describes the state of the user interface that is used to display filters. The **FilterAreaVisibility** element is optional and MUST NOT be specified more than once.

The values and meanings for **FilterAreaVisibility** are as follows.

Value	Meaning
Collapsed	The filter area is visible in a collapsed state.
Expanded	The filter area is visible in an expanded state.
Hidden	The filter area is not displayed.

**Theme:** Specifies an element that describes the name of the theme that is used by the report. The **Theme** element is optional and MUST NOT be specified more than once.

**ReportSections:** Specifies a [ReportSections](#) element that specifies the state for items within that section. The **ReportSections** element is optional and MUST NOT be specified more than once.

The following is the XSD for the **ReportState** element.

```
<xs:element name="ReportState">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="FilterAreaVisibility" minOccurs="0">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:enumeration value="Collapsed"/>
            <xs:enumeration value="Expanded"/>
            <xs:enumeration value="Hidden"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Theme" minOccurs="0"/>
      <xs:element name="ReportSections" minOccurs="0" type="ReportSectionsType" />
      <xs:element ref="rs2013:ReportFilters" minOccurs="0" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

## 2.3 ReportSections

The **ReportSections** element specifies an ordered list of [ReportSection](#) elements.

**ReportSection:** Specifies a **ReportSection** that describes the state of each section within a report. The **ReportSection** element is optional and can be specified more than once.

The following is the XSD for the **ReportSections** element.

```
<xs:complexType name="ReportSectionsType">
  <xs:sequence>
    <xs:element name="ReportSection" type="ReportSectionType" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

## 2.4 ReportSection

The **ReportSection** element describes the state of each report section in a report definition.

**SectionFilters:** Specifies a [SectionFilters](#) element that describes the state of filters that are defined for this section of the report. The **SectionFilters** element is optional and MUST NOT be specified more than once.

**ReportItems:** Specifies a [ReportItems](#) element that describes the state of the **report items** within this section. The **ReportItems** element is optional and MUST NOT be specified more than once.

The following is the XSD for the **ReportSection** element.

```
<xs:complexType name="ReportSectionType">
  <xs:sequence>
    <xs:element name="SectionFilters" type="SectionFiltersType" minOccurs="0" />
    <xs:element name="ReportItems" type="ReportItemsType" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

## 2.5 ReportFilters

Applies to RDL Report State schema 2013/01 [\[MSFT-RDLRS201301\]](#)

The **ReportFilters** element is an ordered list of [Filters](#) elements.

**Filters:** Specifies a **Filters** element that describes the states of the filter within a report that contains one or more [ReportSection](#) elements. The **Filters** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **ReportFilters** element.

```
<xs:complexType name="ReportFiltersType">
  <xs:sequence>
    <xs:element name="Filters" type="rs2011:FiltersType" />
  </xs:sequence>
</xs:complexType>
```

## 2.6 SectionFilters

The **SectionFilters** element is an ordered list of [Filters](#) elements.

**Filters:** Specifies a **Filters** element that describes the states of the filter within a [ReportSection](#). The **Filters** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **SectionFilters** element.

```
<xs:complexType name="SectionFiltersType">
  <xs:sequence>
    <xs:element name="Filters" type="FiltersType" />
  </xs:sequence>
</xs:complexType>
```

## 2.7 Filters

The **Filters** element is an ordered list of [Filter](#) elements.

**Filter:** Specifies a **Filter** that describes the state of a filter. The **Filter** element MUST be specified at least once.

The following is the XSD for the **Filters** element.

```
<xs:complexType name="FiltersType">
  <xs:sequence>
    <xs:element name="Filter" type="FilterType" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

## 2.8 Filter

Applies to RDL Report State schemas 2011/01 [MSFT-RDLRS201101], 2012/01 [MSFT-RDLRS201201], and 2013/01 [MSFT-RDLRS201301]

The **Filter** element describes the state of a filter within a [ReportSection](#) or a [DataRegion](#).

**Mode:** Specifies an element that describes the state of the filter's mode. The **Mode** element MUST be specified.

In RDL Report State schema 2011/01 [MSFT-RDLRS201101], the values and meanings for the **Mode** element are as follows.

Value	Meaning
Advanced	The filter is in advanced mode.
Basic	The filter is in basic mode.
Cleared	The filter is cleared.

In RDL Report State schema 2012/01 [MSFT-RDLRS201201] and RDL Report State schema 2013/01 [MSFT-RDLRS201301], the values and meanings for the **Mode** element are as follows.

Value	Meaning
Advanced	The filter is in advanced mode.
Cleared	The filter is cleared.
List	The filter is a list filter.
Range	The filter is a range filter.

**IsMeasure:** Specifies whether this filter is applied to aggregated data. The **IsMeasure** element is optional and MUST NOT be specified more than once.

**Operand:** Specifies an element that describes the state of an operand that was used in a filter. The **Operand** element MUST be specified and MUST NOT be specified more than once.

**Operand.QueryExpression:** Specifies a [QueryExpression](#) that was used as the filter operand. The **Operand.QueryExpression** element MUST be specified and MUST NOT be specified more than once.

**Condition:** Specifies an element that describes the state of a condition in a filter. The **Condition** element is optional and MUST NOT be specified more than once.

**Condition.CompoundFilterCondition:** Specifies a [CompoundFilterCondition](#) that describes a set of conditions that are logically combined through a filter operator. The **Condition.CompoundFilterCondition** element MUST be specified and MUST NOT be specified more than once.

**Type:** Specifies the [PrimitiveType](#) of the data being filtered. The **Type** attribute MUST be specified and MUST NOT be specified more than once.

**IsDrilldownFilter:** Specifies a [Boolean](#) value that indicates whether drilling down is enabled within the **DataRegion** associated with this filter. The **IsDrilldownFilter** element is optional and MUST not be specified more than once. If **IsDrilldownFilter** is not specified, its value is interpreted as false. (Applies to RDL Report State schema 2012/01 [MSFT-RDLRS2012/01])

Following is the XSD for the **Filter** element.

```
<xs:complexType name="FilterType">
  <xs:sequence>
    <xs:choice>
      <xs:element name="Mode">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:enumeration value="Advanced" />
            <xs:enumeration value="Basic" />
            <xs:enumeration value="Cleared" />
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element ref="rs2012:Mode" />
    </xs:choice>
    <xs:element name="IsMeasure" minOccurs="0" />
    <xs:element ref="rs2012:IsDrilldownFilter" minOccurs="0" />
    <xs:element name="Operand">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="QueryExpression" type="QueryExpression"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Condition" minOccurs="0">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="CompoundFilterCondition" type="CompoundFilterCondition"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="Type" type="PrimitiveType" />
</xs:complexType>
```

RDL Report State schema 2012/01 [MSFT-RDLRS2012/01] and RDL Report State schema 2013/01 [MSFT-RDLRS201301] define the Mode element as follows.

```
<xs:element name="Mode">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:enumeration value="Advanced" />
      <xs:enumeration value="Cleared" />
      <xs:enumeration value="List" />
      <xs:enumeration value="Range" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

## 2.9 PrimitiveType

The **PrimitiveType** element specifies the name of a data type.

The values and meanings for the **PrimitiveType** element are as follows.

Value	Meaning
Boolean	Specifies use of the <a href="#">Boolean</a> data type.
Byte	Specifies use of the <a href="#">Byte</a> data type.
DateTime	Specifies use of the <a href="#">DateTime</a> data type.
Decimal	Specifies use of the <a href="#">Decimal</a> data type.
Double	Specifies use of the <a href="#">Double</a> data type.
Guid	Specifies use of the <a href="#">Guid</a> data type.
Single	Specifies use of the <a href="#">Single</a> data type.
SByte	Specifies use of the <a href="#">SByte</a> data type.
Int16	Specifies use of the <a href="#">Int16</a> data type.
Int32	Specifies use of the <a href="#">Int32</a> data type.
Int64	Specifies use of the <a href="#">Int64</a> data type.
String	Specifies use of the <a href="#">String</a> data type.
Time	Specifies use of the <a href="#">Time</a> data type.

The following is the XSD for the **PrimitiveType** element.

```
<xs:simpleType name="PrimitiveType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Boolean" />
    <xs:enumeration value="Byte" />
    <xs:enumeration value="DateTime" />
    <xs:enumeration value="Decimal" />
    <xs:enumeration value="Double" />
    <xs:enumeration value="Guid" />
    <xs:enumeration value="Single" />
    <xs:enumeration value="SByte" />
    <xs:enumeration value="Int16" />
    <xs:enumeration value="Int32" />
    <xs:enumeration value="Int64" />
    <xs:enumeration value="String" />
    <xs:enumeration value="Time" />
  </xs:restriction>
</xs:simpleType>
```

## 2.10 FilterCondition

The **FilterCondition** element is an abstract element that represents a condition that is used to filter a set of values. In Report State documents, elements of type **FilterCondition** MUST specify one of the following types by using a type attribute as defined in [\[XMLSCHEMA1/2\]](#) section 2.6.1.

<b>Type</b>
<a href="#">SimpleFilterCondition</a>
<a href="#">CompoundFilterCondition</a>

The following is the XSD for the **FilterCondition** element.

```
<xs:complexType name="FilterCondition" abstract="true" />
```

## 2.11 SimpleFilterCondition

Applies to RDL Report State schemas 2011/01 [MSFT-RDLRS201101], 2012/01 [MSFT-RDLRS201201], and 2013/01 [MSFT-RDLRS201301]

The **SimpleFilterCondition** element specifies a type of [FilterCondition](#) that relates a **LeftExpression** and **RightExpression**.

**LeftExpression:** Specifies the [QueryExpression](#) that is on the left side of the **Operator**. The **LeftExpression** element MUST be specified and MUST NOT be specified more than once.

**Not:** Specifies whether this filter condition should be logically negated. The **Not** element is optional and MUST NOT be specified more than once.

**Operator:** Specifies the filter operation to perform on the **LeftExpression** and the **RightExpression**. The **Operator** element MUST be specified and MUST NOT be specified more than once.

The values and meanings for the **Operator** element are as follows.

Value	Meaning
Equal	The value of <b>LeftExpression</b> and the value of <b>RightExpression</b> are equal.
GreaterThan	The value of <b>LeftExpression</b> is greater than the value of <b>RightExpression</b> .
GreaterThanOrEqual	The value of <b>LeftExpression</b> is greater than or equal to the value of <b>RightExpression</b> .
LessThan	The value of <b>LeftExpression</b> is less than the value of <b>RightExpression</b> .
LessThanOrEqual	The value of <b>LeftExpression</b> is less than or equal to the value of <b>RightExpression</b> .
Contains	The value of <b>LeftExpression</b> contains the value of <b>RightExpression</b> .
StartsWith	The value of <b>LeftExpression</b> starts with the value of <b>RightExpression</b> .
DateTimeEqualToSecond	The value of <b>LeftExpression</b> equals the value of <b>RightExpression</b> when any sub-second precision of the value of <b>LeftExpression</b> is ignored. The <b>RightExpression</b> MUST be a QueryLiteralExpression.

In RDL Report State schema 2013/01 [MSFT-RDLRS201301], the following additional enumeration value can be specified for the **Operator** element.

Value	Meaning
AllValues	Represents an assertion that all values are needed for the <b>LeftExpression.Field</b> .

**RightExpression:** Specifies the **QueryExpression** element that is on the right side of the **Operator**. The **RightExpression** element is optional and MUST NOT be specified more than once.

The following is the XSD for the **SimpleFilterCondition** element.

```
<xs:complexType name="SimpleFilterCondition">
  <xs:complexContent>
    <xs:extension base="FilterCondition">
      <xs:sequence>
        <xs:element name="LeftExpression" type="QueryExpression" />
        <xs:element name="Not" type="xs:boolean" minOccurs="0" />
        <xs:element name="Operator">
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:enumeration value="Equal" />
              <xs:enumeration value="GreaterThan" />
              <xs:enumeration value="GreaterThanOrEqual" />
              <xs:enumeration value="LessThanOrEqual" />
              <xs:enumeration value="LessThan" />
              <xs:enumeration value="Contains" />
              <xs:enumeration value="StartsWith" />
              <xs:enumeration value="DateTimeEqualToSecond" />
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
        <xs:element name="RightExpression" type="QueryExpression" minOccurs="0" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

RDL Report State schema 2013/01 [MSFT-RDLRS201301] defines the **SimpleFilterCondition** element as follows.

```
<xs:complexType name="SimpleFilterCondition">
  <xs:complexContent>
    <xs:extension base="rs2011:FilterCondition">
      <xs:sequence>
        <xs:element name="LeftExpression" type="rs2011:QueryExpression" />
        <xs:element name="Not" type="xs:boolean" minOccurs="0" />
        <xs:element name="Operator">
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:enumeration value="Equal" />
              <xs:enumeration value="GreaterThan" />
              <xs:enumeration value="GreaterThanOrEqual" />
              <xs:enumeration value="LessThanOrEqual" />
              <xs:enumeration value="LessThan" />
              <xs:enumeration value="Contains" />
              <xs:enumeration value="StartsWith" />
              <xs:enumeration value="DateTimeEqualToSecond" />
              <xs:enumeration value="AllValues" />
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
        <xs:element name="RightExpression" type="rs2011:QueryExpression" minOccurs="0" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```



## 2.12 CompoundFilterCondition

The **CompoundFilterCondition** element specifies a type of [FilterCondition](#) that combines other **FilterCondition** elements.

**Conditions:** Specifies the ordered set of **FilterCondition** elements to be logically combined together. This **Conditions** element is optional and MUST NOT be specified more than once.

**Conditions.FilterCondition:** Specifies a **FilterCondition**. The **Conditions.FilterCondition** element is optional and can be specified more than once.

**Operator:** Specifies the desired logical combination of the **Conditions**. The **Operator** element is optional and MUST NOT be specified more than once.

The values and meanings for the **Operator** element are as follows.

Value	Meaning
All	All of the <b>Conditions</b> evaluate to true.
Any	Any of the <b>Conditions</b> evaluates to true.
NotAll	Any of the <b>Conditions</b> evaluates to false.
NotAny	All of the <b>Conditions</b> evaluate to false.

The following is the XSD for the **CompoundFilterCondition** element.

```
<xs:complexType name="CompoundFilterCondition">
  <xs:complexContent>
    <xs:extension base="FilterCondition">
      <xs:sequence>
        <xs:element name="Conditions" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="FilterCondition" type="FilterCondition"
                minOccurs="0" maxOccurs="unbounded" />
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="Operator" minOccurs="0">
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:enumeration value="All" />
              <xs:enumeration value="Any" />
              <xs:enumeration value="NotAll" />
              <xs:enumeration value="NotAny" />
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

## 2.13 ReportItems

The **ReportItems** element specifies an ordered set of [DataRegion](#) elements.

**DataRegion:** Specifies a **DataRegion**. This **DataRegion** element MUST be specified and can be specified more than once.

The following is the XSD for the **ReportItems** element.

```
<xs:complexType name="ReportItemsType">
  <xs:sequence>
    <xs:element name="DataRegion" type="DataRegionType" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

## 2.14 DataRegion

The **DataRegion** element specifies the state of a named data region in a report definition.

**Filters:** Specifies the container element for the [Filters](#). The **Filters** element MUST be specified and MUST NOT be specified more than once.

**Filters.Filters:** Specifies the **Filters** to use. The **Filters.Filters** element MUST be specified and MUST NOT be specified more than once.

**Name:** Specifies the name of the data region where the **Filters** are applied. The **Name** attribute MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **DataRegion** element.

```
<xs:complexType name="DataRegionType">
  <xs:sequence>
    <xs:element name="Filters">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Filters" type="FiltersType" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="Name" type="xs:string" />
</xs:complexType>
```

## 2.15 TypeUsage

The **TypeUsage** element specifies a particular use of a primitive data type.

**PrimitiveType:** Specifies the [PrimitiveType](#) element to use. The **PrimitiveType** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **TypeUsage** element.

```
<xs:complexType name="TypeUsage">
  <xs:sequence>
    <xs:element name="PrimitiveType" type="PrimitiveType" />
  </xs:sequence>
</xs:complexType>
```

## 2.16 QueryExpressionBinding

The **QueryExpressionBinding** element specifies a loop over the set of values described by the **Expression** element.

**Expression:** Specifies the set of values being enumerated. The **Expression** element MUST be specified and MUST NOT be specified more than once.

**VariableName:** Specifies the name used to refer to the current value while iterating over the set of values. The **VariableName** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **QueryExpressionBinding** element.

```
<xs:complexType name="QueryExpressionBinding">
  <xs:sequence>
    <xs:element name="Expression" type="QueryExpression"/>
    <xs:element name="VariableName" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

## 2.17 QueryExpressionList

The **QueryExpressionList** element specifies an ordered list of [QueryExpression](#) elements.

**QueryExpression:** Specifies a **QueryExpression** element. This element is optional and can be specified more than once.

The following is the XSD for the **QueryExpressionList** element.

```
<xs:complexType name="QueryExpressionList">
  <xs:sequence minOccurs="0" maxOccurs="unbounded">
    <xs:element name="QueryExpression" type="QueryExpression"/>
  </xs:sequence>
</xs:complexType>
```

## 2.18 QueryExpression

Applies to RDL Report State schemas 2011/01 [[MSFT-RDLRS201101](#)], 2012/01 [[MSFT-RDLRS201201](#)], and 2013/01 [[MSFT-RDLRS201301](#)]

**QueryExpression** is an abstract element. In Report State documents, **QueryExpression** elements MUST specify one of the following types by using a type attribute as defined in [XMLSCHEMA1/2](#) section 2.6.1.

In RDL Report State schema 2011/01 [[MSFT-RDLRS201101](#)], the following types are specified by the **QueryExpression** element.

Type
<a href="#">QueryCalculateExpression</a>
<a href="#">QueryFieldExpression</a>
<a href="#">QueryFunctionExpression</a>
<a href="#">QueryLiteralExpression</a>
<a href="#">QueryMeasureExpression</a>
<a href="#">QueryNullExpression</a>
<a href="#">QueryProjectExpression</a>
<a href="#">QueryScanExpression</a>
<a href="#">QueryVariableReferenceExpression</a>

Type
<a href="#">QdmEntityPlaceholderExpression</a>

In RDL Report State schema 2012/01 [MSFT-RDLRS201201], the following additional types are specified by the **QueryExpression** element.

Type
<a href="#">QueryHierarchyLevelExpression</a>

In RDL Report State schema 2013/01 [MSFT-RDLRS201301], the following additional types are specified by the **QueryExpression** element.

Type
<a href="#">QueryTypeCastExpression</a>

The following is the XML schema definition (XSD) for the **QueryExpression** element.

```
<xs:complexType name="QueryExpression" abstract="true" />
```

## 2.19 QueryCalculateExpression

The **QueryCalculateExpression** element specifies a [QueryExpression](#) element that should be evaluated in a context that is intersected with the specified filter expressions. The **QueryCalculateExpression** element is of type **QueryExpression**.

**Argument:** Specifies the **QueryExpression** element to be evaluated. The **Argument** element MUST be specified and MUST NOT be specified more than once.

**Filters:** Specifies the **QueryExpression** element that is used to filter data while evaluating to the argument. The [Filters](#) element is optional and MUST NOT be specified more than once.

The following is the XSD for the **QueryCalculateExpression** element.

```
<xs:complexType name="QueryCalculateExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Argument" type="QueryExpression" />
        <xs:element name="Filters" type="QueryExpressionList" minOccurs="0" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

## 2.20 QueryFieldExpression

The **QueryFieldExpression** element specifies a reference to a named value projected from the **Instance** [QueryExpression](#). The **QueryFieldExpression** element is of type **QueryExpression**.

**Field:** Specifies the name of the value to be retrieved. This element MUST be of type [PropertyReference](#). The **Field** element MUST be specified and MUST NOT be specified more than once.

**Instance:** Specifies the **QueryExpression** from which the value should be retrieved. The **Instance** element **MUST** be specified and **MUST NOT** be specified more than once.

The following is the XSD for the **QueryFieldExpression** element.

```
<xs:complexType name="QueryFieldExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Field" type="xs:string" />
        <xs:element name="Instance" type="QueryExpression" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

## 2.21 QueryFunctionExpression

The **QueryFunctionExpression** element specifies the function to invoke over a set of arguments as input. The **QueryFunctionExpression** element is of type [QueryExpression](#).

**FunctionName:** Specifies the name of the function to invoke. The **FunctionName** element **MUST** be specified and **MUST NOT** be specified more than once.

The values and meanings for the **FunctionName** element are as follows.

Value	Meaning
<b>Core.Sum</b>	Determines the aggregate summation of all values of the one and only argument. <b>QueryFunctionExpression.Arguments</b> <b>MUST</b> be of size one.
<b>Core.Count</b>	Determines the aggregate count of all non-null values of the one and only argument. <b>QueryFunctionExpression.Arguments</b> <b>MUST</b> be of size one.
<b>Core.DistinctCount</b>	Determines the aggregate count of distinct non-null values of the one and only argument. <b>QueryFunctionExpression.Arguments</b> <b>MUST</b> be of size one.
<b>Core.Average</b>	Determines the aggregate average of all values of the one and only argument. <b>QueryFunctionExpression.Arguments</b> <b>MUST</b> be of size one.
<b>Core.Min</b>	Determines the aggregate minimum of all values of the one and only argument. <b>QueryFunctionExpression.Arguments</b> <b>MUST</b> be of size one.
<b>Core.Max</b>	Determines the aggregate maximum of all values of the one and only argument. <b>QueryFunctionExpression.Arguments</b> <b>MUST</b> be of size one.

**Arguments:** Specifies a [QueryExpressionList](#) element as the input arguments to the function. The **Arguments** element **MUST** be specified and **MUST NOT** be specified more than once.

The following is the XSD for the **QueryFunctionExpression** element.

```
<xs:complexType name="QueryFunctionExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="FunctionName">
          <xs:simpleType name="FunctionName">
            <xs:restriction base="xs:string">
              <xs:enumeration value="Core.Sum" />
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

```

        <xs:enumeration value="Core.Count" />
        <xs:enumeration value="Core.DistinctCount" />
        <xs:enumeration value="Core.Average" />
        <xs:enumeration value="Core.Min" />
        <xs:enumeration value="Core.Max" />
    </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Arguments" type="QueryExpressionList" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

## 2.22 QueryLiteralExpression

The **QueryLiteralExpression** element specifies a typed constant value. The **QueryLiteralExpression** element is of type [QueryExpression](#).

**Value:** Specifies the value of the constant. The **Value** element MUST be specified and MUST NOT be specified more than once. In Report State documents, use of the **Value** element MUST specify one of the following types by using a type attribute as defined in [XMLSCHEMA1/2](#) section 2.6.1.

Value
<a href="#">Boolean</a>
<a href="#">Byte</a>
<a href="#">DateTime</a>
<a href="#">Decimal</a>
<a href="#">Double</a>
<a href="#">Guid</a>
<a href="#">Single</a>
<a href="#">SByte</a>
<a href="#">Int16</a>
<a href="#">Int32</a>
<a href="#">Int64</a>
<a href="#">String</a>
<a href="#">Time</a>

The following is the XSD for the **QueryLiteralExpression** element.

```

<xs:complexType name="QueryLiteralExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Value" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

## 2.23 QueryMeasureExpression

The **QueryMeasureExpression** element specifies a reference to a named property on an entity. The **QueryMeasureExpression** element is of type [QueryExpression](#).

**Measure:** Specifies the name of the property. The **Measure** element MUST be of type [PropertyReference](#). The **Measure** element MUST be specified and MUST NOT be specified more than once.

**Target:** Specifies the target entity containing the item described by the **Measure** element. The **Target** element MUST be of type [EntityReference](#). The **Target** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **QueryMeasureExpression** element.

```
<xs:complexType name="QueryMeasureExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Measure" type="xs:string" />
        <xs:element name="Target" type="xs:string" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

## 2.24 QueryNullExpression

The **QueryNullExpression** element specifies a null value in a data type. The **QueryNullExpression** element is of type [QueryExpression](#).

**Type:** Specifies the data type. The **Type** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **QueryNullExpression** element.

```
<xs:complexType name="QueryNullExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Type" type="TypeUsage" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

## 2.25 QueryProjectExpression

The **QueryProjectExpression** element specifies a type of [QueryExpression](#) element that produces a value for each item in the specified input.

**Input:** Specifies the input [QueryExpressionBinding](#). The **Input** element MUST be specified and MUST NOT be specified more than once.

**Projection:** Specifies the **QueryExpression** element that produces the value. The **Projection** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **QueryProjectExpression** element.

```

<xs:complexType name="QueryProjectExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Input" type="QueryExpressionBinding" />
        <xs:element name="Projection" type="QueryExpression" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

## 2.26 QueryScanExpression

The **QueryScanExpression** element specifies a scan over all rows in the target entity. The **QueryScanExpression** element is of type [QueryExpression](#).

**Target:** Specifies the entity. The **Target** element MUST be of type [EntityReference](#). The **Target** element MUST be specified and MUST NOT be specified more than once.

**ExcludeBlankRow:** Specifies a [Boolean](#) value that indicates whether blank rows should be excluded in the row scan. If omitted, blank rows are included. The **ExcludeBlankRow** element is optional and MUST NOT be specified more than once.

The following is the XSD for the **QueryScanExpression** element.

```

<xs:complexType name="QueryScanExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Target" type="xs:string" />
        <xs:element name="ExcludeBlankRow" type="xs:boolean" minOccurs="0" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

## 2.27 QueryVariableReferenceExpression

The **QueryVariableReferenceExpression** element specifies a reference to a named value. The **QueryVariableReferenceExpression** element is of type [QueryExpression](#).

**VariableName:** Specifies the name of the value. The **VariableName** element MUST be specified.

The following is the XSD for the **QueryVariableReferenceExpression** element.

```

<xs:complexType name="QueryVariableReferenceExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="VariableName" type="xs:string" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

## 2.28 QdmEntityPlaceholderExpression

The **QdmEntityPlaceholderExpression** element specifies a reference to an entity. The **QdmEntityPlaceholderExpression** element is of type [QueryExpression](#).



**Target:** Specifies the entity. The **Target** element MUST be of type **EntityReference**. The **Target** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **QdmEntityPlaceholderExpression** element.

```
<xs:complexType name="QdmEntityPlaceholderExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Target" type="xs:string" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

## 2.29 QueryHierarchyLevelExpression

Applies to RDL Report State schema 2012/01 [\[MSFT-RDLRS201201\]](#)

The **QueryHierarchyLevelExpression** element specifies a reference to a named hierarchy level within a hierarchy on an entity. The **QueryHierarchyLevelExpression** element is of type [QueryExpression](#).

**Hierarchy:** Specifies the name of the hierarchy to which the hierarchy level belongs. This element MUST be of type [String](#). The **Hierarchy** element MUST be specified and MUST NOT be specified more than once.

**HierarchyLevel:** Specifies the name of the hierarchy level to be used for this expression. This element MUST be of type **String**. The **HierarchyLevel** element MUST be specified and MUST NOT be specified more than once.

**Instance:** Specifies the **QueryExpression** from which the value should be retrieved. The **Instance** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **QueryHierarchyLevelExpression** element.

```
<xs:complexType name="QueryHierarchyLevelExpression">
  <xs:complexContent>
    <xs:extension base="rs2011:QueryExpression">
      <xs:sequence>
        <xs:element name="Hierarchy" type="xs:string" />
        <xs:element name="HierarchyLevel" type="xs:string" />
        <xs:element name="Instance" type="rs2011:QueryExpression" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

## 2.30 QueryTypeCastExpression

Applies to RDL Report State schema 2013/01 [\[MSFT-RDLRS201301\]](#)

The **QueryTypeCastExpression** element specifies a type of [QueryExpression](#) element whose data type is cast to the specified **Data Type**. The **QueryTypeCastExpression** element is of type [QueryExpression](#).

**Data Type:** Specifies the data type to which the input can be casted. **Data Type** is of type [PrimitiveType](#). The **Data Type** element MUST be specified and MUST NOT be specified more than once.

**Input:** Specifies the input QueryExpression. The **Input** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **QueryTypeCastExpression** element.

```
<xs:complexType name="QueryTypeCastExpression">
  <xs:complexContent>
    <xs:extension base="rs2011:QueryExpression">
      <xs:sequence>
        <xs:element name="DataType" type="rs2011:PrimitiveType" />
        <xs:element name="Input" type="rs2011:QueryExpression" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

### 2.31 ReportSlicerState

The **ReportSlicerState** element specifies a [CompoundFilterCondition](#) to be applied to items within a report section [\[MS-RDL\]](#). The **ReportSlicerState** element is not used directly within a Report State document.

**CompoundFilterCondition:** Specifies the filter condition to apply to items within a **report section**. The **CompoundFilterCondition** element MUST be specified and MUST NOT be specified more than once.

The following is the XSD for the **ReportSlicerState** element.

```
<xs:element name="ReportSlicerState">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="CompoundFilterCondition" type="CompoundFilterCondition"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

## 3 Structure Examples

The following sections provide examples of the structures that are defined in the Report State file format.

### 3.1 Report State

The following is an example of a Report State document with two [ReportSection](#) elements. The first **ReportSection** contains two section filters and two [DataRegion](#) elements with filters. The second section contains a single section filter.

```
<?xml version="1.0" encoding="utf-8"?>
<ReportState xmlns="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate">
  <FilterAreaVisibility>Expanded</FilterAreaVisibility>
  <Theme>Theme1</Theme>
  <ReportSections>
    <ReportSection>
      <SectionFilters>
        <Filters
xmlns="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate">
          <Filter Type="String">
            <Mode>Basic</Mode>
            <Operand>
              <QueryExpression xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
i:type="QueryFieldExpression">
                <Field>Genre</Field>
                <Instance i:type="QdmEntityPlaceholderExpression">
                  <Target>Sandbox.Media</Target>
                </Instance>
              </QueryExpression>
            </Operand>
            <Condition>
              <CompoundFilterCondition xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
                <Conditions>
                  <FilterCondition i:type="SimpleFilterCondition">
                    <LeftExpression i:type="QueryFieldExpression">
                      <Field>Genre</Field>
                      <Instance i:type="QdmEntityPlaceholderExpression">
                        <Target>Sandbox.Media</Target>
                      </Instance>
                    </LeftExpression>
                    <Operator>Equal</Operator>
                    <RightExpression i:type="QueryLiteralExpression">
                      <Value xmlns:d5p1="http://www.w3.org/2001/XMLSchema"
i:type="d5p1:string">Action/Adventure</Value>
                    </RightExpression>
                  </FilterCondition>
                </Conditions>
                <Operator>Any</Operator>
              </CompoundFilterCondition>
            </Condition>
          </Filter>
          <Filter Type="String">
            <Mode>Cleared</Mode>
            <Operand>
              <QueryExpression xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
i:type="QueryFieldExpression">
                <Field>Color</Field>
                <Instance i:type="QdmEntityPlaceholderExpression">
                  <Target>Sandbox.Media</Target>
                </Instance>
              </QueryExpression>
            </Operand>
          </Filter>
        </Filters>
      </SectionFilters>
    </ReportSection>
  </ReportSections>
</ReportState>
```

```

<ReportItems>
  <DataRegion Name="Tablix1">
    <Filters>
      <Filters
xmlns="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate">
        <Filter Type="Decimal">
          <Mode>Advanced</Mode>
          <IsMeasure />
          <Operand>
            <QueryExpression xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
i:type="QueryCalculateExpression">
              <Argument i:type="QueryFunctionExpression">
                <FunctionName>Core.Sum</FunctionName>
                <Arguments>
                  <QueryExpression i:type="QueryProjectExpression">
                    <Input>
                      <Expression i:type="QueryScanExpression">
                        <Target>Sandbox.Media</Target>
                      </Expression>
                      <VariableName>Media</VariableName>
                    </Input>
                    <Projection i:type="QueryFieldExpression">
                      <Field>Gross</Field>
                      <Instance i:type="QueryVariableReferenceExpression">
                        <VariableName>Media</VariableName>
                      </Instance>
                    </Projection>
                  </QueryExpression>
                </Arguments>
              </Argument>
            </QueryExpression>
          </Operand>
          <Condition>
            <CompoundFilterCondition xmlns:i="http://www.w3.org/2001/XMLSchema-
instance">
              <Conditions>
                <FilterCondition i:type="SimpleFilterCondition">
                  <LeftExpression i:type="QueryCalculateExpression">
                    <Argument i:type="QueryFunctionExpression">
                      <FunctionName>Core.Sum</FunctionName>
                      <Arguments>
                        <QueryExpression i:type="QueryProjectExpression">
                          <Input>
                            <Expression i:type="QueryScanExpression">
                              <Target>Sandbox.Media</Target>
                            </Expression>
                            <VariableName>Media</VariableName>
                          </Input>
                          <Projection i:type="QueryFieldExpression">
                            <Field>Gross</Field>
                            <Instance i:type="QueryVariableReferenceExpression">
                              <VariableName>Media</VariableName>
                            </Instance>
                          </Projection>
                        </QueryExpression>
                      </Arguments>
                    </Argument>
                  </LeftExpression>
                  <Operator>GreaterThanOrEqual</Operator>
                  <RightExpression i:type="QueryLiteralExpression">
                    <Value xmlns:d5p1="http://www.w3.org/2001/XMLSchema"
i:type="d5p1:decimal">1</Value>
                  </RightExpression>
                </FilterCondition>
                <FilterCondition i:type="SimpleFilterCondition">
                  <LeftExpression i:type="QueryCalculateExpression">
                    <Argument i:type="QueryFunctionExpression">
                      <FunctionName>Core.Sum</FunctionName>
                      <Arguments>

```

```

        <QueryExpression i:type="QueryProjectExpression">
          <Input>
            <Expression i:type="QueryScanExpression">
              <Target>Sandbox.Media</Target>
            </Expression>
            <VariableName>Media</VariableName>
          </Input>
          <Projection i:type="QueryFieldExpression">
            <Field>Gross</Field>
            <Instance i:type="QueryVariableReferenceExpression">
              <VariableName>Media</VariableName>
            </Instance>
          </Projection>
        </QueryExpression>
      </Arguments>
    </Argument>
  </LeftExpression>
  <Operator>LessThan</Operator>
  <RightExpression i:type="QueryLiteralExpression">
    <Value xmlns:d5p1="http://www.w3.org/2001/XMLSchema"
i:type="d5p1:decimal">1000000000</Value>
  </RightExpression>
</FilterCondition>
</Conditions>
</CompoundFilterCondition>
</Condition>
</Filter>
</Filters>
</Filters>
</DataRegion>
<DataRegion Name="Tablix3">
  <Filters>
    <Filters
xmlns="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate">
      <Filter Type="String">
        <Mode>Basic</Mode>
        <Operand>
          <QueryExpression xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
i:type="QueryFieldExpression">
            <Field>Color</Field>
            <Instance i:type="QdmEntityPlaceholderExpression">
              <Target>Sandbox.Media</Target>
            </Instance>
          </QueryExpression>
        </Operand>
      <Condition>
        <CompoundFilterCondition xmlns:i="http://www.w3.org/2001/XMLSchema-
instance">
          <Conditions>
            <FilterCondition i:type="SimpleFilterCondition">
              <LeftExpression i:type="QueryFieldExpression">
                <Field>Color</Field>
                <Instance i:type="QdmEntityPlaceholderExpression">
                  <Target>Sandbox.Media</Target>
                </Instance>
              </LeftExpression>
              <Operator>Equal</Operator>
              <RightExpression i:type="QueryLiteralExpression">
                <Value xmlns:d5p1="http://www.w3.org/2001/XMLSchema"
i:type="d5p1:string">Red</Value>
              </RightExpression>
            </FilterCondition>
          </Conditions>
          <Operator>Any</Operator>
        </CompoundFilterCondition>
      </Condition>
    </Filter>
  </Filters>
</Filters>

```

```

        </DataRegion>
    </ReportItems>
</ReportSection>
<ReportSection>
    <SectionFilters>
        <Filters
xmlns="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate">
            <Filter Type="Int64">
                <Mode>Basic</Mode>
                <Operand>
                    <QueryExpression xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
i:type="QueryFieldExpression">
                        <Field>Duration</Field>
                        <Instance i:type="QdmEntityPlaceholderExpression">
                            <Target>Sandbox.Media</Target>
                        </Instance>
                    </QueryExpression>
                </Operand>
            <Condition>
                <CompoundFilterCondition xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
                    <Conditions>
                        <FilterCondition i:type="SimpleFilterCondition">
                            <LeftExpression i:type="QueryFieldExpression">
                                <Field>Duration</Field>
                                <Instance i:type="QdmEntityPlaceholderExpression">
                                    <Target>Sandbox.Media</Target>
                                </Instance>
                            </LeftExpression>
                            <Operator>GreaterThanOrEqual</Operator>
                            <RightExpression i:type="QueryLiteralExpression">
                                <Value xmlns:d5p1="http://www.w3.org/2001/XMLSchema"
i:type="d5p1:long">8049</Value>
                            </RightExpression>
                        </FilterCondition>
                    </Conditions>
                </CompoundFilterCondition>
            </Condition>
        </Filter>
    </Filters>
</SectionFilters>
</ReportSection>
</ReportSections>
</ReportState>

```

## **4 Security**

### **4.1 Security Considerations for Implementers**

None.

### **4.2 Index of Security Fields**

None.

## 5 Appendix A: Full XML Schema

For ease of implementation, the following sections provide the full XML schemas for this protocol.

Schema name	Prefix	Section
RDL Report State Schema for Version 2011/01	xs:	<a href="#">5.1.1</a>
RDL Report State Schema for Version 2012/01	xs:	<a href="#">5.1.2</a>
RDL Report State Schema for Version 2013/01	xs:	<a href="#">5.1.3</a>
Serialization Schema	xs:	<a href="#">5.2</a>

### 5.1 RDL Report State Schema

The following sections contain the full RDL Report State XML schemas for versions 2011/01, 2012/01, and 2013/01. Note that the RDL Report State XML schema for version 2012/01 and 2013/01 are not standalone schemas, but are dependent on the RDL Report State XML schema for version 2011/01.

#### 5.1.1 RDL Report State Schema for Version 2011/01

```
<?xml version="1.0" encoding="utf-8"?>
<!-- Copyright (c) Microsoft Corporation. All rights reserved. -->
<xs:schema
targetNamespace="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate"
elementFormDefault="qualified"
xmlns="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:rs2012="http://schemas.microsoft.com/sqlserver/reporting/2012/01/reportstate"
xmlns:rs2013="http://schemas.microsoft.com/sqlserver/reporting/2013/01/reportstate"
version="1.0">

  <xs:import namespace="http://schemas.microsoft.com/sqlserver/reporting/2012/01/reportstate"
  />
  <xs:import namespace="http://schemas.microsoft.com/sqlserver/reporting/2013/01/reportstate"
  />

  <xs:element name="ReportState">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="FilterAreaVisibility" minOccurs="0">
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:enumeration value="Collapsed"/>
              <xs:enumeration value="Expanded"/>
              <xs:enumeration value="Hidden"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
        <xs:element name="Theme" minOccurs="0"/>
        <xs:element name="ReportSections" minOccurs="0" type="ReportSectionsType" />
        <xs:element ref="rs2013:ReportFilters" minOccurs="0" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>

  <xs:complexType name="ReportSectionsType">
    <xs:sequence>
      <xs:element name="ReportSection" type="ReportSectionType" minOccurs="0"
maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</pre>
```



```

<xs:complexType name="ReportSectionType">
  <xs:sequence>
    <xs:element name="SectionFilters" type="SectionFiltersType" minOccurs="0" />
    <xs:element name="ReportItems" type="ReportItemsType" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="SectionFiltersType">
  <xs:sequence>
    <xs:element name="Filters" type="FiltersType" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="FiltersType">
  <xs:sequence>
    <xs:element name="Filter" type="FilterType" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="FilterType">
  <xs:sequence>
    <xs:choice>
      <xs:element name="Mode">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:enumeration value="Advanced" />
            <xs:enumeration value="Basic" />
            <xs:enumeration value="Cleared" />
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element ref="rs2012:Mode" />
    </xs:choice>
    <xs:element name="IsMeasure" minOccurs="0" />
    <xs:element ref="rs2012:IsDrilldownFilter" minOccurs="0" />
    <xs:element name="Operand">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="QueryExpression" type="QueryExpression"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Condition" minOccurs="0">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="CompoundFilterCondition" type="CompoundFilterCondition"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="Type" type="PrimitiveType" />
</xs:complexType>

<xs:simpleType name="PrimitiveType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Boolean" />
    <xs:enumeration value="Byte" />
    <xs:enumeration value="DateTime" />
    <xs:enumeration value="Decimal" />
    <xs:enumeration value="Double" />
    <xs:enumeration value="Guid" />
    <xs:enumeration value="Single" />
    <xs:enumeration value="SByte" />
    <xs:enumeration value="Int16" />
    <xs:enumeration value="Int32" />
    <xs:enumeration value="Int64" />
    <xs:enumeration value="String" />
    <xs:enumeration value="Time" />
  </xs:restriction>

```

```

</xs:simpleType>

<xs:complexType name="FilterCondition" abstract="true" />

<xs:complexType name="SimpleFilterCondition">
  <xs:complexContent>
    <xs:extension base="FilterCondition">
      <xs:sequence>
        <xs:element name="LeftExpression" type="QueryExpression" />
        <xs:element name="Not" type="xs:boolean" minOccurs="0" />
        <xs:element name="Operator">
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:enumeration value="Equal" />
              <xs:enumeration value="GreaterThan" />
              <xs:enumeration value="GreaterThanOrEqual" />
              <xs:enumeration value="LessThanOrEqual" />
              <xs:enumeration value="LessThan" />
              <xs:enumeration value="Contains" />
              <xs:enumeration value="StartsWith" />
              <xs:enumeration value="DateTimeEqualToSecond" />
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
        <xs:element name="RightExpression" type="QueryExpression" minOccurs="0" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="CompoundFilterCondition">
  <xs:complexContent>
    <xs:extension base="FilterCondition">
      <xs:sequence>
        <xs:element name="Conditions" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="FilterCondition" type="FilterCondition" minOccurs="0"
maxOccurs="unbounded" />
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="Operator" minOccurs="0">
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:enumeration value="All" />
              <xs:enumeration value="Any" />
              <xs:enumeration value="NotAll" />
              <xs:enumeration value="NotAny" />
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="ReportItemsType">
  <xs:sequence>
    <xs:element name="DataRegion" type="DataRegionType" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="DataRegionType">
  <xs:sequence>
    <xs:element name="Filters">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Filters" type="FiltersType" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:sequence>
<xs:attribute name="Name" type="xs:string" />
</xs:complexType>

<xs:complexType name="TypeUsage">
    <xs:sequence>
        <xs:element name="PrimitiveType" type="PrimitiveType" />
    </xs:sequence>
</xs:complexType>

<xs:complexType name="QueryExpressionBinding">
    <xs:sequence>
        <xs:element name="Expression" type="QueryExpression"/>
        <xs:element name="VariableName" type="xs:string" />
    </xs:sequence>
</xs:complexType>

<xs:complexType name="QueryExpressionList">
    <xs:sequence minOccurs="0" maxOccurs="unbounded">
        <xs:element name="QueryExpression" type="QueryExpression"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="QueryExpression" abstract="true" />

<xs:complexType name="QueryCalculateExpression">
    <xs:complexContent>
        <xs:extension base="QueryExpression">
            <xs:sequence>
                <xs:element name="Argument" type="QueryExpression" />
                <xs:element name="Filters" type="QueryExpressionList" minOccurs="0" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

<xs:complexType name="QueryFieldExpression">
    <xs:complexContent>
        <xs:extension base="QueryExpression">
            <xs:sequence>
                <xs:element name="Field" type="xs:string" />
                <xs:element name="Instance" type="QueryExpression" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

<xs:complexType name="QueryFunctionExpression">
    <xs:complexContent>
        <xs:extension base="QueryExpression">
            <xs:sequence>
                <xs:element name="FunctionName">
                    <xs:simpleType>
                        <xs:restriction base="xs:string">
                            <xs:enumeration value="Core.Sum" />
                            <xs:enumeration value="Core.Count" />
                            <xs:enumeration value="Core.DistinctCount" />
                            <xs:enumeration value="Core.Average" />
                            <xs:enumeration value="Core.Min" />
                            <xs:enumeration value="Core.Max" />
                        </xs:restriction>
                    </xs:simpleType>
                </xs:element>
                <xs:element name="Arguments" type="QueryExpressionList" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

```

```

    </xs:complexContent>
</xs:complexType>

<xs:complexType name="QueryLiteralExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Value" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="QueryMeasureExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Measure" type="xs:string" />
        <xs:element name="Target" type="xs:string" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="QueryNullExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Type" type="TypeUsage" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="QueryProjectExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Input" type="QueryExpressionBinding" />
        <xs:element name="Projection" type="QueryExpression" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="QueryScanExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="Target" type="xs:string" />
        <xs:element name="ExcludeBlankRow" type="xs:boolean" minOccurs="0" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="QueryVariableReferenceExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">
      <xs:sequence>
        <xs:element name="VariableName" type="xs:string" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="QdmEntityPlaceholderExpression">
  <xs:complexContent>
    <xs:extension base="QueryExpression">

```

```

        <xs:sequence>
          <xs:element name="Target" type="xs:string" />
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

  <xs:element name="ReportSlicerState">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="CompoundFilterCondition" type="CompoundFilterCondition"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:schema>

```

### 5.1.2 RDL Report State Schema for Version 2012/01

Note that the RDLRS XML schema for version 2012/01 is not a standalone schema, but is dependent on the RDLRS XML schema for version 2011/01 [\[MSFT-RDLRS201101\]](#).

```

<?xml version="1.0" encoding="utf-8"?>
<!-- Copyright (c) Microsoft Corporation. All rights reserved. -->
<xs:schema
targetNamespace="http://schemas.microsoft.com/sqlserver/reporting/2012/01/reportstate"
elementFormDefault="qualified"
xmlns="http://schemas.microsoft.com/sqlserver/reporting/2012/01/reportstate"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:rs2011="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate"
version="1.0">

  <xs:import namespace="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate"
/>

  <xs:element name="IsDrilldownFilter" type="xs:boolean"/>

  <xs:complexType name="QueryHierarchyLevelExpression">
    <xs:complexContent>
      <xs:extension base="rs2011:QueryExpression">
        <xs:sequence>
          <xs:element name="Hierarchy" type="xs:string" />
          <xs:element name="HierarchyLevel" type="xs:string" />
          <xs:element name="Instance" type="rs2011:QueryExpression" />
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

  <xs:element name="Mode">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="Advanced" />
        <xs:enumeration value="Cleared" />
        <xs:enumeration value="List" />
        <xs:enumeration value="Range" />
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
</xs:schema>

```

### 5.1.3 RDL Report State Schema for Version 2013/01

Note that the RDLRS XML schema for version 2013/01 is not a standalone schema, but is dependent on the RDLRS XML schema for version 2011/01 [\[MSFT-RDLRS201101\]](#).

```
<?xml version="1.0" encoding="utf-8"?>
<!-- Copyright (c) Microsoft Corporation. All rights reserved. -->
<xs:schema
targetNamespace="http://schemas.microsoft.com/sqlserver/reporting/2013/01/reportstate"
  elementFormDefault="qualified"
  xmlns="http://schemas.microsoft.com/sqlserver/reporting/2013/01/reportstate"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:rs2011="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate"
  version="1.0">

  <xs:import namespace="http://schemas.microsoft.com/sqlserver/reporting/2011/01/reportstate"
  />

  <xs:element name="ReportFilters" type="ReportFiltersType" />

  <xs:complexType name="ReportFiltersType">
    <xs:sequence>
      <xs:element name="Filters" type="rs2011:FiltersType" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="QueryTypeCastExpression">
    <xs:complexContent>
      <xs:extension base="rs2011:QueryExpression">
        <xs:sequence>
          <xs:element name="DataType" type="rs2011:PrimitiveType" />
          <xs:element name="Input" type="rs2011:QueryExpression" />
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

  <xs:complexType name="SimpleFilterCondition">
    <xs:complexContent>
      <xs:extension base="rs2011:FilterCondition">
        <xs:sequence>
          <xs:element name="LeftExpression" type="rs2011:QueryExpression" />
          <xs:element name="Not" type="xs:boolean" minOccurs="0" />
          <xs:element name="Operator">
            <xs:simpleType>
              <xs:restriction base="xs:string">
                <xs:enumeration value="Equal" />
                <xs:enumeration value="GreaterThan" />
                <xs:enumeration value="GreaterThanOrEqual" />
                <xs:enumeration value="LessThanOrEqual" />
                <xs:enumeration value="LessThan" />
                <xs:enumeration value="Contains" />
                <xs:enumeration value="StartsWith" />
                <xs:enumeration value="DateTimeEqualToSecond" />
                <xs:enumeration value="AllValues" />
              </xs:restriction>
            </xs:simpleType>
          </xs:element>
          <xs:element name="RightExpression" type="rs2011:QueryExpression" minOccurs="0" />
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

</xs:schema>
```

## 5.2 Serialization Schema

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema attributeFormDefault="qualified"
  elementFormDefault="qualified"
  targetNamespace =
    "http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/">

  <!-- Top-level elements for primitive types. -->
  <xs:element name="anyType" nillable="true" type="xs:anyType"/>
  <xs:element name="anyURI" nillable="true" type="xs:anyURI"/>
  <xs:element name="base64Binary"
    nillable="true" type="xs:base64Binary"/>
  <xs:element name="boolean" nillable="true" type="xs:boolean"/>
  <xs:element name="byte" nillable="true" type="xs:byte"/>
  <xs:element name="dateTime" nillable="true" type="xs:dateTime"/>
  <xs:element name="decimal" nillable="true" type="xs:decimal"/>
  <xs:element name="double" nillable="true" type="xs:double"/>
  <xs:element name="float" nillable="true" type="xs:float"/>
  <xs:element name="int" nillable="true" type="xs:int"/>
  <xs:element name="long" nillable="true" type="xs:long"/>
  <xs:element name="QName" nillable="true" type="xs:QName"/>
  <xs:element name="short" nillable="true" type="xs:short"/>
  <xs:element name="string" nillable="true" type="xs:string"/>
  <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte"/>
  <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt"/>
  <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong"/>
  <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort"/>

  <!-- Primitive types introduced for certain .NET simple types. -->
  <xs:element name="char" nillable="true" type="tns:char"/>
  <xs:simpleType name="char">
    <xs:restriction base="xs:int"/>
  </xs:simpleType>

  <!-- xs:duration is restricted to an ordered value space,
  to map to System.TimeSpan -->
  <xs:element name="duration" nillable="true" type="tns:duration"/>
  <xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
      <xs:pattern
        value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?"/>
      <xs:minInclusive value="-P10675199DT2H48M5.4775808S"/>
      <xs:maxInclusive value="P10675199DT2H48M5.4775807S"/>
    </xs:restriction>
  </xs:simpleType>

  <xs:element name="guid" nillable="true" type="tns:guid"/>
  <xs:simpleType name="guid">
    <xs:restriction base="xs:string">
      <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-
        [\da-fA-F]{4}-[\da-fA-F]{12}"/>
    </xs:restriction>
  </xs:simpleType>

  <!-- This is used for schemas exported from ISerializable type. -->
  <xs:attribute name="FactoryType" type="xs:QName"/>
</xs:schema>
```

## 6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

- Microsoft SQL Server 2012
- Microsoft SQL Server 2014
- Microsoft SQL Server 2016

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

<1> [Section 1.6](#): The following table describes RDLRS versions of Report Definition Language Report State (RDLRS) and which products support each version. Newer releases of Reporting Services support previous RDLRS versions. For example, Microsoft SQL Server 2016 Reporting Services supports all previous RDLRS versions.

RDLRS schema version	Release introduced
RDLRS 2011/01	SQL Server 2012 Reporting Services
RDLRS 2012/01	Microsoft SQL Server 2012 Service Pack 1 (SP1) Reporting Services
RDLRS 2013/01	SQL Server 2012 SP1 Reporting Services



## 7 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">6</a> Appendix B: Product Behavior	Added SQL Server 2016 to the list of applicable products.	Y	Content update.

## 8 Index

### A

[Applicability](#) 7

### C

[Change tracking](#) 41  
[common Report State types](#) 8  
[CompoundFilterCondition element](#) 17  
[CSDL document](#) 6

### D

[DataRegion element](#) 18

### E

[Examples](#) 27  
    [Report State](#) 27  
[extensible fields](#) 7

### F

[Fields - security index](#) 31  
[Fields - vendor-extensible](#) 7  
[Filter element](#) 12  
[filter metadata](#) 7  
[FilterCondition element](#) 14  
[Filters element](#) 11  
[Full XML schema](#) 32

### G

[Glossary](#) 5

### I

[Implementer - security considerations](#) 31  
[Index of security fields](#) 31  
[Informative references](#) 6  
[Introduction](#) 5

### L

[Localization](#) 7

### N

[namespace](#) 6  
[Normative references](#) 5

### O

[Overview \(synopsis\)](#) 6

### P

[PrimitiveType element](#) 14  
[Product behavior](#) 40

### Q

[OdmEntityPlaceholderExpression element](#) 24  
[QueryCalculateExpression element](#) 20  
[QueryExpression element](#) 19  
[QueryExpressionBinding element](#) 18  
[QueryExpressionList element](#) 19  
[QueryFieldExpression element](#) 20  
[QueryFunctionExpression element](#) 21  
[QueryHierarchyLevelExpression element](#) 25  
[QueryLiteralExpression element](#) 22  
[QueryMeasureExpression element](#) 23  
[QueryNullExpression element](#) 23  
[QueryProjectExpression element](#) 23  
[QueryScanExpression element](#) 24  
[QueryVariableReferenceExpression element](#) 24

### R

RDL  
    [data region](#) 6  
    [report section](#) 6  
    [ReportSlicerState](#) 6  
[RDL Report State schema for version 2011/01](#) 32

### RDLRS

[about](#) 6  
[extensions](#) 7  
[filter metadata](#) 7  
[schema versions](#) 7

### References

[informative](#) 6  
[normative](#) 5  
[Relationship to protocols and other structures](#) 6  
[Report State example](#) 27  
[ReportItems element](#) 17  
[ReportSection element](#) 11  
[ReportSections element](#) 10  
[ReportSlicerState element](#) 26  
[ReportState element](#) 10

### S

[schema versions](#) 7  
[SectionFilters element](#) 11  
Security  
    [field index](#) 31  
    [implementer considerations](#) 31  
[SimpleFilterCondition element](#) 15

### T

[Tracking changes](#) 41  
[TypeUsage element](#) 18

### V

[Vendor-extensible fields](#) 7  
[Versioning](#) 7

### X

[XML Namespace](#) 6  
[XML schema](#) 32  
[XML schema versions](#) 7