

[MS-RSWSRE2005-Diff]:

Report Server Web Service for Report Execution: ReportExecution2005

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, [IDL's](#), or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, [email-mail](#) addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

| Date | Revision History | Revision Class | Comments |
|---------------|------------------|----------------|--|
| 08/078/7/2009 | 0.1 | Major | First release. |
| 11/066/2009 | 0.1.1 | Editorial | Revised/Changed language and edited/formatting in the technical content. |
| 03/053/5/2010 | 1.0 | Major | Updated and revised the technical content. |
| 044/21/2010 | 1.0.1 | Editorial | Revised/Changed language and edited/formatting in the technical content. |
| 06/046/4/2010 | 1.1 | Minor | Updated/Clarified the meaning of the technical content. |
| 09/039/3/2010 | 1.2 | Minor | Clarified the meaning of the technical content. |
| 02/092/9/2011 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 07/077/7/2011 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 11/033/2011 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 041/19/2012 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 022/23/2012 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 033/27/2012 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 055/24/2012 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 066/29/2012 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 077/16/2012 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 10/088/2012 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 10/23/2012 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 033/26/2013 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 066/11/2013 | 1.2 | No change/None | No changes to the meaning, language, or formatting of the technical content. |
| 08/088/8/2013 | 1.2 | No | No changes to the meaning, language, or formatting of |

| Date | Revision History | Revision Class | Comments |
|--------------------------|------------------|---|---|
| | | changeNone | the technical content. |
| 12/ 055 /2013 | 1.2 | No change None | No changes to the meaning, language, or formatting of the technical content. |
| 022 /11/2014 | 2.0 | Major | Significantly changed Updated and revised the technical content. |
| 055 /20/2014 | 2.0 | No change None | No changes to the meaning, language, or formatting of the technical content. |
| 5/10/2016 | 3.0 | Major | <u>Significantly changed the technical content.</u> |

Table of Contents

| | | |
|------------------|---|-----------|
| 1 | Introduction | 5 |
| 1.1 | Glossary..... | 5 |
| References | | 5 |
| 1.2 | 5 | |
| 1.2.1 | Normative References | 6 |
| 1.2.1.1 | Prescriptive API References | 6 |
| 1.2.2 | Informative References | 6 |
| 1.3 | Overview..... | 7 |
| 1.4 | Relationship to Other Protocols | 9 |
| 1.5 | Prerequisites/Preconditions..... | 9 |
| 1.6 | Applicability Statement | 9 |
| 1.7 | Versioning and Capability Negotiation | 9 |
| 1.8 | Vendor-Extensible Fields | 9 |
| 1.9 | Standards Assignments..... | 9 |
| 2 | Messages..... | 10 |
| 2.1 | Transport | 10 |
| 2.2 | Messages | 10 |
| 2.2.1 | Namespaces..... | 11 |
| 2.2.2 | Methods | 12 |
| 2.2.3 | Types..... | 14 |
| 2.2.4 | SOAP Headers | 15 |
| 3 | Appendix A: Full WSDL | 16 |
| 4 | Appendix B: Product Behavior | 59 |
| 5 | Change Tracking | 61 |
| 6 | Index..... | 63 |

1 1—Introduction

The Report Server Web Service for Report Execution: ReportExecution2005 protocol is an API protocol that is provided by the ReportExecution2005 web service. This web service is used for running and navigating reports on a **report server**.

1.1 Glossary

The Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms are defined in [MS-GLOS]:

SOAP header
SOAP message
WSDL message
WSDL operation
XML namespace

The following terms are specific to this document:

report server: A location on the network to which clients can connect by using SOAP over HTTP or SOAP over HTTPS to publish, manage, and execute reports.

SOAP header: A mechanism for implementing extensions to a **SOAP message** in a decentralized manner without prior agreement between the communicating parties. See [SOAP1.2-1/2007] section 5.2 for more information.

SOAP message: An XML document consisting of a mandatory SOAP envelope, an optional **SOAP header**, and a mandatory SOAP body. See [SOAP1.2-1/2007] section 5 for more information.

WSDL message: An abstract, typed definition of the data that is communicated during a **WSDL operation** [WSDL]. Also, an element that describes the data being exchanged between web service providers and clients.

WSDL operation: A single action or function of a web service. The execution of a WSDL operation typically requires the exchange of messages between the service requestor and the service provider.

XML namespace: A collection of names that is used to identify elements, types, and attributes in XML documents identified in a URI reference [RFC3986]. A combination of XML namespace and local name allows XML documents to use elements, types, and attributes that have the same names but come from different sources. For more information, see [XMLNS-2ED].

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as describeddefined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2 References

Links to a document in the Microsoft Open Specifications documentation do not include a publishing year because links are to the latest library point to the correct section in the most recently published version of the referenced document. However, because individual documents, which in the library are not updated frequently. References to other documents include a publishing year when one is

available at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

1.1.1.1.2.1 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.rfc-editor.org/rfc/rfc2616.txt>

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.rfc-editor.org/rfc/rfc2818.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2] See [SOAP1.2-1/2007].

[SOAP1.2-1/2007] Gudgin, M., Hadley, M., Mendelsohn, N., et al., Eds., "SOAP Version 1.2 Part 1: Messaging Framework (Second Edition)", W3C Recommendation [27](#), April 2007, <http://www.w3.org/TR/2007/REC-soap12-part1-20070427/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLNS3] See [XMLNS].

[XMLSHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmleschema-1-20010502/>

[XMLSHEMA2] Biron, P.V., Ed. and Malhotra, A., EdsEd., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmleschema-2-20010502/>

1.1.1.1.2.1.1 1.2.1.1 Prescriptive API References

[MSDN-SQLRSRE2005] Microsoft Corporation, "ReportExecution2005 Namespace", <http://msdn.microsoft.com/en-us/library/reportexecution2005.aspx>

1.1.21.2.2 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "Windows Protocols Master Glossary".

[MSDN-EXHC] Microsoft Corporation, "ExecutionHeader Class", <http://msdn.microsoft.com/en-us/library/reportexecution2005.executionheader.aspx>

[MSDN-EXIC] Microsoft Corporation, "ExecutionInfo Class", <http://msdn.microsoft.com/en-us/library/reportexecution2005.executioninfo.aspx>

[MSDN-RESExeHdr] See [MSDN-EXHC].

[MSDN-RESExeInfo] See [MSDN-EXIC].

[MSDN-RESMethods] Microsoft Corporation, "ReportExecutionService Methods",
http://msdn.microsoft.com/en-us/library/reportexecution2005.reportexecutionservice_methods.aspx

[MSDN-SoapHeader] Microsoft Corporation, "SoapHeader Class", <http://msdn.microsoft.com/en-us/library/system.web.services.protocols.soapheader.aspx>

[MSDN-SSMode] Microsoft Corporation, "Planning a Deployment Mode",
<http://msdn.microsoft.com/en-us/library/bb326345.aspx>

[MSDN-~~SS2008RSSRS~~] Microsoft Corporation, "~~SQL Server~~ Reporting Services", ~~SQL Server 2008 Books Online, (SSRS)~~, <http://msdn.microsoft.com/en-us/library/ms159106.aspx>

1.3 Overview

1.3 Overview

The ReportExecution2005 web service protocol that is described in this document provides methods for running and navigating reports and for customizing report processing and rendering on a report server [MSDN-~~SQL2008RSSRS~~] that is configured for native mode or Microsoft SharePoint integrated mode ~~or native mode~~ [MSDN-SSMode].

Typically, the client establishes a connection with the server. After the connection is established by using the HTTP [RFC2616] or HTTPS [RFC2818] protocol, **SOAP messages** [SOAP1.1] [SOAP1.2-1/2007] are used to communicate between the client and the server.

The ReportExecution2005 web service protocol uses the security facilities that are built into HTTP or HTTPS for authentication and identification and for channel encryption negotiation. The protocol uses the facilities that are built into SOAP for specification of requests from client to server and for returning data from the server to the client. The following diagram depicts a (simplified) typical flow of communication in the protocol.




Figure 14: Communication flow for ReportExecution2005

Each method in the protocol is a SOAP operation that accepts a set of parameters as a SOAP request and returns a set of values as a SOAP response. The client sends a request to the server through a SOAP request message, and the server sends return values to the client through a SOAP response message.

The following procedure describes a simple example client/server exchange for running a report:

1. 1.—The client calls the **LoadReport** method and passes in the full path of the report in the *Report* parameter of the method.
2. 2.—The server loads the report, prepares it for execution, and establishes a report execution session. The server outputs an **ExecutionHeader**[MSDN-EXHC] **SOAP header** that contains information for the session and then returns an **ExecutionInfo**[MSDN-EXIC] object that contains information for the loaded report.
3. 3.—The client calls the **Render** method and passes in the format in which to render the report in the *Format* parameter of the method. The client then sends back the **ExecutionHeader** SOAP header that it received from the server earlier.
4. 4.—The server returns a `Byte[]` array of the report in the specified format.

1.21.4 1.4—Relationship to Other Protocols

The ReportExecution2005 web protocol uses SOAP over HTTP as shown in the following layering diagram.




Figure 22: SOAP over HTTP

~~The ReportExecution2005 web protocol uses SOAP or over HTTPS as shown in the following layering diagram.~~

Figure 3: SOAP over HTTPS

1.31.5 1.5—Prerequisites/Preconditions

The ReportExecution2005 web service operates against a URL. The URL is identified by protocol clients. The protocol server endpoint is formed by appending "/ReportExecution2005.asmx" to the URL, as in the following example:

`http://www.contoso.com/ReportServer/ReportExecution2005.asmx`

It is assumed that authentication has been performed by the underlying protocol. The account that accesses this web service is assigned with proper permissions to the site and its items.

1.41.6 1.6—Applicability Statement

The ReportExecution2005 web service protocol enables client applications to run and navigate reports on a report server over SOAP.

1.51.7 1.7—Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

Supported Transports: The ReportExecution2005 web service protocol uses multiple transports with SOAP as described in section 2.1.

1.61.8 1.8—Vendor-Extensible Fields

None.

1.71.9 1.9—Standards Assignments

None.

2 2—Messages

2.1 Transport

2.1 Transport

Protocol servers MUST support SOAP over HTTP and MUST support SOAP over HTTPS for securing communication with clients.

Protocol messages MUST be formatted as specified in section 4 of [SOAP1.1] or section 3 of [SOAP1.2-1/2007].<1>

2.2 Messages

2.2 Messages

This section defines the messages that are used by this protocol. The syntax of the definitions uses XML Schema as defined in [XMLSCHEMA1] and [XMLSCHEMA2], and it uses Web Services Description Language (WSDL) as defined in [WSDL].

The following information describes the steps by which the API is mapped to structures and operations in the ReportExecution2005 web service [MSDN-SQLRSRE2005].

Each class in the ReportExecution2005 web service, except the class that is derived from **System.Web.Services.Protocols.SoapHttpClientProtocol**, becomes one WSDL type. The following rules apply:

- Non-inherited public properties become elements in the type, with the following exceptions and additional rules:
 - Any property named *AnyAttr* becomes the XSD **anyAttribute** in the type rather than an element.
 - If the name of a property is the concatenation of the name of another property in the same class and “Specified” no element is created for the former property in the type. The **minOccurs** attribute of the element for the latter property is 0. For other properties, the **minOccurs** attribute is 1 unless the API data type is **String**, **Byte[]**, or an array type, in which case the **minOccurs** attribute is 0.
 - The **maxOccurs** attribute of the element is 1 for nonarray types and “unbounded” for array types.
- If the class inherits another class in the web service, the WSDL type of the inherited class becomes an XSD extension in the WSDL type corresponding to the inheriting class.

Each enumeration in the web service becomes one WSDL type as an XSD enumeration.

Each class that inherits **System.Web.Services.Protocols.SoapHeader** [MSDN-SoapHeader] becomes one SOAP header.

Each method in the class that is derived from **System.Web.Services.Protocols.SoapHttpClientProtocol** that is not derived from a base method in a base class or from an interface becomes one **WSDL operation** with a corresponding SOAP operation, a request **WSDL message**, a response WSDL message, and the corresponding WSDL types. The following rules apply:

- Out parameters and return values of the method become elements in the WSDL type for the response WSDL message.

- Other parameters of the method become elements in the WSDL type for the request WSDL message.
- If the method uses a SOAP header, the WSDL operation contains a WSDL message that has a single part of the WSDL type corresponding to the SOAP header.

An array of a class becomes a WSDL type with an element of the WSDL type corresponding to the class.

The primitive data types that are used by the API are mapped to WSDL XML Schema types as described in the following table.

| API primitive data type | WSDL XML Schema type |
|--------------------------------|-----------------------------|
| Byte[] | base64Binary |
| Boolean | boolean |
| SByte | byte |
| Double | double |
| DateTime | dateTime |
| Decimal | decimal |
| Single | float |
| Int32 | int |
| Int64 | long |
| XmIQualifiedName | QName |
| Int16 | short |
| String | string |
| Byte | unsignedByte |
| UInt32 | unsignedInt |
| UInt64 | unsignedLong |
| UInt16 | unsignedShort |

The result of this mapping can be found in the full WSDL in Appendix A of this specification.

2.1.12.2.1 2.2.1 Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms that are specified in [XMLNS]. Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

| Prefix | Namespace URI | Reference |
|---------------|---|--|
| soap | http://schemas.xmlsoap.org/wsdl/soap/ | [WSDL] |
| tns | http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices | Defined in Appendix A of this document |

| Prefix | Namespace URI | Reference |
|--------|---|-------------|
| s | http://www.w3.org/2001/XMLSchema | [XMLSHEMA1] |
| soap12 | http://schemas.xmlsoap.org/wsdl/soap12/ | [WSDL] |
| wsdl | http://schemas.xmlsoap.org/wsdl | [WSDL] |

2.2.2 Methods

2.2.2 Methods

The following table summarizes the set of method definitions that are defined by this specification. ReportExecution: ReportExecution2005 methods are defined in detail in [MSDN-RESMethods].

| Method | Description |
|--|---|
| DeliverReportItem<2> | Sends a report item to a specified extension and creates a subscription for refreshing it. |
| FindString | Returns the logical page number of the next occurrence of the specified string. |
| GetDocumentMap | Returns a representation of the document map for the execution. |
| GetExecutionInfo | Returns information about the report execution as an ExecutionInfo object . |
| GetExecutionInfo2 | Returns information about the report execution as an ExecutionInfo2 object . |
| GetExecutionInfo3<3> | Returns information about the report execution as an ExecutionInfo3 object . |
| GetRenderResource | Returns the resource for a specified rendering extension format. |
| ListRenderingExtensions | Returns a list of rendering extensions. |
| ListSecureMethods | Returns a list of SOAP methods that require a secure (SSL) connection when invoked. |
| LoadDrillthroughTarget | Creates a report execution as an ExecutionInfo object from a drillthrough action. |
| LoadDrillthroughTarget2 | Creates a report execution as an ExecutionInfo2 object from a drillthrough action. |
| LoadDrillthroughTarget3<4> | Creates a report execution as an ExecutionInfo3 object from a drillthrough action. |
| LoadReport | Loads a report from the report server into a new execution and returns it as an ExecutionInfo object . |
| LoadReport2 | Loads a report from the report server into a new execution and returns it as an ExecutionInfo2 object . |
| LoadReport3<5> | Loads a report from the report server into a new execution and returns it as an ExecutionInfo3 object . |
| LoadReportDefinition | Creates a report execution as an ExecutionInfo object from a report definition that is supplied by the client. |
| LoadReportDefinition2 | Creates a report execution as an ExecutionInfo2 object from a report definition that is supplied by the client. |

| Method | Description |
|---|--|
| LoadReportDefinition3<6> | Creates a report execution as an ExecutionInfo3 object from a report definition that is supplied by the client. |
| Logoff | Logs off the current user who is making web service requests. |
| LogonUser | Logs on a user and authenticates a user request to the Report Server web service. |
| NavigateBookmark | Navigates to a specific bookmark in the report. |
| NavigateDocumentMap | Navigates to a specific section of the report. |
| Render | Processes a specific report and renders it in the specified format. |
| Render2 | Processes a specific report and renders it in the specified format <u>that includes a PageCountMode.</u> |
| RenderStream | Returns a secondary rendering stream that is associated with a processed report. |
| ResetExecution | Resets the current report execution by clearing the snapshot and resetting the session state. <u>The report execution is then returned as an ExecutionInfo object.</u> |
| ResetExecution2 | Resets the current report execution by clearing the snapshot and resetting the session state. <u>The report execution is then returned as an ExecutionInfo2 object.</u> |
| ResetExecution3<7> | <u>Resets the current report execution by clearing the snapshot and resetting the session state. The report execution is then returned as an ExecutionInfo3 object.</u> |
| SetExecutionCredentials | Sets the credentials that are associated with the current report execution. <u>The report execution is then returned as an ExecutionInfo object.</u> |
| SetExecutionCredentials2 | Sets the credentials that are associated with the current report execution. <u>The report execution is then returned as an ExecutionInfo2 object.</u> |
| SetExecutionCredentials3<8> | <u>Sets the credentials that are associated with the current report execution. The report execution is then returned as an ExecutionInfo3 object.</u> |
| SetExecutionParameters | Sets and validates parameter values that are associated with the current report execution. <u>The report execution is then returned as an ExecutionInfo object.</u> |
| SetExecutionParameters2 | Sets and validates parameter values that are associated with the current report execution. <u>The report execution is then returned as an ExecutionInfo2 object.</u> |
| SetExecutionParameters3<9> | <u>Sets and validates parameter values that are associated with the current report execution. The report execution is then returned as an ExecutionInfo3 object.</u> |
| Sort | Applies or removes a sort for the execution, <u>as an ExecutionInfo object,</u> based on a user sort action. |
| Sort2 | Applies or removes a sort for the execution, <u>as an ExecutionInfo2 object,</u> based on a user sort action. |
| Sort3<10> | <u>Applies or removes a sort for the execution, as an ExecutionInfo3 object,</u> based on a user sort action. |
| ToggleItem | Toggles the show/hide item in a report. |

2.2.3 Types

2.2.3 Types

The following table summarizes the set of type definitions that are defined by this specification. ReportExecution: ReportExecution2005 types are defined in [detail in \[MSDN-SQLRSRE2005\]](#).

| Type | Description |
|--|---|
| DataSourceCredentials | Represents data source credentials. |
| DataSourcePrompt | Represents the name of a data source and the prompt to display to a user. |
| DocumentMapNode | Represents a single node in the document map. |
| ExecutionInfo | Describes the state of the current report execution. |
| ExecutionInfo2 | Describes the state of the current report execution, including everything that is described by an ExecutionInfo object and PageCountMode . |
| ExecutionInfo3<11> | Describes the state of the current report execution, including everything that is described by an ExecutionInfo2 object and ParameterGridLayoutDefinition . |
| Extension | Represents an extension that is registered with the report server. |
| ExtensionSettings | Represents a delivery extension and its configurable settings . |
| ExtensionTypeEnum | Describes the type of extension that is registered with the report server. |
| PageCountMode | Specifies how the page count is processed. |
| PageSettings | Represents the page settings for a report. |
| ParameterFieldReference | Represents a field name that a report server uses to retrieve the value for a parameter . |
| ParametersGridCellDefinition | Represents the definition of a cell in the grid that references a ReportParameter name . |
| ParametersGridLayoutDefinition | Represents the definition of how parameters should be displayed by a client in a grid that contains layout information . |
| ParameterStateEnum | Specifies the state of a parameter. |
| ParameterTypeEnum | Specifies the data type of a parameter. |
| ParameterValue | Represents data that is used in parameterized reports or in delivery extension settings. |
| ParameterValueOrFieldReference | Represents a user-supplied value or a field name that represents the value of a parameter. |
| ReportMargins | Represents the page margins for a report. |
| ReportPaperSize | Represents the paper size of a report page. This value is read-only. |
| ReportParameter | Represents a report parameter. |
| SortDirectionEnum | Specifies sort directions. |

| Type | Description |
|------------|--|
| ValidValue | Represents a valid value for an extension setting. |
| Warning | Represents a list of errors or warnings that are returned when a report is published or processed. |

2.2.4 SOAP Headers

2.2.4 SOAP Headers

The following table summarizes the set of SOAP header definitions that are defined by this specification. ReportExecution: ReportExecution2005 SOAP headers are defined in [\[MSDN-SQLRSRE2005\]](#).

| SOAP Header | Description |
|-------------------|---|
| ExecutionHeader | Represents state information for sessions in the report server. |
| ServerInfoHeader | Represents information about the report server. |
| TrustedUserHeader | Supports the SQL Server infrastructure.< 212 > |

3—Appendix A: Full WSDL

For ease of implementation, the full WSDL is provided here.

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:ssoap="http://www.w3.org/2001/XMLSchema"
    xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
    xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
    xmlns:mime="http://schemas.xmlsoap.org/wsdl/mime/"
    xmlns:tns="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices"
    xmlns:s="http://www.w3.org/2001/XMLSchema"
    xmlns:soap12soap="http://schemas.xmlsoap.org/wsdl/soap12soap/"
    xmlns:tm="http://microsoft.com/wsdl/mime/textMatching/"
    xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
    targetNamespace="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservice
s" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:documentation xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">The Reporting Services
    Execution Service enables report execution</wsdl:documentation>
    <wsdl:types>
        <s:schema elementFormDefault="qualified"
            targetNamespace="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservice
s">
            <s:element name="ListSecureMethods">
                <s:complexType />
            </s:element>
            <s:element name="ListSecureMethodsResponse">
                <s:complexType>
                    <s:sequence>
                        <s:element minOccurs="0" maxOccurs="1" name="ListSecureMethodsResult"
                            type="tns:ArrayOfString" />
                    </s:sequence>
                </s:complexType>
            </s:element>
            <s:complexType name="ArrayOfString">
                <s:sequence>
                    <s:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
                        type="s:string" />
                </s:sequence>
            </s:complexType>
            <s:element name="TrustedUserHeader" type="tns:TrustedUserHeader" />
            <s:complexType name="TrustedUserHeader">
                <s:sequence>
                    <s:element minOccurs="0" maxOccurs="1" name="UserName" type="s:string" />
                    <s:element minOccurs="0" maxOccurs="1" name="UserToken" type="s:base64Binary" />
                </s:sequence>
                <s:anyAttribute />
            </s:complexType>
            <s:element name="ServerInfoHeader" type="tns:ServerInfoHeader" />
            <s:complexType name="ServerInfoHeader">
                <s:sequence>
                    <s:element minOccurs="0" maxOccurs="1" name="ReportServerVersionNumber"
                        type="s:string" />
                    <s:element minOccurs="0" maxOccurs="1" name="ReportServerEdition" type="s:string"
                />
                    <s:element minOccurs="0" maxOccurs="1" name="ReportServerVersion" type="s:string"
                />
                    <s:element minOccurs="0" maxOccurs="1" name="ReportServerDateTime" type="s:string"
                />
                </s:sequence>
                <s:anyAttribute />
            </s:complexType>
            <s:element name="LoadReport">
                <s:complexType>
                    <s:sequence>
                        <s:element minOccurs="0" maxOccurs="1" name="Report" type="s:string" />
                        <s:element minOccurs="0" maxOccurs="1" name="HistoryID" type="s:string" />
                    </s:sequence>
                </s:complexType>
            </s:element>
        </s:schema>
    </wsdl:types>
    <wsdl:message name="ListSecureMethodsRequest">
        <wsdl:part name="parameters" type="tns>ListSecureMethods" />
    </wsdl:message>
    <wsdl:message name="ListSecureMethodsResponse">
        <wsdl:part name="parameters" type="tns>ListSecureMethodsResult" />
    </wsdl:message>
    <wsdl:operation name="ListSecureMethods">
        <wsdl:input message="ListSecureMethodsRequest" />
        <wsdl:output message="ListSecureMethodsResponse" />
    </wsdl:operation>
    <wsdl:operation name="TrustedUserHeader">
        <wsdl:input message="tns:TrustedUserHeader" />
        <wsdl:output message="tns:TrustedUserHeaderResponse" />
    </wsdl:operation>
    <wsdl:operation name="ServerInfoHeader">
        <wsdl:input message="tns:ServerInfoHeader" />
        <wsdl:output message="tns:ServerInfoHeaderResponse" />
    </wsdl:operation>
    <wsdl:operation name="LoadReport">
        <wsdl:input message="tns:LoadReport" />
        <wsdl:output message="tns:LoadReportResponse" />
    </wsdl:operation>
</wsdl:definitions>
```

```

        </s:complexType>
    </s:element>
    <s:element name="LoadReportResponse">
        <s:complexType>
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo" />
            </s:sequence>
        </s:complexType>
    </s:element>
    <s:complexType name="ExecutionInfo">
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="HasSnapshot" type="s:boolean" />
            <s:element minOccurs="1" maxOccurs="1" name="NeedsProcessing" type="s:boolean" />
            <s:element minOccurs="1" maxOccurs="1" name="AllowQueryExecution" type="s:boolean" />
        </s:sequence>
        <s:element minOccurs="1" maxOccurs="1" name="CredentialsRequired" type="s:boolean" />
        <s:element minOccurs="1" maxOccurs="1" name="ParametersRequired" type="s:boolean" />
        <s:element minOccurs="1" maxOccurs="1" name="ExpirationDateTime" type="s:dateTime" />
        <s:element minOccurs="1" maxOccurs="1" name="ExecutionDateTime" type="s:dateTime" />
        <s:element minOccurs="1" maxOccurs="1" name="NumPages" type="s:int" />
        <s:element minOccurs="0" maxOccurs="1" name="Parameters" type="tns:ArrayOfReportParameter" />
        <s:element minOccurs="0" maxOccurs="1" name="DataSourcePrompts" type="tns:ArrayOfDataSourcePrompt" />
            <s:element minOccurs="1" maxOccurs="1" name="HasDocumentMap" type="s:boolean" />
            <s:element minOccurs="0" maxOccurs="1" name="ExecutionID" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="ReportPath" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="HistoryID" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="ReportPageSettings" type="tns:PageSettings" />
                <s:element minOccurs="1" maxOccurs="1" name="AutoRefreshInterval" type="s:int" />
            </s:sequence>
        </s:complexType>
        <s:complexType name="ArrayOfReportParameter">
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="unbounded" name="ReportParameter" nillable="true" type="tns:ReportParameter" />
            </s:sequence>
        </s:complexType>
        <s:complexType name="ReportParameter">
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="1" name="Name" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="Type" type="tns:ParameterTypeEnum" />
                <s:element minOccurs="0" maxOccurs="1" name="Nullable" type="s:boolean" />
                <s:element minOccurs="0" maxOccurs="1" name="AllowBlank" type="s:boolean" />
                <s:element minOccurs="0" maxOccurs="1" name="MultiValue" type="s:boolean" />
                <s:element minOccurs="0" maxOccurs="1" name="QueryParameter" type="s:boolean" />
                <s:element minOccurs="0" maxOccurs="1" name="Prompt" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="PromptUser" type="s:boolean" />
                <s:element minOccurs="0" maxOccurs="1" name="Dependencies" type="tns:ArrayOfString1" />
                    <s:element minOccurs="0" maxOccurs="1" name="ValidValuesQueryBased" type="s:boolean" />
                    <s:element minOccurs="0" maxOccurs="1" name="ValidValues" type="tns:ArrayOfValidValue" />
                    <s:element minOccurs="0" maxOccurs="1" name="DefaultValuesQueryBased" type="s:boolean" />
                    <s:element minOccurs="0" maxOccurs="1" name="DefaultValues" type="tns:ArrayOfString2" />
                </s:sequence>
            </s:complexType>
        </s:sequence>
    </s:complexType>

```

```

<s:simpleType name="ParameterTypeEnum">
  <s:restriction base="s:string">
    <s:enumeration value="Boolean" />
    <s:enumeration value="DateTime" />
    <s:enumeration value="Integer" />
    <s:enumeration value="Float" />
    <s:enumeration value="String" />
  </s:restriction>
</s:simpleType>
<s:complexType name="ArrayOfString1">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="unbounded" name="Dependency" nillable="true"
      type="s:string" />
  </s:sequence>
</s:complexType>
<s:complexType name="ArrayOfValidValue">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="unbounded" name="ValidValue" nillable="true"
      type="tns:ValidValue" />
  </s:sequence>
</s:complexType>
<s:complexType name="ValidValue">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="1" name="Label" type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="Value" type="s:string" />
  </s:sequence>
</s:complexType>
<s:complexType name="ArrayOfString2">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="unbounded" name="Value" nillable="true"
      type="s:string" />
  </s:sequence>
</s:complexType>
<s:simpleType name="ParameterStateEnum">
  <s:restriction base="s:string">
    <s:enumeration value="HasValidValue" />
    <s:enumeration value="MissingValidValue" />
    <s:enumeration value="HasOutstandingDependencies" />
    <s:enumeration value="DynamicValuesUnavailable" />
  </s:restriction>
</s:simpleType>
<s:complexType name="ArrayOfDataSourcePrompt">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="unbounded" name="DataSourcePrompt"
      nillable="true" type="tns:DataSourcePrompt" />
  </s:sequence>
</s:complexType>
<s:complexType name="DataSourcePrompt">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="1" name="Name" type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="DataSourceID" type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="Prompt" type="s:string" />
  </s:sequence>
</s:complexType>
<s:complexType name="PageSettings">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="1" name="PaperSize" type="tns:ReportPaperSize"
      />
    <s:element minOccurs="0" maxOccurs="1" name="Margins" type="tns:ReportMargins" />
  </s:sequence>
</s:complexType>
<s:complexType name="ReportPaperSize">
  <s:sequence>
    <s:element minOccurs="1" maxOccurs="1" name="Height" type="s:double" />
    <s:element minOccurs="1" maxOccurs="1" name="Width" type="s:double" />
  </s:sequence>
</s:complexType>
<s:complexType name="ReportMargins">
  <s:sequence>

```

```

<s:element minOccurs="1" maxOccurs="1" name="Top" type="s:double" />
<s:element minOccurs="1" maxOccurs="1" name="Bottom" type="s:double" />
<s:element minOccurs="1" maxOccurs="1" name="Left" type="s:double" />
<s:element minOccurs="1" maxOccurs="1" name="Right" type="s:double" />
</s:sequence>
</s:complexType>
<s:element name="ExecutionHeader" type="tns:ExecutionHeader" />
<s:complexType name="ExecutionHeader">
<s:sequence>
<s:element minOccurs="0" maxOccurs="1" name="ExecutionID" type="s:string" />
</s:sequence>
<s:anyAttribute />
</s:complexType>
<s:element name="LoadReport2LoadReport3">
<s:complexType>
<s:sequence>
<s:element minOccurs="0" maxOccurs="1" name="Report" type="s:string" />
<s:element minOccurs="0" maxOccurs="1" name="HistoryID" type="s:string" />
</s:sequence>
</s:complexType>
</s:element>
<s:element name="LoadReport2ResponseLoadReport3Response">
<s:complexType>
<s:sequence>
<s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo2ExecutionInfo3" />
</s:sequence>
</s:complexType>
</s:element>
<s:complexType name="ExecutionInfo3">
<s:complexContent mixed="false">
<s:extension base="tns:ExecutionInfo2">
<s:sequence>
<s:element minOccurs="0" maxOccurs="1" name="ParametersLayout"
type="tns:ParametersGridLayoutDefinition" />
</s:sequence>
</s:extension>
</s:complexContent>
</s:complexType>
<s:complexType name="ExecutionInfo2">
<s:complexContent mixed="false">
<s:extension base="tns:ExecutionInfo">
<s:sequence>
<s:element minOccurs="1" maxOccurs="1" name="PageCountMode"
type="tns:PageCountMode" />
</s:sequence>
</s:extension>
</s:complexContent>
</s:complexType>
<s:simpleType name="PageCountMode">
<s:restriction base="s:string">
<s:enumeration value="Actual" />
<s:enumeration value="Estimate" />
</s:restriction>
</s:simpleType>
<s:complexType name="ParametersGridLayoutDefinition">
<s:sequence>
<s:element minOccurs="1" maxOccurs="1" name="NumberOfColumns" type="s:int" />
<s:element minOccurs="1" maxOccurs="1" name="NumberOfRows" type="s:int" />
<s:element minOccurs="0" maxOccurs="1" name="CellDefinitions"
type="tns:ArrayOfParametersGridLayoutCellDefinition" />
</s:sequence>
</s:complexType>
<s:complexType name="ArrayOfParametersGridLayoutCellDefinition">
<s:sequence>
<s:element minOccurs="0" maxOccurs="unbounded" name="ParametersGridLayoutCellDefinition"
nillable="true" type="tns:ParametersGridLayoutCellDefinition" />
</s:sequence>
</s:complexType>

```

```

<s:complexType name="ParametersGridCellDefinition">
    <s:sequence>
        <s:element minOccurs="1" maxOccurs="1" name="RowIndex" type="s:int" />
        <s:element minOccurs="1" maxOccurs="1" name="ColumnsIndex" type="s:int" />
        <s:element minOccurs="0" maxOccurs="1" name="ParameterName" type="s:string" />
    </s:sequence>
</s:complexType>
<s:element name="LoadReport2">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Report" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="HistoryID" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="LoadReport2Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo2" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="LoadReportDefinition">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Definition" type="s:base64Binary" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="LoadReportDefinitionResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo" />
            <s:element minOccurs="0" maxOccurs="1" name="warnings" type="tns:ArrayOfWarning"
/>
        </s:sequence>
    </s:complexType>
</s:element>
<s:complexType name="ArrayOfWarning">
    <s:sequence>
        <s:element minOccurs="0" maxOccurs="unbounded" name="Warning" nillable="true"
type="tns:Warning" />
    </s:sequence>
</s:complexType>
<s:complexType name="Warning">
    <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="Code" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="Severity" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="ObjectName" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="ObjectType" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="Message" type="s:string" />
    </s:sequence>
</s:complexType>
<s:element name="LoadReportDefinition2">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Definition" type="s:base64Binary" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="LoadReportDefinition2Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo2" />
            <s:element minOccurs="0" maxOccurs="1" name="warnings" type="tns:ArrayOfWarning"
/>
        </s:sequence>
    </s:complexType>
</s:element>

```

```

        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="LoadReportDefinition3">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Definition" type="s:base64Binary" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="LoadReportDefinition3Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo3" />
            <s:element minOccurs="0" maxOccurs="1" name="warnings" type="tns:ArrayOfWarning"
/>
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionCredentials">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Credentials"
type="tns:ArrayOfDataSourceCredentials" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:complexType name="ArrayOfDataSourceCredentials">
    <s:sequence>
        <s:element minOccurs="0" maxOccurs="unbounded" name="DataSourceCredentials"
nillable="true" type="tns:DataSourceCredentials" />
    </s:sequence>
</s:complexType>
<s:complexType name="DataSourceCredentials">
    <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="DataSourceName" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="UserName" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="Password" type="s:string" />
    </s:sequence>
</s:complexType>
<s:element name="SetExecutionCredentialsResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionCredentials2">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Credentials"
type="tns:ArrayOfDataSourceCredentials" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionCredentials2Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo2" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionCredentials3">
    <s:complexType>
        <s:sequence>

```

```

        <s:element minOccurs="0" maxOccurs="1" name="Credentials"
type="tns:ArrayOfDataSourceCredentials" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionCredentials3Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo3" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionParameters">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Parameters"
type="tns:ArrayOfParameterValue" />
            <s:element minOccurs="0" maxOccurs="1" name="ParameterLanguage" type="s:string"
/>
        </s:sequence>
    </s:complexType>
</s:element>
<s:complexType name="ArrayOfParameterValue">
    <s:sequence>
        <s:element minOccurs="0" maxOccurs="unbounded" name="ParameterValue"
nillable="true" type="tns:ParameterValue" />
    </s:sequence>
</s:complexType>
<s:complexType name="ParameterValue">
    <s:complexContent mixed="false">
        <s:extension base="tns:ParameterValueOrFieldReference">
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="1" name="Name" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="Value" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="Label" type="s:string" />
            </s:sequence>
        </s:extension>
    </s:complexContent>
</s:complexType>
<s:complexType name="ParameterValueOrFieldReference" />
<s:element name="SetExecutionParametersResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionParameters2">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Parameters"
type="tns:ArrayOfParameterValue" />
            <s:element minOccurs="0" maxOccurs="1" name="ParameterLanguage" type="s:string"
/>
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionParameters2Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo2" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="SetExecutionParameters3">
    <s:complexType>

```

```

<s:sequence>
  <s:element minOccurs="0" maxOccurs="1" name="Parameters"
  type="tns:ArrayOfParameterValue" />
    <s:element minOccurs="0" maxOccurs="1" name="ParameterLanguage" type="s:string"
  />
  </s:sequence>
</s:complexType>
</s:element>
<s:element name="SetExecutionParameters3Response">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
      type="tns:ExecutionInfo3" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="ResetExecution">
  <s:complexType />
</s:element>
<s:element name="ResetExecutionResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
      type="tns:ExecutionInfo" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="ResetExecution2">
  <s:complexType />
</s:element>
<s:element name="ResetExecution2Response">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
      type="tns:ExecutionInfo2" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="ResetExecution3">
  <s:complexType />
</s:element>
<s:element name="ResetExecution3Response">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
      type="tns:ExecutionInfo3" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="Render">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="Format" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="DeviceInfo" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="RenderResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="Result" type="s:base64Binary" />
      <s:element minOccurs="0" maxOccurs="1" name="Extension" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="MimeType" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="Encoding" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="Warnings" type="tns:ArrayOfWarning"
    />
      <s:element minOccurs="0" maxOccurs="1" name="StreamIds" type="tns:ArrayOfString"
    />
  </s:sequence>

```

```

        </s:complexType>
    </s:element>
    <s:element name="Render2">
        <s:complexType>
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="1" name="Format" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="DeviceInfo" type="s:string" />
                <s:element minOccurs="1" maxOccurs="1" name="PaginationMode"
type="tns:PageCountMode" />
            </s:sequence>
        </s:complexType>
    </s:element>
    <s:element name="Render2Response">
        <s:complexType>
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="1" name="Result" type="s:base64Binary" />
                <s:element minOccurs="0" maxOccurs="1" name="Extension" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="MimeType" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="Encoding" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="Warnings" type="tns:ArrayOfWarning"
/>
            <s:element minOccurs="0" maxOccurs="1" name="StreamIds" type="tns:ArrayOfString"
/>
        </s:sequence>
    </s:complexType>

```

<s:element name="DeliverReportItem">

```

        <s:complexType>
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="1" name="Format" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="DeviceInfo" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="ExtensionSettings"
type="tns:ExtensionSettings" />
                <s:element minOccurs="0" maxOccurs="1" name="Description" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="EventType" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="MatchData" type="s:string" />
            </s:sequence>
        </s:complexType>

```

</s:element>

```

        <s:complexType name="ExtensionSettings">
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="1" name="Extension" type="s:string" />
                <s:element minOccurs="0" maxOccurs="1" name="ParameterValues"
type="tns:ArrayOfChoice1" />
            </s:sequence>
        </s:complexType>

```

</s:complexType>

```

        <s:complexType name="ArrayOfChoice1">
            <s:choice minOccurs="0" maxOccurs="unbounded">
                <s:element minOccurs="1" maxOccurs="1" name="ParameterValue" nillable="true"
type="tns:ParameterValue" />
                <s:element minOccurs="1" maxOccurs="1" name="ParameterFieldReference"
nillable="true" type="tns:ParameterFieldReference" />
            </s:choice>
        </s:complexType>

```

<s:complexType name="ParameterFieldReference">

```

        <s:complexContent mixed="false">
            <s:extension base="tns:ParameterValueOrFieldReference">
                <s:sequence>
                    <s:element minOccurs="0" maxOccurs="1" name="ParameterName" type="s:string" />
                    <s:element minOccurs="0" maxOccurs="1" name="FieldAlias" type="s:string" />
                </s:sequence>
            </s:extension>
        </s:complexContent>

```

</s:complexType>

```

        <s:element name="DeliverReportItemResponse">
            <s:complexType />

```

</s:element>

```

        <s:element name="RenderStream">
            <s:complexType>

```

```

<s:sequence>
    <s:element minOccurs="0" maxOccurs="1" name="Format" type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="StreamID" type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="DeviceInfo" type="s:string" />
</s:sequence>
</s:complexType>
</s:element>
<s:element name="RenderStreamResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Result" type="s:base64Binary" />
            <s:element minOccurs="0" maxOccurs="1" name="Encoding" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="MimeType" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="GetExecutionInfo">
    <s:complexType />
</s:element>
<s:element name="GetExecutionInfoResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="GetExecutionInfo2">
    <s:complexType />
</s:element>
<s:element name="GetExecutionInfo2Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo2" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="GetExecutionInfo3">
    <s:complexType />
</s:element>
<s:element name="GetExecutionInfo3Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="executionInfo"
type="tns:ExecutionInfo3" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="GetDocumentMap">
    <s:complexType />
</s:element>
<s:element name="GetDocumentMapResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="result" type="tns:DocumentMapNode"
/>
        </s:sequence>
    </s:complexType>
</s:element>
<s:complexType name="DocumentMapNode">
    <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="Label" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="UniqueName" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="Children"
type="tns:ArrayOfDocumentMapNode" />
    </s:sequence>
</s:complexType>
<s:complexType name="ArrayOfDocumentMapNode">

```

```

<s:sequence>
  <s:element minOccurs="0" maxOccurs="unbounded" name="DocumentMapNode"
  nillable="true" type="tns:DocumentMapNode" />
</s:sequence>
</s:complexType>
<s:element name="LoadDrillthroughTarget">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="DrillthroughID" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="LoadDrillthroughTargetResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ExecutionInfo"
      type="tns:ExecutionInfo" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="LoadDrillthroughTarget2">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="DrillthroughID" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="LoadDrillthroughTarget2Response">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ExecutionInfo"
      type="tns:ExecutionInfo2" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="LoadDrillthroughTarget3">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="DrillthroughID" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="LoadDrillthroughTarget3Response">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ExecutionInfo"
      type="tns:ExecutionInfo3" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="ToggleItem">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ToggleID" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="ToggleItemResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="1" maxOccurs="1" name="Found" type="s:boolean" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="NavigateDocumentMap">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="DocMapID" type="s:string" />
    </s:sequence>

```

```

        </s:complexType>
    </s:element>
<s:element name="NavigateDocumentMapResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="PageNumber" type="s:int" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="NavigateBookmark">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="BookmarkID" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="NavigateBookmarkResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="PageNumber" type="s:int" />
            <s:element minOccurs="0" maxOccurs="1" name="UniqueName" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="FindString">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="StartPage" type="s:int" />
            <s:element minOccurs="1" maxOccurs="1" name="EndPage" type="s:int" />
            <s:element minOccurs="0" maxOccurs="1" name="FindValue" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="FindStringResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="PageNumber" type="s:int" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="Sort">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="SortItem" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="Direction" type="tns:SortDirectionEnum" />
            <s:element minOccurs="1" maxOccurs="1" name="Clear" type="s:boolean" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:simpleType name="SortDirectionEnum">
    <s:restriction base="s:string">
        <s:enumeration value="None" />
        <s:enumeration value="Ascending" />
        <s:enumeration value="Descending" />
    </s:restriction>
</s:simpleType>
<s:element name="SortResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="PageNumber" type="s:int" />
            <s:element minOccurs="0" maxOccurs="1" name="ReportItem" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="NumPages" type="s:int" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="Sort2">
    <s:complexType>
        <s:sequence>

```

```

        <s:element minOccurs="0" maxOccurs="1" name="SortItem" type="s:string" />
        <s:element minOccurs="1" maxOccurs="1" name="Direction"
type="tns:SortDirectionEnum" />
            <s:element minOccurs="1" maxOccurs="1" name="Clear" type="s:boolean" />
            <s:element minOccurs="1" maxOccurs="1" name="PaginationMode"
type="tns:PageCountMode" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="Sort2Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="PageNumber" type="s:int" />
            <s:element minOccurs="0" maxOccurs="1" name="ReportItem" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="ExecutionInfo"
type="tns:ExecutionInfo2" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="Sort3">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="SortItem" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="Direction"
type="tns:SortDirectionEnum" />
            <s:element minOccurs="1" maxOccurs="1" name="Clear" type="s:boolean" />
            <s:element minOccurs="1" maxOccurs="1" name="PaginationMode"
type="tns:PageCountMode" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="Sort3Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="PageNumber" type="s:int" />
            <s:element minOccurs="0" maxOccurs="1" name="ReportItem" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="ExecutionInfo"
type="tns:ExecutionInfo3" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="GetRenderResource">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Format" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="DeviceInfo" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="GetRenderResourceResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Result" type="s:base64Binary" />
            <s:element minOccurs="0" maxOccurs="1" name="MimeType" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="ListRenderingExtensions">
    <s:complexType />
</s:element>
<s:element name="ListRenderingExtensionsResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="Extensions"
type="tns:ArrayOfExtension" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:complexType name="ArrayOfExtension">
    <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="Extension"
type="tns:Extension" />
    </s:sequence>
</s:complexType>
</s:element>
</s:complexType>

```

```

<s:sequence>
  <s:element minOccurs="0" maxOccurs="unbounded" name="Extension" nillable="true"
type="tns:Extension" />
</s:sequence>
</s:complexType>
<s:complexType name="Extension">
  <s:sequence>
    <s:element minOccurs="1" maxOccurs="1" name="ExtensionType"
type="tns:ExtensionTypeEnum" />
      <s:element minOccurs="0" maxOccurs="1" name="Name" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="LocalizedName" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="Visible" type="s:boolean" />
      <s:element minOccurs="1" maxOccurs="1" name="IsModelGenerationSupported"
type="s:boolean" />
    </s:sequence>
  </s:complexType>
<s:simpleType name="ExtensionTypeEnum">
  <s:restriction base="s:string">
    <s:enumeration value="Delivery" />
    <s:enumeration value="Render" />
    <s:enumeration value="Data" />
    <s:enumeration value="All" />
  </s:restriction>
</s:simpleType>
<s:element name="LogonUser">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="userName" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="password" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="authority" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="LogonUserResponse">
  <s:complexType />
</s:element>
<s:element name="Logoff">
  <s:complexType />
</s:element>
<s:element name="LogoffResponse">
  <s:complexType />
</s:element>
</s:schema>
</wsdl:types>
</wsdl:message name="ListSecureMethodsSoapIn">
  <wsdl:part name="parameters" element="tns>ListSecureMethods" />
</wsdl:message>
<wsdl:message name="ListSecureMethodsSoapOut">
  <wsdl:part name="parameters" element="tns>ListSecureMethodsResponse" />
</wsdl:message>
<wsdl:message name="ListSecureMethodsServerInfoHeader">
  <wsdl:part name="ServerInfoHeader" element="tns ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="ListSecureMethodsTrustedUserHeader">
  <wsdl:part name="TrustedUserHeader" element="tns TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadReportSoapIn">
  <wsdl:part name="parameters" element="tns LoadReport" />
</wsdl:message>
<wsdl:message name="LoadReportSoapOut">
  <wsdl:part name="parameters" element="tns LoadReportResponse" />
</wsdl:message>
<wsdl:message name="LoadReportExecutionHeader">
  <wsdl:part name="ExecutionHeader" element="tns ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadReportServerInfoHeader">
  <wsdl:part name="ServerInfoHeader" element="tns ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadReportTrustedUserHeader">

```

```

<wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadReport3SoapIn">
    <wsdl:part name="parameters" element="tns:LoadReport3" />
</wsdl:message>
<wsdl:message name="LoadReport3SoapOut">
    <wsdl:part name="parameters" element="tns:LoadReport3Response" />
</wsdl:message>
<wsdl:message name="LoadReport3ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadReport3ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadReport3TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadReport2SoapIn">
    <wsdl:part name="parameters" element="tns:LoadReport2" />
</wsdl:message>
<wsdl:message name="LoadReport2SoapOut">
    <wsdl:part name="parameters" element="tns:LoadReport2Response" />
</wsdl:message>
<wsdl:message name="LoadReport2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadReport2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadReport2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinitionSoapIn">
    <wsdl:part name="parameters" element="tns:LoadReportDefinition" />
</wsdl:message>
<wsdl:message name="LoadReportDefinitionSoapOut">
    <wsdl:part name="parameters" element="tns:LoadReportDefinitionResponse" />
</wsdl:message>
<wsdl:message name="LoadReportDefinitionExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinitionServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinitionTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition2SoapIn">
    <wsdl:part name="parameters" element="tns:LoadReportDefinition2" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition2SoapOut">
    <wsdl:part name="parameters" element="tns:LoadReportDefinition2Response" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition3SoapIn">
    <wsdl:part name="parameters" element="tns:LoadReportDefinition3" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition3SoapOut">
    <wsdl:part name="parameters" element="tns:LoadReportDefinition3Response" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition3ExecutionHeader">

```

```

<wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition3ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadReportDefinition3TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentialsSoapIn">
    <wsdl:part name="parameters" element="tns:SetExecutionCredentials" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentialsSoapOut">
    <wsdl:part name="parameters" element="tns:SetExecutionCredentialsResponse" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentialsExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentialsServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentialsTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials2SoapIn">
    <wsdl:part name="parameters" element="tns:SetExecutionCredentials2" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials2SoapOut">
    <wsdl:part name="parameters" element="tns:SetExecutionCredentials2Response" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials3SoapIn">
    <wsdl:part name="parameters" element="tns:SetExecutionCredentials3" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials3SoapOut">
    <wsdl:part name="parameters" element="tns:SetExecutionCredentials3Response" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials3ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials3ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionCredentials3TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParametersSoapIn">
    <wsdl:part name="parameters" element="tns:SetExecutionParameters" />
</wsdl:message>
<wsdl:message name="SetExecutionParametersSoapOut">
    <wsdl:part name="parameters" element="tns:SetExecutionParametersResponse" />
</wsdl:message>
<wsdl:message name="SetExecutionParametersExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParametersServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParametersTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters2SoapIn">

```

```

<wsdl:part name="parameters" element="tns:SetExecutionParameters2" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters2SoapOut">
    <wsdl:part name="parameters" element="tns:SetExecutionParameters2Response" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters3SoapIn">
    <wsdl:part name="parameters" element="tns:SetExecutionParameters3" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters3SoapOut">
    <wsdl:part name="parameters" element="tns:SetExecutionParameters3Response" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters3ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters3ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="SetExecutionParameters3TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="ResetExecutionSoapIn">
    <wsdl:part name="parameters" element="tns:ResetExecution" />
</wsdl:message>
<wsdl:message name="ResetExecutionSoapOut">
    <wsdl:part name="parameters" element="tns:ResetExecutionResponse" />
</wsdl:message>
<wsdl:message name="ResetExecutionExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="ResetExecutionServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="ResetExecutionTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="ResetExecution2SoapIn">
    <wsdl:part name="parameters" element="tns:ResetExecution2" />
</wsdl:message>
<wsdl:message name="ResetExecution2SoapOut">
    <wsdl:part name="parameters" element="tns:ResetExecution2Response" />
</wsdl:message>
<wsdl:message name="ResetExecution2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="ResetExecution2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="ResetExecution2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="ResetExecution3SoapIn">
    <wsdl:part name="parameters" element="tns:ResetExecution3" />
</wsdl:message>
<wsdl:message name="ResetExecution3SoapOut">
    <wsdl:part name="parameters" element="tns:ResetExecution3Response" />
</wsdl:message>
<wsdl:message name="ResetExecution3ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="ResetExecution3ServerInfoHeader">

```

```

<wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="ResetExecution3TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="RenderSoapIn">
    <wsdl:part name="parameters" element="tns:Render" />
</wsdl:message>
<wsdl:message name="RenderSoapOut">
    <wsdl:part name="parameters" element="tns:RenderResponse" />
</wsdl:message>
<wsdl:message name="RenderExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="RenderServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="RenderTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="Render2SoapIn">
    <wsdl:part name="parameters" element="tns:Render2" />
</wsdl:message>
<wsdl:message name="Render2SoapOut">
    <wsdl:part name="parameters" element="tns:Render2Response" />
</wsdl:message>
<wsdl:message name="Render2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="Render2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="Render2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="DeliverReportItemSoapIn">
    <wsdl:part name="parameters" element="tns:DeliverReportItem" />
</wsdl:message>
<wsdl:message name="DeliverReportItemSoapOut">
    <wsdl:part name="parameters" element="tns:DeliverReportItemResponse" />
</wsdl:message>
<wsdl:message name="DeliverReportItemExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="DeliverReportItemServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="DeliverReportItemTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="RenderStreamSoapIn">
    <wsdl:part name="parameters" element="tns:RenderStream" />
</wsdl:message>
<wsdl:message name="RenderStreamSoapOut">
    <wsdl:part name="parameters" element="tns:RenderStreamResponse" />
</wsdl:message>
<wsdl:message name="RenderStreamExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="RenderStreamServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="RenderStreamTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfoSoapIn">
    <wsdl:part name="parameters" element="tns:GetExecutionInfo" />
</wsdl:message>
<wsdl:message name="GetExecutionInfoSoapOut">

```

```

<wsdl:part name="parameters" element="tns:GetExecutionInfoResponse" />
</wsdl:message>
<wsdl:message name="GetExecutionInfoExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfoServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfoTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo2SoapIn">
    <wsdl:part name="parameters" element="tns:GetExecutionInfo2" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo2SoapOut">
    <wsdl:part name="parameters" element="tns:GetExecutionInfo2Response" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo3SoapIn">
    <wsdl:part name="parameters" element="tns:GetExecutionInfo3" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo3SoapOut">
    <wsdl:part name="parameters" element="tns:GetExecutionInfo3Response" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo3ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo3ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="GetExecutionInfo3TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="GetDocumentMapSoapIn">
    <wsdl:part name="parameters" element="tns:GetDocumentMap" />
</wsdl:message>
<wsdl:message name="GetDocumentMapSoapOut">
    <wsdl:part name="parameters" element="tns:GetDocumentMapResponse" />
</wsdl:message>
<wsdl:message name="GetDocumentMapExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="GetDocumentMapServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="GetDocumentMapTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTargetSoapIn">
    <wsdl:part name="parameters" element="tns:LoadDrillthroughTarget" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTargetSoapOut">
    <wsdl:part name="parameters" element="tns:LoadDrillthroughTargetResponse" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTargetExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTargetServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTargetTrustedUserHeader">

```

```

<wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget2SoapIn">
    <wsdl:part name="parameters" element="tns:LoadDrillthroughTarget2" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget2SoapOut">
    <wsdl:part name="parameters" element="tns:LoadDrillthroughTarget2Response" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget3SoapIn">
    <wsdl:part name="parameters" element="tns:LoadDrillthroughTarget3" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget3SoapOut">
    <wsdl:part name="parameters" element="tns:LoadDrillthroughTarget3Response" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget3ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget3ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LoadDrillthroughTarget3TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="ToggleItemSoapIn">
    <wsdl:part name="parameters" element="tns:ToggleItem" />
</wsdl:message>
<wsdl:message name="ToggleItemSoapOut">
    <wsdl:part name="parameters" element="tns:ToggleItemResponse" />
</wsdl:message>
<wsdl:message name="ToggleItemExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="ToggleItemServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="ToggleItemTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="NavigateDocumentMapSoapIn">
    <wsdl:part name="parameters" element="tns:.NavigateDocumentMap" />
</wsdl:message>
<wsdl:message name="NavigateDocumentMapSoapOut">
    <wsdl:part name="parameters" element="tns:.NavigateDocumentMapResponse" />
</wsdl:message>
<wsdl:message name="NavigateDocumentMapExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="NavigateDocumentMapServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="NavigateDocumentMapTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="NavigateBookmarkSoapIn">
    <wsdl:part name="parameters" element="tns:.NavigateBookmark" />
</wsdl:message>
<wsdl:message name="NavigateBookmarkSoapOut">
    <wsdl:part name="parameters" element="tns:.NavigateBookmarkResponse" />
</wsdl:message>
<wsdl:message name="NavigateBookmarkExecutionHeader">

```

```

<wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="NavigateBookmarkServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="NavigateBookmarkTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="FindStringSoapIn">
    <wsdl:part name="parameters" element="tns:FindString" />
</wsdl:message>
<wsdl:message name="FindStringSoapOut">
    <wsdl:part name="parameters" element="tns:FindStringResponse" />
</wsdl:message>
<wsdl:message name="FindStringExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="FindStringServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="FindStringTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="SortSoapIn">
    <wsdl:part name="parameters" element="tns:Sort" />
</wsdl:message>
<wsdl:message name="SortSoapOut">
    <wsdl:part name="parameters" element="tns:SortResponse" />
</wsdl:message>
<wsdl:message name="SortExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="SortServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="SortTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="Sort2SoapIn">
    <wsdl:part name="parameters" element="tns:Sort2" />
</wsdl:message>
<wsdl:message name="Sort2SoapOut">
    <wsdl:part name="parameters" element="tns:Sort2Response" />
</wsdl:message>
<wsdl:message name="Sort2ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="Sort2ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="Sort2TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="Sort3SoapIn">
    <wsdl:part name="parameters" element="tns:Sort3" />
</wsdl:message>
<wsdl:message name="Sort3SoapOut">
    <wsdl:part name="parameters" element="tns:Sort3Response" />
</wsdl:message>
<wsdl:message name="Sort3ExecutionHeader">
    <wsdl:part name="ExecutionHeader" element="tns:ExecutionHeader" />
</wsdl:message>
<wsdl:message name="Sort3ServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="Sort3TrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="GetRenderResourceSoapIn">

```

```

<wsdl:part name="parameters" element="tns:GetRenderResource" />
</wsdl:message>
<wsdl:message name="GetRenderResourceSoapOut">
    <wsdl:part name="parameters" element="tns:GetRenderResourceResponse" />
</wsdl:message>
<wsdl:message name="GetRenderResourceServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="GetRenderResourceTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="ListRenderingExtensionsSoapIn">
    <wsdl:part name="parameters" element="tns>ListRenderingExtensions" />
</wsdl:message>
<wsdl:message name="ListRenderingExtensionsSoapOut">
    <wsdl:part name="parameters" element="tns>ListRenderingExtensionsResponse" />
</wsdl:message>
<wsdl:message name="ListRenderingExtensionsServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="ListRenderingExtensionsTrustedUserHeader">
    <wsdl:part name="TrustedUserHeader" element="tns:TrustedUserHeader" />
</wsdl:message>
<wsdl:message name="LogonUserSoapIn">
    <wsdl:part name="parameters" element="tns:LogonUser" />
</wsdl:message>
<wsdl:message name="LogonUserSoapOut">
    <wsdl:part name="parameters" element="tns:LogonUserResponse" />
</wsdl:message>
<wsdl:message name="LogonUserServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:message name="LogoffSoapIn">
    <wsdl:part name="parameters" element="tns:Logoff" />
</wsdl:message>
<wsdl:message name="LogoffSoapOut">
    <wsdl:part name="parameters" element="tns:LogoffResponse" />
</wsdl:message>
<wsdl:message name="LogoffServerInfoHeader">
    <wsdl:part name="ServerInfoHeader" element="tns:ServerInfoHeader" />
</wsdl:message>
<wsdl:portType name="ReportExecutionServiceSoap">
    <wsdl:operation name="ListSecureMethods">
        <wsdl:input message="tns>ListSecureMethodsSoapIn" />
        <wsdl:output message="tns>ListSecureMethodsSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="LoadReport">
        <wsdl:input message="tns:LoadReportSoapIn" />
        <wsdl:output message="tns:LoadReportSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="LoadReport3">
        <wsdl:input message="tns:LoadReport3SoapIn" />
        <wsdl:output message="tns:LoadReport3SoapOut" />
    </wsdl:operation>
    <wsdl:operation name="LoadReport2">
        <wsdl:input message="tns:LoadReport2SoapIn" />
        <wsdl:output message="tns:LoadReport2SoapOut" />
    </wsdl:operation>
    <wsdl:operation name="LoadReportDefinition">
        <wsdl:input message="tns:LoadReportDefinitionSoapIn" />
        <wsdl:output message="tns:LoadReportDefinitionSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="LoadReportDefinition2">
        <wsdl:input message="tns:LoadReportDefinition2SoapIn" />
        <wsdl:output message="tns:LoadReportDefinition2SoapOut" />
    </wsdl:operation>
    <wsdl:operation name="LoadReportDefinition3">
        <wsdl:input message="tns:LoadReportDefinition3SoapIn" />
        <wsdl:output message="tns:LoadReportDefinition3SoapOut" />
    </wsdl:operation>

```

```

        </wsdl:operation>
<wsdl:operation name="SetExecutionCredentials">
    <wsdl:input message="tns:SetExecutionCredentialsSoapIn" />
    <wsdl:output message="tns:SetExecutionCredentialsSoapOut" />
</wsdl:operation>
<wsdl:operation name="SetExecutionCredentials2">
    <wsdl:input message="tns:SetExecutionCredentials2SoapIn" />
    <wsdl:output message="tns:SetExecutionCredentials2SoapOut" />
</wsdl:operation>
<wsdl:operation name="SetExecutionCredentials3">
    <wsdl:input message="tns:SetExecutionCredentials3SoapIn" />
    <wsdl:output message="tns:SetExecutionCredentials3SoapOut" />
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters">
    <wsdl:input message="tns:SetExecutionParametersSoapIn" />
    <wsdl:output message="tns:SetExecutionParametersSoapOut" />
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters2">
    <wsdl:input message="tns:SetExecutionParameters2SoapIn" />
    <wsdl:output message="tns:SetExecutionParameters2SoapOut" />
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters3">
    <wsdl:input message="tns:SetExecutionParameters3SoapIn" />
    <wsdl:output message="tns:SetExecutionParameters3SoapOut" />
</wsdl:operation>
<wsdl:operation name="ResetExecution">
    <wsdl:input message="tns:ResetExecutionSoapIn" />
    <wsdl:output message="tns:ResetExecutionSoapOut" />
</wsdl:operation>
<wsdl:operation name="ResetExecution2">
    <wsdl:input message="tns:ResetExecution2SoapIn" />
    <wsdl:output message="tns:ResetExecution2SoapOut" />
</wsdl:operation>
<wsdl:operation name="ResetExecution3">
    <wsdl:input message="tns:ResetExecution3SoapIn" />
    <wsdl:output message="tns:ResetExecution3SoapOut" />
</wsdl:operation>
<wsdl:operation name="Render">
    <wsdl:input message="tns:RenderSoapIn" />
    <wsdl:output message="tns:RenderSoapOut" />
</wsdl:operation>
<wsdl:operation name="Render2">
    <wsdl:input message="tns:Render2SoapIn" />
    <wsdl:output message="tns:Render2SoapOut" />
</wsdl:operation>
<wsdl:operation name="DeliverReportItem">
    <wsdl:input message="tns:DeliverReportItemSoapIn" />
    <wsdl:output message="tns:DeliverReportItemSoapOut" />
</wsdl:operation>
<wsdl:operation name="RenderStream">
    <wsdl:input message="tns:RenderStreamSoapIn" />
    <wsdl:output message="tns:RenderStreamSoapOut" />
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo">
    <wsdl:input message="tns:GetExecutionInfoSoapIn" />
    <wsdl:output message="tns:GetExecutionInfoSoapOut" />
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo2">
    <wsdl:input message="tns:GetExecutionInfo2SoapIn" />
    <wsdl:output message="tns:GetExecutionInfo2SoapOut" />
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo3">
    <wsdl:input message="tns:GetExecutionInfo3SoapIn" />
    <wsdl:output message="tns:GetExecutionInfo3SoapOut" />
</wsdl:operation>
<wsdl:operation name="GetDocumentMap">
    <wsdl:input message="tns:GetDocumentMapSoapIn" />
    <wsdl:output message="tns:GetDocumentMapSoapOut" />
</wsdl:operation>

```

```

<wsdl:operation name="LoadDrillthroughTarget">
  <wsdl:input message="tns:LoadDrillthroughTargetSoapIn" />
  <wsdl:output message="tns:LoadDrillthroughTargetSoapOut" />
</wsdl:operation>
<wsdl:operation name="LoadDrillthroughTarget2">
  <wsdl:input message="tns:LoadDrillthroughTarget2SoapIn" />
  <wsdl:output message="tns:LoadDrillthroughTarget2SoapOut" />
</wsdl:operation>
<wsdl:operation name="LoadDrillthroughTarget3">
  <wsdl:input message="tns:LoadDrillthroughTarget3SoapIn" />
  <wsdl:output message="tns:LoadDrillthroughTarget3SoapOut" />
</wsdl:operation>
<wsdl:operation name="ToggleItem">
  <wsdl:input message="tns:ToggleItemSoapIn" />
  <wsdl:output message="tns:ToggleItemSoapOut" />
</wsdl:operation>
<wsdl:operation name="NavigateDocumentMap">
  <wsdl:input message="tns:NavigateDocumentMapSoapIn" />
  <wsdl:output message="tns:NavigateDocumentMapSoapOut" />
</wsdl:operation>
<wsdl:operation name="NavigateBookmark">
  <wsdl:input message="tns:NavigateBookmarkSoapIn" />
  <wsdl:output message="tns:NavigateBookmarkSoapOut" />
</wsdl:operation>
<wsdl:operation name="FindString">
  <wsdl:input message="tns:FindStringSoapIn" />
  <wsdl:output message="tns:FindStringSoapOut" />
</wsdl:operation>
<wsdl:operation name="Sort">
  <wsdl:input message="tns:SortSoapIn" />
  <wsdl:output message="tns:SortSoapOut" />
</wsdl:operation>
<wsdl:operation name="Sort2">
  <wsdl:input message="tns:Sort2SoapIn" />
  <wsdl:output message="tns:Sort2SoapOut" />
</wsdl:operation>
<wsdl:operation name="Sort3">
  <wsdl:input message="tns:Sort3SoapIn" />
  <wsdl:output message="tns:Sort3SoapOut" />
</wsdl:operation>
<wsdl:operation name="GetRenderResource">
  <wsdl:input message="tns:GetRenderResourceSoapIn" />
  <wsdl:output message="tns:GetRenderResourceSoapOut" />
</wsdl:operation>
<wsdl:operation name="ListRenderingExtensions">
  <wsdl:input message="tns>ListRenderingExtensionsSoapIn" />
  <wsdl:output message="tns>ListRenderingExtensionsSoapOut" />
</wsdl:operation>
<wsdl:operation name="LogonUser">
  <wsdl:input message="tns:LogonUserSoapIn" />
  <wsdl:output message="tns:LogonUserSoapOut" />
</wsdl:operation>
<wsdl:operation name="Logoff">
  <wsdl:input message="tns:LogoffSoapIn" />
  <wsdl:output message="tns:LogoffSoapOut" />
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="ReportExecutionServiceSoap" type="tns:ReportExecutionServiceSoap">
  <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="ListSecureMethods">
    <soap:operation
      soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Lis
      tSecureMethods" style="document" />
    <wsdl:input>
      <soap:body use="literal" />
      <soap:header message="tns>ListSecureMethodsTrustedUserHeader"
      part="TrustedUserHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>

```

```

<soap:body use="literal" />
<soap:header message="tns>ListSecureMethodsServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReport">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReport" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadReportTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:LoadReportExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:LoadReportServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReport3">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReport3" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadReport3TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:LoadReport3ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:LoadReport3ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReport2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReport2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadReport2TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:LoadReport2ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:LoadReport2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReportDefinition">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReportDefinition" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadReportDefinitionTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:LoadReportDefinitionExecutionHeader" part="ExecutionHeader"
use="literal" />

```

```

<soap:header message="tns:LoadReportDefinitionServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReportDefinition2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReportDefinition2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadReportDefinition2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:LoadReportDefinition2ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:LoadReportDefinition2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReportDefinition3">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReportDefinition3" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadReportDefinition3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:LoadReportDefinition3ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:LoadReportDefinition3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionCredentials">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionCredentials" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionCredentialsExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:SetExecutionCredentialsTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionCredentialsServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionCredentials2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionCredentials2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionCredentials2ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:SetExecutionCredentials2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />

```

```

<soap:header message="tns:SetExecutionCredentials2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionCredentials3">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionCredentials3" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionCredentials3ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:SetExecutionCredentials3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionCredentials3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionParameters" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionParametersExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:SetExecutionParametersTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionParametersServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionParameters2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionParameters2ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:SetExecutionParameters2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionParameters2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters3">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionParameters3" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:SetExecutionParameters3ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:SetExecutionParameters3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />

```

```

<soap:header message="tns:SetExecutionParameters3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ResetExecution">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Res
etExecution" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:ResetExecutionExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:ResetExecutionTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:ResetExecutionServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ResetExecution2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Res
etExecution2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:ResetExecution2ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:ResetExecution2TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:ResetExecution2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ResetExecution3">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Res
etExecution3" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:ResetExecution3ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:ResetExecution3TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:ResetExecution3ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="Render">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Ren
der" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:RenderExecutionHeader" part="ExecutionHeader" use="literal"
/>
<soap:header message="tns:RenderTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />

```

```

<soap:header message="tns:RenderServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="Render2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Ren
der2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:Render2ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:Render2TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:Render2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeliverReportItem">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Del
iverReportItem" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:DeliverReportItemExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:DeliverReportItemTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:DeliverReportItemServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="RenderStream">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Ren
derStream" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:RenderStreamExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:RenderStreamTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:RenderStreamServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
ExecutionInfo" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:GetExecutionInfoExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:GetExecutionInfoTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />

```

```

<soap:header message="tns:GetExecutionInfoServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
ExecutionInfo2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:GetExecutionInfo2ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:GetExecutionInfo2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:GetExecutionInfo2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo3">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
ExecutionInfo3" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:GetExecutionInfo3ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:GetExecutionInfo3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:GetExecutionInfo3ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDocumentMap">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
DocumentMap" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:GetDocumentMapExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:GetDocumentMapTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:GetDocumentMapServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadDrillthroughTarget">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dDrillthroughTarget" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadDrillthroughTargetExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:LoadDrillthroughTargetTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />

```

```

<soap:header message="tns:LoadDrillthroughTargetExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:LoadDrillthroughTargetServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadDrillthroughTarget2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dDrillthroughTarget2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadDrillthroughTarget2ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:LoadDrillthroughTarget2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:LoadDrillthroughTarget2ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:LoadDrillthroughTarget2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadDrillthroughTarget3">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dDrillthroughTarget3" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:LoadDrillthroughTarget3ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:LoadDrillthroughTarget3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:LoadDrillthroughTarget3ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap:header message="tns:LoadDrillthroughTarget3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ToggleItem">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Tog
gleItem" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:ToggleItemExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:ToggleItemTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:ToggleItemServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="NavigateDocumentMap">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Nav
igateDocumentMap" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:NavigateDocumentMapExecutionHeader" part="ExecutionHeader"
use="literal" />

```

```

<soap:header message="tns:.NavigateDocumentMapTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:.NavigateDocumentMapServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="NavigateBookmark">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/NavigateBookmark" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:.NavigateBookmarkExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:.NavigateBookmarkTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:.NavigateBookmarkServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="FindString">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/FindString" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:FindStringExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap:header message="tns:FindStringTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:FindStringServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="Sort">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Sort" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:SortExecutionHeader" part="ExecutionHeader" use="literal"
/>
<soap:header message="tns:SortTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
<soap:header message="tns:SortServerInfoHeader" part="ServerInfoHeader" use="literal"
/>
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="Sort2">
<soap:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Sort2" style="document" />
<wsdl:input>
<soap:body use="literal" />
<soap:header message="tns:Sort2ExecutionHeader" part="ExecutionHeader" use="literal"
/>

```

```

<soap:header message="tns:Sort2TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
    <soap:body use="literal" />
    <soap:header message="tns:Sort2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="Sort3">
    <soap:operation
    soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Sor
t3" style="document" />
    <wsdl:input>
        <soap:body use="literal" />
        <soap:header message="tns:Sort3ExecutionHeader" part="ExecutionHeader" use="literal"
    />
        <soap:header message="tns:Sort3TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
            <soap:header message="tns:Sort3ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="GetRenderResource">
            <soap:operation
            soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
RenderResource" style="document" />
            <wsdl:input>
                <soap:body use="literal" />
                <soap:header message="tns:GetRenderResourceTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap:body use="literal" />
                <soap:header message="tns:GetRenderResourceServerInfoHeader" part="ServerInfoHeader"
use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="ListRenderingExtensions">
            <soap:operation
            soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Lis
tRenderingExtensions" style="document" />
            <wsdl:input>
                <soap:body use="literal" />
                <soap:header message="tns:ListRenderingExtensionsTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap:body use="literal" />
                <soap:header message="tns:ListRenderingExtensionsServerInfoHeader"
part="ServerInfoHeader" use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="LogonUser">
            <soap:operation
            soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Log
onUser" style="document" />
            <wsdl:input>
                <soap:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap:body use="literal" />
                <soap:header message="tns:LogonUserServerInfoHeader" part="ServerInfoHeader"
use="literal" />
            </wsdl:output>
        </wsdl:operation>
    </wsdl:output>

```

```

<wsdl:operation name="Logoff">
  <soap:operation
    soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Logoff" style="document" />
    <wsdl:input>
      <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" />
      <soap:header message="tns:LogoffServerInfoHeader" part="ServerInfoHeader" use="literal" />
    </wsdl:output>
  </wsdl:operation>
</wsdl:binding>
<wsdl:binding name="ReportExecutionServiceSoap12" type="tns:ReportExecutionServiceSoap">
  <soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
    <wsdl:operation name="ListSecureMethods">
      <soap12:operation
        soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/ListSecureMethods" style="document" />
        <wsdl:input>
          <soap12:body use="literal" />
          <soap12:header message="tns>ListSecureMethodsTrustedUserHeader" part="TrustedUserHeader" use="literal" />
        </wsdl:input>
        <wsdl:output>
          <soap12:body use="literal" />
          <soap12:header message="tns>ListSecureMethodsServerInfoHeader" part="ServerInfoHeader" use="literal" />
        </wsdl:output>
      </wsdl:operation>
      <wsdl:operation name="LoadReport">
        <soap12:operation
          soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/LoadReport" style="document" />
          <wsdl:input>
            <soap12:body use="literal" />
            <soap12:header message="tns:LoadReportTrustedUserHeader" part="TrustedUserHeader" use="literal" />
          </wsdl:input>
          <wsdl:output>
            <soap12:body use="literal" />
            <soap12:header message="tns:LoadReportExecutionHeader" part="ExecutionHeader" use="literal" />
            <soap12:header message="tns:LoadReportServerInfoHeader" part="ServerInfoHeader" use="literal" />
          </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="LoadReport3">
          <soap12:operation
            soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/LoadReport3" style="document" />
            <wsdl:input>
              <soap12:body use="literal" />
              <soap12:header message="tns:LoadReport3TrustedUserHeader" part="TrustedUserHeader" use="literal" />
            </wsdl:input>
            <wsdl:output>
              <soap12:body use="literal" />
              <soap12:header message="tns:LoadReport3ExecutionHeader" part="ExecutionHeader" use="literal" />
              <soap12:header message="tns:LoadReport3ServerInfoHeader" part="ServerInfoHeader" use="literal" />
            </wsdl:output>
          </wsdl:operation>
          <wsdl:operation name="LoadReport2">
            <soap12:operation
              soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/LoadReport2" style="document" />

```

```

<wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:LoadReport2TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
    <soap12:header message="tns:LoadReport2ExecutionHeader" part="ExecutionHeader"
use="literal" />
    <soap12:header message="tns:LoadReport2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReportDefinition">
    <soap12:operation
        soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReportDefinition" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:LoadReportDefinitionTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
    <soap12:header message="tns:LoadReportDefinitionExecutionHeader"
part="ExecutionHeader" use="literal" />
    <soap12:header message="tns:LoadReportDefinitionServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReportDefinition2">
    <soap12:operation
        soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReportDefinition2" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:LoadReportDefinition2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
    <soap12:header message="tns:LoadReportDefinition2ExecutionHeader"
part="ExecutionHeader" use="literal" />
    <soap12:header message="tns:LoadReportDefinition2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadReportDefinition3">
    <soap12:operation
        soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dReportDefinition3" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:LoadReportDefinition3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
    <soap12:header message="tns:LoadReportDefinition3ExecutionHeader"
part="ExecutionHeader" use="literal" />
    <soap12:header message="tns:LoadReportDefinition3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionCredentials">
    <soap12:operation
        soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionCredentials" style="document" />
<wsdl:input>

```

```

        <soap12:body use="literal" />
        <soap12:header message="tns:SetExecutionCredentialsExecutionHeader"
part="ExecutionHeader" use="literal" />
            <soap12:header message="tns:SetExecutionCredentialsTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
            <soap12:header message="tns:SetExecutionCredentialsServerInfoHeader"
part="ServerInfoHeader" use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="SetExecutionCredentials2">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionCredentials2" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:SetExecutionCredentials2ExecutionHeader"
part="ExecutionHeader" use="literal" />
    <soap12:header message="tns:SetExecutionCredentials2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
        <soap12:header message="tns:SetExecutionCredentials2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionCredentials3">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionCredentials3" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:SetExecutionCredentials3ExecutionHeader"
part="ExecutionHeader" use="literal" />
    <soap12:header message="tns:SetExecutionCredentials3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
        <soap12:header message="tns:SetExecutionCredentials3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionParameters" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:SetExecutionParametersExecutionHeader"
part="ExecutionHeader" use="literal" />
    <soap12:header message="tns:SetExecutionParametersTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
        <soap12:header message="tns:SetExecutionParametersServerInfoHeader"
part="ServerInfoHeader" use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters2">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionParameters2" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />

```

```

<soap12:header message="tns:SetExecutionParameters2ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap12:header message="tns:SetExecutionParameters2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:SetExecutionParameters2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetExecutionParameters3">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Set
ExecutionParameters3" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:SetExecutionParameters3ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap12:header message="tns:SetExecutionParameters3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:SetExecutionParameters3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ResetExecution">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Res
etExecution" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:ResetExecutionExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:ResetExecutionTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:ResetExecutionServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ResetExecution2">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Res
etExecution2" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:ResetExecution2ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:ResetExecution2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:ResetExecution2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ResetExecution3">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Res
etExecution3" style="document" />
<wsdl:input>
<soap12:body use="literal" />

```

```

<soap12:header message="tns:ResetExecution3ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:ResetExecution3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:ResetExecution3ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="Render">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Ren
der" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:RenderExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:RenderTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:RenderServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="Render2">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Ren
der2" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:Render2ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:Render2TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:Render2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeliverReportItem">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Del
iverReportItem" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:DeliverReportItemExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:DeliverReportItemTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:DeliverReportItemServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="RenderStream">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Ren
derStream" style="document" />
<wsdl:input>
<soap12:body use="literal" />

```

```

<soap12:header message="tns:RenderStreamExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:RenderStreamTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:RenderStreamServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
ExecutionInfo" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:GetExecutionInfoExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:GetExecutionInfoTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:GetExecutionInfoServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo2">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
ExecutionInfo2" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:GetExecutionInfo2ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:GetExecutionInfo2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:GetExecutionInfo2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetExecutionInfo3">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
ExecutionInfo3" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:GetExecutionInfo3ExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:GetExecutionInfo3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:GetExecutionInfo3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDocumentMap">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
DocumentMap" style="document" />
<wsdl:input>
<soap12:body use="literal" />

```

```

<soap12:header message="tns:GetDocumentMapExecutionHeader" part="ExecutionHeader"
use="literal" />
<soap12:header message="tns:GetDocumentMapTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:GetDocumentMapServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadDrillthroughTarget">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dDrillthroughTarget" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:LoadDrillthroughTargetExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap12:header message="tns:LoadDrillthroughTargetTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:LoadDrillthroughTargetExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap12:header message="tns:LoadDrillthroughTargetServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadDrillthroughTarget2">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dDrillthroughTarget2" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:LoadDrillthroughTarget2ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap12:header message="tns:LoadDrillthroughTarget2TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:LoadDrillthroughTarget2ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap12:header message="tns:LoadDrillthroughTarget2ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LoadDrillthroughTarget3">
<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Loa
dDrillthroughTarget3" style="document" />
<wsdl:input>
<soap12:body use="literal" />
<soap12:header message="tns:LoadDrillthroughTarget3ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap12:header message="tns:LoadDrillthroughTarget3TrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
<soap12:header message="tns:LoadDrillthroughTarget3ExecutionHeader"
part="ExecutionHeader" use="literal" />
<soap12:header message="tns:LoadDrillthroughTarget3ServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ToggleItem">

```

```

<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/ToggleItem" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:ToggleItemExecutionHeader" part="ExecutionHeader" use="literal" />
        <soap12:header message="tns:ToggleItemTrustedUserHeader" part="TrustedUserHeader" use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
                <soap12:header message="tns:ToggleItemServerInfoHeader" part="ServerInfoHeader" use="literal" />
            </wsdl:output>
        </wsdl:operation>
<wsdl:operation name="NavigateDocumentMap">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/NavigateDocumentMap" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:ExecuteHeader" part="ExecutionHeader" use="literal" />
            <soap12:header message="tns:ExecuteTrustedUserHeader" part="TrustedUserHeader" use="literal" />
                </wsdl:input>
                <wsdl:output>
                    <soap12:body use="literal" />
                    <soap12:header message="tns:ExecuteServerInfoHeader" part="ServerInfoHeader" use="literal" />
                </wsdl:output>
            </wsdl:operation>
<wsdl:operation name="NavigateBookmark">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/NavigateBookmark" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:ExecuteHeader" part="ExecutionHeader" use="literal" />
            <soap12:header message="tns:ExecuteTrustedUserHeader" part="TrustedUserHeader" use="literal" />
                </wsdl:input>
                <wsdl:output>
                    <soap12:body use="literal" />
                    <soap12:header message="tns:ExecuteServerInfoHeader" part="ServerInfoHeader" use="literal" />
                </wsdl:output>
            </wsdl:operation>
<wsdl:operation name="FindString">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/FindString" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:ExecuteHeader" part="ExecutionHeader" use="literal" />
            <soap12:header message="tns:ExecuteTrustedUserHeader" part="TrustedUserHeader" use="literal" />
                </wsdl:input>
                <wsdl:output>
                    <soap12:body use="literal" />
                    <soap12:header message="tns:ExecuteServerInfoHeader" part="ServerInfoHeader" use="literal" />
                </wsdl:output>
            </wsdl:operation>
<wsdl:operation name="Sort">

```

```

<soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Sor
t" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:SortExecutionHeader" part="ExecutionHeader" use="literal"
/>
    <soap12:header message="tns:SortTrustedUserHeader" part="TrustedUserHeader"
use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
    <soap12:header message="tns:SortServerInfoHeader" part="ServerInfoHeader"
use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="Sort2">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Sor
t2" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:Sort2ExecutionHeader" part="ExecutionHeader"
use="literal" />
        <soap12:header message="tns:Sort2TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
        <soap12:header message="tns:Sort2ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="Sort3">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Sor
t3" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:Sort3ExecutionHeader" part="ExecutionHeader"
use="literal" />
        <soap12:header message="tns:Sort3TrustedUserHeader" part="TrustedUserHeader"
use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
        <soap12:header message="tns:Sort3ServerInfoHeader" part="ServerInfoHeader"
use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetRenderResource">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Get
RenderResource" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:GetRenderResourceTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
        <soap12:header message="tns:GetRenderResourceServerInfoHeader"
part="ServerInfoHeader" use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ListRenderingExtensions">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Lis
tRenderingExtensions" style="document" />

```

```

<wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:ListRenderingExtensionsTrustedUserHeader"
part="TrustedUserHeader" use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
    <soap12:header message="tns:ListRenderingExtensionsServerInfoHeader"
part="ServerInfoHeader" use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="LogonUser">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Log
onUser" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
        <soap12:header message="tns:LogonUserServerInfoHeader" part="ServerInfoHeader"
use="literal" />
    </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="Logoff">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sqlserver/2005/06/30/reporting/reportingservices/Log
off" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
        <soap12:header message="tns:LogoffServerInfoHeader" part="ServerInfoHeader"
use="literal" />
    </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
<wsdl:service name="ReportExecutionService">
    <wsdl:documentation xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">The Reporting Services
Execution Service enables report execution</wsdl:documentation>
    <wsdl:port name="ReportExecutionServiceSoap" binding="tns:ReportExecutionServiceSoap">
        <soap:address
location="%ReportServerServiceObjectURL%"="http://localhost:80/ReportServer/ReportExecution20
05.asmx" />
    </wsdl:port>
    <wsdl:port name="ReportExecutionServiceSoap12"
binding="tns:ReportExecutionServiceSoap12">
        <soap12:address
location="%ReportServerServiceObjectURL%"="http://localhost:80/ReportServer/ReportExecution20
05.asmx" />
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

4 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs[‡].

- Microsoft SQL Server 2005
- Microsoft SQL Server 2008
- Microsoft SQL Server 2008 R2
- Microsoft SQL Server 2012
- Microsoft SQL Server 2014
- Microsoft SQL Server 2016

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

<1> Section 2.1: Microsoft SQL Server 2005 Reporting Services and Microsoft SQL Server 2008 Reporting Services do not fully support SOAP 1.2 [SOAP1.2-1/2007].

<2> Section 2.2.2: The **DeliverReportItem** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014, and it does not work with report servers configured in Microsoft SharePoint integrated mode.

<3> Section 2.2.2: The **GetExecutionInfo3** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

<4> Section 2.2.2: The **LoadDrillthroughTarget3** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

<5> Section 2.2.2: The **LoadReport3** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

<6> Section 2.2.2: The **LoadReportDefinition3** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

<7> Section 2.2.2: The **ResetExecution3** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

<8> Section 2.2.2: The **SetExecutionCredentials3** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

<9> Section 2.2.2: The **SetExecutionParameters3** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

<10> Section 2.2.2: The **Sort3** method is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

<11> Section 2.2.3: The **ExecutionInfo3** type is not available in SQL Server 2005, SQL Server 2008, SQL Server 2008 R2, SQL Server 2012, and SQL Server 2014.

| [<12>](#) Section 2.2.4: In SQL Server 2005 Reporting Services, **TrustedUserHeader** does not support the SQL Server infrastructure.

5 Change Tracking

No table of This section identifies changes is available. The that were made to this document is either new or has had no changes since it's the last release. Changes are classified as New, Major, Minor, Editorial, or No change.

6—The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

| <u>Section</u> | <u>Tracking number (if applicable) and description</u> | <u>Major change (Y or N)</u> | <u>Change type</u> |
|--|---|------------------------------|---------------------------------|
| 2.2.2 Methods | Added description for DeliverReportItem, GetExecutionInfo3, LoadDrillthroughTarget3, LoadReport3, LoadReportDefinition3, ResetExecution3, SetExecutionCredentials3, SetExecutionParameters3, and Sort3. | Y | Content update. |
| 2.2.3 Types | Added descriptions for ExecutionInfo3, ParameterFieldReference, ParametersGridCellDefinition, and ParametersGridLayoutDefinition.. | Y | Content update. |
| 3 Appendix A: Full WSDL | Updated WSDL for SQL Server 2016. | Y | Content update. |
| 4 Appendix B: Product Behavior | Added SQL Server 2016 to product applicability list. | Y | Content update. |

6 Index

A

[Applicability](#) 9
Applicability statement 9
authentication (section 1.3 7, section 1.5 9)

C

[Capability negotiation](#) 9

Change tracking 61
channel encryption 7
classes 10

10

D

data types 10
DataSourceCredentials type 14
DataSourcePrompt type 14
DocumentMapNode type 14

13

E

enumerations 10
ExecutionHeader SOAP header 15
ExecutionInfo type 14
ExecutionInfo2 type 14
Extension type 14
ExtensionTypeEnum type 14

13

F

[Fields - vendor-extensible](#) 9
FindString method 12
[Full WSDL](#) 16

G

GetDocumentMap method 12
GetExecutionInfo method 12
GetExecutionInfo2 12
GetRenderResource method 12
[Glossary](#) 5

H

HTTP protocol 7
HTTPS protocol 7

§

I

[informative](#)
[Informative](#) references 6
inherited classes 10
[Introduction](#) 5

L

ListRenderingExtensions method 12
ListSecureMethods 12
LoadDrillthroughTarget method 12
LoadDrillthroughTarget2 method 12

LoadReport method 12[12](#)
LoadReport2 method 12[12](#)
LoadReportDefinition method 12[12](#)
LoadReportDefinition2 method 12[12](#)
Logoff method 12[12](#)
LogonUser method 12
[12](#)

M

mapping types 10[10](#)
Messages (section 2 10[10](#), [section 2.2 10](#))
[methods \(](#)[_section 2.2 10](#), [_section 2.2.2 10](#)[\)\)](#)
[_transport](#) 10
[methods \(](#)[section 2.2 10](#), [section 2.2.2 12](#)[\)](#)

N

namespaces 11[11](#)
NavigateBookmark method 12[12](#)
NavigateDocumentMap method 12[12](#)
[normative](#)[Normative](#) references 6
[5](#)

O

out parameters 10[10](#)
[Overview \(synopsis\)](#) 7

P

PageCountMode type 14[13](#)
PageSettings type 14[13](#)
ParameterStateEnum type 14[13](#)
ParameterTypeEnum type 14[13](#)
ParameterValue type 14[13](#)
ParameterValueOrFieldReference type 14[13](#)
[Preconditions](#) 9
[Prerequisites](#) 9
prescriptive API references 6[6](#)
[Product behavior](#) 59
protocol server endpoint 9[8](#)
protocols 9[8](#)
public properties 10
[10](#)

R

[references](#)

[References](#) 5
informative 6[6](#)
normative 6[5](#)
prescriptive 6[6](#)
[Relationship to other protocols](#) 9
Render method 12[12](#)
Render2 method 12[12](#)
RenderStream method 12[12](#)
report server 7[6](#)
ReportExecution2005
about 7[6](#)
classes 10[10](#)
data types 10[10](#)
messages 10[10](#)
methods (section 2.2 10[10](#), [section 2.2.2 12](#)[12](#)[\)\)](#)
protocol server endpoint 9[8](#)
protocols 9[8](#)
security 7[6](#)

supported transports (section 1.7 97, section 2.1 1010)

types 1413

ReportMargins type 1413

ReportPaperSize type 1413

ReportParameter type 1413

ResetExecution method 1212

ResetExecution2 method 12

12

S

security 76

ServerInfoHeader SOAP header 1514

SetExecutionCredentials method 1212

SetExecutionCredentials2 method 1212

SetExecutionParameters method 1212

SetExecutionParameters2 method 1212

SOAP headers 1514

SOAP over HTTP (section 1.4 98, section 2.1 1010)

SOAP over HTTPS (section 1.4 98, section 2.1 1010)

SOAP 1.2 binding 53

Sort method 1212

Sort2 method 1212

SortDirectionEnum type 1413

Standards assignments 9

T

ToggleItem method 1212

Tracking changes 6154

Transport 10

transports 1010

TrustedUserHeader SOAP header 1514

type definitions 14

13

V

ValidValue type 14

Vendor-extensible fields 913

Versioning 9

W

Warning type 1413

WSDL 16

WSDL XML Schema types 10

10

X

XML namespaces 11

11