

# [MS-SCCSTR]:

## SqlClient Connection String Structure

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
4/21/2010	0.1	Major	First release.
6/4/2010	0.1.1	Editorial	Changed language and formatting in the technical content.
9/3/2010	0.1.1	None	No changes to the meaning, language, or formatting of the technical content.
2/9/2011	0.1.1	None	No changes to the meaning, language, or formatting of the technical content.
7/7/2011	0.1.1	None	No changes to the meaning, language, or formatting of the technical content.
11/3/2011	2.0	Major	Updated and revised the technical content.
1/19/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
2/23/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
3/27/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
5/24/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
6/29/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
7/16/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
10/8/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
10/23/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
3/26/2013	2.0	None	No changes to the meaning, language, or formatting of the technical content.
6/11/2013	3.0	Major	Updated and revised the technical content.
8/8/2013	3.0	None	No changes to the meaning, language, or formatting of the technical content.
12/5/2013	4.0	Major	Updated and revised the technical content.
2/11/2014	5.0	Major	Updated and revised the technical content.
5/20/2014	5.0	None	No changes to the meaning, language, or formatting of the technical content.
6/30/2015	6.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>4</b>
1.1	Glossary .....	4
1.2	References .....	6
1.2.1	Normative References .....	6
1.2.2	Informative References .....	7
1.3	Overview .....	7
1.4	Relationship to Protocols and Other Structures .....	8
1.5	Applicability Statement .....	8
1.6	Versioning and Localization .....	8
1.7	Vendor-Extensible Fields .....	8
<b>2</b>	<b>Structures .....</b>	<b>9</b>
2.1	SqlClient Connection String .....	9
2.1.1	Guidelines.....	10
2.1.2	Restrictions.....	11
2.2	Keys and Values .....	11
<b>3</b>	<b>Structure Examples .....</b>	<b>19</b>
3.1	Trusted Connection .....	19
3.2	Standard Security Connection.....	19
3.3	Named Instance.....	19
3.4	SQL Server Express LocalDB Default Instance.....	20
3.5	Escaped Single Quote .....	20
<b>4</b>	<b>Security.....</b>	<b>21</b>
4.1	Security Considerations for Implementers .....	21
4.2	Index of Security Fields .....	21
<b>5</b>	<b>Appendix A: Product Behavior .....</b>	<b>22</b>
<b>6</b>	<b>Change Tracking.....</b>	<b>26</b>
<b>7</b>	<b>Index.....</b>	<b>28</b>

# 1 Introduction

The SqlConnection Connection String structure specifies the format of the **connection strings** that are used by Microsoft .NET Framework **applications** that connect to Microsoft SQL Server by using the Microsoft .NET Framework Data Provider for SQL Server ("SqlConnection"). SqlConnection is a set of .NET Framework classes that are designed to enable developers to query, update, insert, and delete data on SQL Server.

A connection string is a series of arguments, delimited by a semicolon, that describe the location of a database and how to connect to it.

Sections 1.7 and 2 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in [\[RFC2119\]](#). All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are specific to this document:

**.NET Framework:** An integral Windows component that supports building and running applications and XML web services. The .NET Framework has two main components: the common language runtime and the .NET Framework class library. For more information about the .NET Framework, see [\[MSDN-.NET-FRAMEWORK\]](#). The following versions of the .NET Framework are available in the following released Windows products or as supplemental software. Microsoft .NET Framework 1.0: Windows NT 4.0 operating system, Microsoft Windows 98 operating system, Windows 2000 operating system, Windows Millennium Edition operating system, Windows XP operating system, and Windows Server 2003 operating system. Microsoft .NET Framework 1.1: Windows 98, Windows 2000, Windows Millennium Edition, Windows XP, Windows Server 2003, Windows Server 2003 R2 operating system, Windows Vista operating system, and Windows Server 2008 operating system. Microsoft .NET Framework 2.0: Windows 98, Windows 2000, Windows Millennium Edition, Windows XP, Windows Server 2003, Windows Server 2003 R2, Windows Vista, Windows Server 2008, Windows 7 operating system, Windows Server 2008 R2 operating system, Windows 8 operating system, Windows Server 2012 operating system, Windows 8.1 operating system, Windows Server 2012 R2 operating system, Windows 10 operating system, and Windows Server 2016 Technical Preview operating system. Microsoft .NET Framework 3.0: Windows XP, Windows Server 2003, Windows Server 2003 R2, Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, and Windows Server 2016 Technical Preview. Microsoft .NET Framework 3.5: Windows XP, Windows Server 2003, Windows Server 2003 R2, Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, and Windows Server 2016 Technical Preview. Microsoft .NET Framework 4.0: Windows XP, Windows Server 2003, Windows Server 2003 R2, Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, and Windows Server 2016 Technical Preview. Microsoft .NET Framework 4.5: Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, and Windows 10. Microsoft .NET Framework 4.6: Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, and Windows 10.

**Active Directory:** A general-purpose network directory service. **Active Directory** also refers to the Windows implementation of a directory service. **Active Directory** stores information about a variety of objects in the network. Importantly, user accounts, computer accounts, groups, and all related credential information used by the Windows implementation of Kerberos are stored in **Active Directory**. **Active Directory** is either deployed as Active Directory Domain Services (AD DS) or Active Directory Lightweight Directory Services (AD LDS). [\[MS-ADTS\]](#) describes both

forms. For more information, see [\[MS-AUTHSOD\]](#) section 1.1.1.5.2, Lightweight Directory Access Protocol (LDAP) versions 2 and 3, Kerberos, and DNS.

**application:** A participant that is responsible for beginning, propagating, and completing an atomic transaction. An application communicates with a transaction manager in order to begin and complete transactions. An application communicates with a transaction manager in order to marshal transactions to and from other applications. An application also communicates in application-specific ways with a resource manager in order to submit requests for work on resources.

**Augmented Backus-Naur Form (ABNF):** A modified version of Backus-Naur Form (BNF), commonly used by Internet specifications. ABNF notation balances compactness and simplicity with reasonable representational power. ABNF differs from standard BNF in its definitions and uses of naming rules, repetition, alternatives, order-independence, and value ranges. For more information, see [\[RFC5234\]](#).

**authentication:** The act of proving an identity to a server while providing key material that binds the identity to subsequent communications.

**certificate chain:** A sequence of certificates (1), where each certificate in the sequence is signed by the subsequent certificate. The last certificate in the chain is normally a self-signed certificate.

**connection:** Each user that has a session with a server can create multiple share connections, or resource connections, using that user ID. This resource connection is created using a tree connect Server Message Block (SMB) and is identified by an SMB TreeID or TID.

**connection pool:** A cache of opened connections to data sources.

**connection string:** A series of arguments, delimited by a semicolon, that defines the location of a database and how to connect to it.

**context:** A collection of context properties that describe an execution environment.

**credential:** Previously established, **authentication** data that is used by a security principal to establish its own identity. When used in reference to the Netlogon Protocol, it is the data that is stored in the NETLOGON\_CREDENTIAL structure.

**data source:** A database, web service, disk, file, or other collection of information from which data is queried or submitted. Supported data sources vary based on application and data provider.

**database instance:** A database that has a unique set of services that can have unique settings.

**database mirroring:** An availability solution that is based on keeping copies of the same database in different servers.

**default database:** The current database just after the connection is made.

**encryption:** In cryptography, the process of obscuring information to make it unreadable without special knowledge.

**federated authentication:** An authentication mechanism that allows a **security token service (STS)** in one trust domain to delegate user authentication to an **identity provider** in another trust domain, while generating a **security token** for the user, when there is a trust relationship between the two domains.

**identity provider:** A web service that performs identity verification as part of its processing.

**idle connection:** An active connection that was opened but that does not have any pending data.

**in-process connection:** A connection that is opened from within the server, such as a connection that is opened by a .NET stored procedure.

**Multiple Active Result Sets (MARS):** A feature in SQL Server that allows applications to have more than one pending request per connection. For more information, see [\[MSDN-MARS\]](#).

**named pipe:** A named, one-way, or duplex pipe for communication between a pipe server and one or more pipe clients.

**remote procedure call (RPC):** A context-dependent term commonly overloaded with three meanings. Note that much of the industry literature concerning RPC technologies uses this term interchangeably for any of the three meanings. Following are the three definitions: (\*) The runtime environment providing remote procedure call facilities. The preferred usage for this meaning is "RPC runtime". (\*) The pattern of request and response message exchange between two parties (typically, a client and a server). The preferred usage for this meaning is "RPC exchange". (\*) A single message from an exchange as defined in the previous definition. The preferred usage for this term is "RPC message". For more information about RPC, see [\[C706\]](#).

**replication:** The process of propagating the effects of all originating writes to any replica of a naming context (NC), to all replicas of the NC. If originating writes cease and replication continues, all replicas converge to a common application-visible state.

**security token:** An opaque data packet that is provided to an authorized user of computer services to facilitate authentication.

**security token service (STS):** A web service that issues **security tokens**. That is, it makes assertions based on evidence that it trusts; these assertions are for consumption by whoever trusts it.

**transaction:** In OleTx, an atomic transaction.

**Unicode:** A character encoding standard developed by the Unicode Consortium that represents almost all of the written languages of the world. The **Unicode** standard [\[UNICODE5.0.0/2007\]](#) provides three forms (UTF-8, UTF-16, and UTF-32) and seven schemes (UTF-8, UTF-16, UTF-16 BE, UTF-16 LE, UTF-32, UTF-32 LE, and UTF-32 BE).

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[MS-TDS] Microsoft Corporation, "[Tabular Data Stream Protocol](#)".

[RFC1002] Network Working Group, "Protocol Standard for a NetBIOS Service on a TCP/UDP Transport: Detailed Specifications", STD 19, RFC 1002, March 1987, <http://www.rfc-editor.org/rfc/rfc1002.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2460] Deering, S., and Hinden, R., "Internet Protocol, Version 6 (IPv6) Specification", RFC 2460, December 1998, <http://www.rfc-editor.org/rfc/rfc2460.txt>

[RFC4120] Neuman, C., Yu, T., Hartman, S., and Raeburn, K., "The Kerberos Network Authentication Service (V5)", RFC 4120, July 2005, <http://www.rfc-editor.org/rfc/rfc4120.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

[RFC791] Postel, J., Ed., "Internet Protocol: DARPA Internet Program Protocol Specification", RFC 791, September 1981, <http://www.rfc-editor.org/rfc/rfc791.txt>

[RFC793] Postel, J., Ed., "Transmission Control Protocol: DARPA Internet Program Protocol Specification", RFC 793, September 1981, <http://www.rfc-editor.org/rfc/rfc793.txt>

[UNICODE2.0.0] UNICODE, "Unicode 2.0.0", July 1996, <http://www.unicode.org/versions/Unicode2.0.0/>

## 1.2.2 Informative References

[MSDN-DAD] Microsoft Corporation, "Database Detach and Attach (SQL Server)", <http://msdn.microsoft.com/en-us/library/ms190794.aspx>

[MSDN-DLO] Microsoft Corporation, "default language Option", Administering SQL Server (SQL Server 2000), [http://msdn.microsoft.com/en-us/library/aa196707\(SQL.80\).aspx](http://msdn.microsoft.com/en-us/library/aa196707(SQL.80).aspx)

[MSDN-FILE] Microsoft Corporation, "Naming Files, Paths, and Namespaces", <http://msdn.microsoft.com/en-us/library/aa365247.aspx>

[MSDN-NETLIB] Microsoft Corporation, "Network Libraries", [http://msdn.microsoft.com/en-us/library/aa176603\(SQL.80\).aspx](http://msdn.microsoft.com/en-us/library/aa176603(SQL.80).aspx)

[MSDN-NP] Microsoft Corporation, "Named Pipes", <http://msdn.microsoft.com/en-us/library/aa365590.aspx>

[MSDN-NTLM] Microsoft Corporation, "Microsoft NTLM", <http://msdn.microsoft.com/en-us/library/aa378749.aspx>

[MSDN-SD] Microsoft Corporation, "Selecting a Database", SQL Server 2005 Books Online, <http://msdn.microsoft.com/en-us/library/ms180770.aspx>

[MSDN-UNI] Microsoft Corporation, "Using Named Instances", <http://msdn.microsoft.com/en-us/library/ms165614.aspx>

[MSKB-313295] Microsoft Corporation, "How to use the server name parameter in a connection string to specify the client network library", <http://support.microsoft.com/kb/313295>

[MSKB-328383] Microsoft Corporation, "SQL Server clients may change protocols when the client computers try to connect to an instance of SQL Server", <http://support.microsoft.com/kb/328383>

## 1.3 Overview

The SqlConnection Connection String Structure specifies a method for a .NET Framework application to specify the parameters that are used to connect to a **data source**. A connection string specifies a set of properties as keys and their associated values. The connection string can include one or more

key/value pairs to specify information such as the user identification, the password, the server name, and the database name. The values that are specified in the connection string affect the way an application connects to the data source.

## 1.4 Relationship to Protocols and Other Structures

Some of the properties of the SqlConnection connection string set specific tabular data stream (TDS) fields.

For more details, see section [2.2](#).

## 1.5 Applicability Statement

This document describes the format of SqlConnection connection strings that are used to establish a **connection** between a .NET Framework application and a SQL Server data source in scenarios where network or local connectivity is available. If network or local connectivity is not available, attempts to establish a connection will fail.

## 1.6 Versioning and Localization

The SqlConnection connection string **TypeSystemVersion** property (see section [2.2](#)) MUST be used to indicate the type of system that is expected by the .NET Framework application.

The SqlConnection connection string **PacketSize** property (see section 2.2) MUST be used to specify the packet size, in bytes, to use for the data exchange between a data source object and a database.

## 1.7 Vendor-Extensible Fields

None.



## 2 Structures

### 2.1 SqlClient Connection String

A SqlClient connection string MUST conform to the **Augmented Backus-Naur Form (ABNF)** [\[RFC5234\]](#) grammar. In accordance with section 2.4 of the RFC, this description assumes external encoding of **Unicode**.

```
SqlClientConnectionString = *(KeyValuePair SC) [KeyValuePair] *(WhiteSpace / NullTerm)

KeyValuePair=*WhiteSpace /
(*WhiteSpace Key *WhiteSpace EQ (*WhiteSpace / Value) *WhiteSpace)

Key="Addr" / "Address" / "App" / "ApplicationIntent" / "Application Name" / "Async" /
"Asynchronous Processing" / "AttachDBFilename" / "Authentication" / "Column Encryption
Setting" / "Connection Lifetime" / "Connection Reset" / "ConnectionRetryCount" /
"ConnectionRetryInterval" / "Connect Timeout" / "Connection Timeout" / "Context Connection" /
"Current Language" / "Database" / "Data Source" / "Encrypt" / "Enlist" / "Extended
Properties" / "Failover Partner" / "Initial Catalog" / "Initial File Name" / "Integrated
Security" / "Language" / "Load Balance Timeout" / "Max Pool Size" / "Min Pool Size" /
"MultipleActiveResultSets" / "MultiSubnetFailover" / "Net" / "Network" / "Network Address" /
"Network Library" / "Packet Size" / "Password" / "Persist Security Info" /
"PersistSecurityInfo" / "Pooling" / "PWD" / "Replication" / "Server" / "Timeout" /
"Transaction Binding" / "Trusted Connection" / "TrustServerCertificate" / "Type System
Version" / "UID" / "User" / "User ID" / "User Instance" / "Workstation ID" / "WSID"

Value= UnquotedValue / SingleQuotedValue / DoubleQuotedValue

SingleQuotedValue = SQUOTE *(NonNullSQuote / EscSQuote)SQUOTE
NonNullSQuote=%x0001 - %x0026 / %x0028-%xFFFF; not null, not single quote
EscSQuote=SQUOTE SQUOTE; Escaped single quote

DoubleQuotedValue = DQUOTE *( NonNullDQuote / EscDQuote) DQUOTE
NonNullDQuote= %x0001 - %x0021 / %x0023-%xFFFF; not null, not double quote
EscDQuote=DQUOTE DQUOTE; Escaped double quote

UnquotedValue = (UnquotedStart / (1*WhiteSpace EQ)) *NonCtrlSC UnquotedEnd

; not control chars, not white space, not single quote, not double quote, not semicolon
UnquotedEnd= UnquotedStart / EQ

; not control chars, not white space, not single quote, not double quote
; not semicolon, not equal sign
UnquotedStart=%x0021-%x0021 / %x0023-%x0026 / %x0028-%x003A /
%x003C / %x003E-%x007E / %x00A0-%x167F / %x1681-%x180D /
%x180F-%x1FFF / %x200B-%x2027 / %x202A-%x202E /
%x2030-%x205E / %x2060-%x2FFF / %x3001-%xFFFF

; not control chars, not semicolon,
NonCtrlSC=%x0020-%x003A / %x003C-%x007E / %x00A0-%xFFFF

WhiteSpace=SP / OSM / MVS / ENQD / EMQD / ENSP / EMSP / TPEMSP / FPEMSP / SPEMSP /
FSP / PSP / TSP / HSP / NNOBRKSP / MMSP / ISP / LS / PS / CHTAB / LF /
LNTAB / FF / CR / NL / NBRKSP

NullTerm= %x0000; NULL terminator (U+0000)
SP= %x0020; SPACE (U+0020)
OSM= %x1680; OGHAM SPACE MARK (U+1680)
MVS= %x180E; MONGOLIAN VOWEL SEPARATOR (U+180E)
ENQD= %x2000; EN QUAD (U+2000)
EMQD= %x2001; EM QUAD (U+2001)
ENSP= %x2002; EN SPACE (U+2002)
EMSP= %x2003; EM SPACE (U+2003)
TPEMSP= %x2004; THREE-PER-EM SPACE (U+2004)
FPEMSP= %x2005; FOUR-PER-EM SPACE (U+2005)
```

SPEMSP= %x2006; SIX-PER-EM SPACE (U+2006)  
 FSP= %x2007; FIGURE SPACE (U+2007)  
 PSP= %x2008; PUNCTUATION SPACE (U+2008)  
 TSP= %x2009; THIN SPACE (U+2009)  
 HSP= %x200A; HAIR SPACE (U+200A)  
 NNOBRKSP= %x202F ; NARROW NO-BREAK SPACE (U+202F)  
 MMSF= %x205F ; MEDIUM MATHEMATICAL SPACE (U+205F)  
 ISP= %x3000; IDEOGRAPHIC SPACE (U+3000);  
  
 LS= %x2028; LINE SEPARATOR character (U+2028)  
  
 PS= %x2029; PARAGRAPH SEPARATOR character (U+2029)  
  
 CHTAB= %x0009; CHARACTER TABULATION (U+0009)  
 LF= %x000A; LINE FEED (U+000A)  
 LNTAB= %x000B; LINE TABULATION (U+000B)  
 FF= %x000C; FORM FEED (U+000C)  
 CR= %x000D; CARRIAGE RETURN (U+000D)  
 NL= %x0085; NEXT LINE (U+0085)  
 NBRKSP= %x00A0; NO-BREAK SPACE (U+00A0)  
  
 SC= %x003B; SEMICOLON (U+003B)  
 EQ= %x003D; EQUAL SIGN (U+003D)  
 SQUOTE= %x0027; SINGLE QUOTE (U+0027)  
 DQUOTE= %x0022; DOUBLE QUOTE (U+0022)

### 2.1.1 Guidelines

The following list contains guidelines for the components of the SqlConnection Connection String.

- KeyValuePair
  - A **KeyValuePair** structure is a collection of keys and values in which each key is associated with one or more values. In a SqlConnection connection string, **KeyValuePair** structures follow the following format: key1=value1, key2=value2, and so on.
  - If only white spaces are inside a **KeyValuePair** structure, the **KeyValuePair** structure MUST be ignored.
- Key
  - Any white spaces that precede the **Key** value MUST be ignored.
  - Any white spaces that precede the **EQ** value MUST be ignored.
  - The **Key** value MUST be case insensitive.
- Value
  - The value in a **KeyValuePair** MUST be **UnquotedValue**, **SingleQuotedValue**, **DoubleQuotedValue**, or empty.
  - **UnquotedValue**, which starts with **EQ**, MUST be preceded by at least one space. **UnquotedValue** MUST NOT end with **SQUOTE** or **DQUOTE**.
  - A single quote symbol MUST be escaped to be used within **SingleQuotedValue** (use **EscSQuote**). A double quote symbol MUST be escaped to be used within **DoubleQuotedValue** (use **EscDQuote**).
  - Any white spaces that precede or trail **Value** MUST be ignored. **Value** MUST be case insensitive, with the exception of the value of **Password Key**. The value of **Password Key** MUST be case sensitive.

## 2.1.2 Restrictions

Only the keys specified in **Key** are valid in the SqlClient Connection String structure, and their meanings are described in section 2.2. Any other **KeyValuePair** properties MUST be treated as errors.

If there are duplicate keys, the last instance wins.

If **Context Connection** is set to "true", the only other key allowed is **Type System Version**.

If the **MultiSubnetFailover** key is set to "true", the **Failover Partner** key MUST NOT be allowed.

If the **ApplicationIntent** key is set to "ReadOnly", the **Failover Partner** key MUST NOT be allowed.

There MUST be no default values for keys if the **KeyValuePair** (whole pair) is missing, unless otherwise specified in section 2.2.

## 2.2 Keys and Values

The following table provides a list of all keys accepted as a SqlClient Connection String.

Keyword	Description
Addr	Synonym of the <b>Data Source</b> key.
Address	Synonym of the <b>Data Source</b> key.
App	Synonym of the <b>Application Name</b> key.
ApplicationIntent	When the value of this key is set to "ReadOnly", the client MUST request a read workload when connecting to an AlwaysOn-enabled database. The value of this key MUST be "ReadOnly" or "ReadWrite". The default value of this key is "ReadWrite".
Application Name	Sets the name of the application in the application identifier as specified by the <b>ibAppName</b> and <b>cchAppName</b> fields in section 2.2.6.4 of [MS-TDS]. The value of this key MUST be a string that has a maximum length of 128 characters. The default value of this key is ".NET SqlClient Data Provider".
Async	Synonym of the <b>Asynchronous Processing</b> key.
Asynchronous Processing<1>	When the value of this key is set to "true", asynchronous support MUST be enabled. The value of this key MUST be "true", "false", "yes", or "no". A value of "yes" MUST be treated the same as a value of "true". A value of "no" MUST be treated the same as a value of "false". The default value of this key is "false".
AttachDBFilename	Sets the name of the primary file of an attachable database<2> as specified by the <b>ibAtchDBFile</b> and <b>cchAtchDBFile</b> fields in section 2.2.6.4 of [MS-TDS]. The default value of this key is "". If the value of the <b>AttachDBFilename</b> key is specified in the connection string, the database is attached and becomes the <b>default database</b> for the connection. If this key is not specified and if the database was previously attached, the database will not be reattached. The previously attached database will be used as the default database for the connection. If this key is specified together with the <b>AttachDBFilename</b> key, the value of this key SHOULD be used as the alias. However, if the name is already used in another attached database, the connection MUST fail.

Keyword	Description
	<p>For more information about attachable databases, see <a href="#">[MSDN-DAD]</a>.  For more information about default databases, see <a href="#">[MSDN-SD]</a>.</p>
Authentication	<p>Specifies the authentication method that is used to authenticate a user. The value of this key MUST be one of the following:</p> <ul style="list-style-type: none"> <li>▪ "Sql Password": Indicates SQL Server authentication. If this value is specified, the <b>User ID</b> and <b>Password</b> keys MUST also be specified, unless the user name and the password are passed as a secure string by using SqlClient programming interfaces.</li> <li>▪ "Active Directory Password": Indicates <b>federated authentication</b> <a href="#">&lt;3&gt;</a> with user name and password. If this value is specified, the <b>User ID</b> and <b>Password</b> keys MUST also be specified, unless the user name and the password are passed as a secure string by using SqlClient programming interfaces. SqlClient contacts a <b>security token service (STS)</b> to obtain a <b>security token</b> for the database. STS validates the user name and password in <b>Active Directory</b>, which acts as an <b>identity provider</b>. Subsequently, SqlClient uses the security token to connect to the database.</li> <li>▪ "Active Directory Integrated": Indicates that a user connects by using either Kerberos <a href="#">[RFC4120]</a> or another platform-specific authentication process, such as NTLM <a href="#">[MSDN-NTLM]</a>. <a href="#">&lt;4&gt;</a> If this value is set, the <b>User ID</b> and <b>Password</b> keys MUST NOT be set.</li> </ul> <p>If the <b>Authentication</b> key is specified, the <b>Integrated Security</b> key cannot be set to "true", "yes", or "SSPI".</p>
Column Encryption Setting	<p>When this key is set to "enabled" and column encryption is supported, <a href="#">&lt;5&gt;</a> SqlClient transparently encrypts the values of input query parameters that correspond to transparently encrypted columns in the database, before sending the values to the server. Similarly, SqlClient transparently decrypts any values from encrypted columns that are received from the server in query results.</p> <p>If this key is set to "disabled" and the query contains any parameters that correspond to transparently encrypted columns, the query will fail.</p> <p>If this key is set to "disabled" and the query retrieves any values from transparently encrypted columns, the user will receive the values in cypher text. In other words, SqlClient will not decrypt these values.</p> <p>The value of this key MUST be "enabled" or "disabled".  The default value of this key is "disabled".</p>
Connection Lifetime	<p>The minimum time, in seconds, for the connection to live in the <b>connection pool</b> before it is destroyed.</p> <p>Valid values MUST be unsigned integers that range from greater than or equal to 0 to less than or equal to 2147483647.</p> <p>The default value of this key is 0, which means no pool usage at all.</p>
Connection Reset	<p>The value of this key MUST be "true", "false", "yes", or "no".  A value of "yes" MUST be treated the same as a value of "true".  A value of "no" MUST be treated the same as a value of "false".  The default value of this key is "true", and "false" is ignored.</p>
ConnectionRetryCount	<p>Specifies the number of reconnection attempts if an <b>idle connection</b> failure is detected.</p> <p>Valid values MUST be unsigned integers that range from greater than or equal to 0 to less than or equal to 255.</p> <p>The default value of this key is 1.</p>
ConnectionRetryInterval	<p>Specifies the amount of time, in seconds, between each reconnection attempt.</p> <p>Valid values MUST be unsigned integers that range from greater than or equal to</p>

Keyword	Description
	<p>1 to less than or equal to 60. The default value of this key is 10.</p>
Connection Timeout	<p>Specifies the amount of time, in seconds, to wait for a connection to complete. Valid values MUST be unsigned integers that range from greater than or equal to 0 to less than or equal to 2147483647. The default value of this key is 15.</p>
Connect Timeout	<p>Synonym of the <b>Connection Timeout</b> key.</p>
Context Connection	<p>The value of this key MUST be "true" to open an <b>in-process connection</b> to the server. The value of this key MUST be "true", "false", "yes", or "no". A value of "yes" MUST be treated the same as a value of "true". A value of "no" MUST be treated the same as a value of "false". The default value of this key is "false".</p>
Current Language	<p>Sets the language used for database server warning or error messages as specified by the <b>ibLanguage</b> and <b>cchLanguage</b> fields in section 2.2.6.4 of [MS-TDS]. For more information about default language, see <a href="#">[MSDN-DLO]</a>. The value of this key MUST be a string that has a maximum length of 128 characters. The default value of this key is "".</p>
Database	<p>Synonym of the <b>Initial Catalog</b> key.</p>
Data Source	<p>Specifies the network address of an instance of the database server. <a href="#">&lt;6&gt;</a> The value of this key MUST be a string that has a maximum length of 128 characters. The default value of this key is "".</p> <p><b>Data Source</b> MUST be the TCP format, the Named Pipes format, or the LocalDB format.</p> <p>TCP format is as follows:</p> <ul style="list-style-type: none"> <li>▪ tcp:&lt;host name&gt;\&lt;instance name&gt;</li> <li>▪ tcp:&lt;host name&gt;,&lt;TCP/IP port number&gt;</li> </ul> <p>The TCP format MUST start with the prefix "tcp:" and is followed by the database instance, as specified by a host name and an instance name. The host name MUST be specified in one of the following ways:</p> <ul style="list-style-type: none"> <li>▪ NetBIOSName <a href="#">[RFC1002]</a></li> <li>▪ IPv4Address <a href="#">[RFC791]</a></li> <li>▪ IPv6Address <a href="#">[RFC2460]</a></li> </ul> <p>The instance name is used to resolve to a particular TCP/IP port number <a href="#">[RFC793]</a> on which a <b>database instance</b> is hosted. Alternatively, specifying a TCP/IP port number directly is also allowed. If both instance name and port number are not present, the default database instance is used. For more information about instance name, see <a href="#">[MSDN-UNI]</a>.</p> <p>The Named Pipes format is as follows:</p>

Keyword	Description
	<ul style="list-style-type: none"> <li>▪ np:\\&lt;host name&gt;\pipe\&lt;pipe name&gt;</li> </ul> <p>The Named Pipes format MUST start with the prefix "np:" and is followed by a <b>named pipe</b> name.</p> <p>The host name MUST be specified in one of the following ways:</p> <ul style="list-style-type: none"> <li>▪ NetBIOSName [RFC1002]</li> <li>▪ IPv4Address [RFC791]</li> <li>▪ IPv6Address [RFC2460]</li> </ul> <p>The pipe name is used to identify the database instance to which the .NET Framework application will be connected.</p> <p>If the value of the <b>Network</b> key is specified, the prefixes "tcp:" and "np:" SHOULD NOT&lt;7&gt; be specified.</p> <p>The LocalDB format MUST start with "(localdb)" followed by a "\" and either the instance name or the LocalDB version number in the format "vXX.X". The format is as follows:</p> <ul style="list-style-type: none"> <li>▪ (localdb)\&lt;instance name&gt;, where &lt;instance name&gt; MUST be case insensitive and MUST NOT contain the terms Default, MSSQLServer, or other reserved keywords. If a reserved keyword is used in an instance name, an error will occur. Also, &lt;instance name&gt; MUST be limited to 16 characters, where the first character MUST be a letter or an underscore (_). Acceptable letters are those that are defined by the Unicode Standard 2.0 [UNICODE2.0.0], including Latin characters a-z and A-Z, and letter characters from other languages. Subsequent characters MUST be letters defined by the Unicode Standard 2.0, decimal numbers from Basic Latin or other national scripts, the dollar sign (\$), or an underscore (_). Embedded spaces of other special characters MUST NOT be allowed in instance names. The backslash (\), comma (,), colon (:), semicolon (;), single quotation mark ('), ampersand (&amp;), number sign (#), or at sign (@) also MUST NOT be allowed in instance names.</li> <li>▪ (localdb)\vXX.X, for the default instance, where X MUST be any valid decimal number from Basic Latin or other national scripts.</li> </ul> <p>For more information about the format of the <b>Data Source</b> key, see [MSKB-313295].</p> <p>For more information about named pipes, see [MSDN-NP].</p>
Encrypt	<p>Specifies whether <b>encryption</b> is used as specified by section 2.2.6.5 of [MS-TDS].</p> <p>The value of this key MUST be "true", "false", "yes", or "no".</p> <p>A value of "yes" MUST be treated the same as a value of "true".</p> <p>A value of "no" MUST be treated as a value of "false".</p> <p>If the <b>Authentication</b> key is specified, the default value of this key is "true". Otherwise, the default value of this key SHOULD&lt;8&gt; be "false".</p>
Enlist	<p>When the value of this key is set to "true", the connection MUST be automatically enlisted in current <b>transaction context</b>.</p> <p>The value of this key MUST be "true", "false", "yes", or "no".</p> <p>A value of "yes" MUST be treated the same as a value of "true".</p> <p>A value of "no" MUST be treated the same as a value of "false".</p>

Keyword	Description
	The default value of this key MAY <a href="#">&lt;9&gt;</a> be "false".
Extended Properties	Synonym of the <b>AttachDBFilename</b> key.
Failover Partner <a href="#">&lt;10&gt;</a>	<p>The name of the failover partner server where <b>database mirroring</b> is configured. This parameter is optional.</p> <p>If the value of this key is "", then <b>Initial Catalog</b> MUST be present, and its value MUST NOT be "".</p> <p>The value of this key MUST be a string that has a maximum length of 128 characters.</p> <p>The default value of this key is "".</p>
Initial Catalog	<p>Sets the name of the initial or default database of a data source as specified by the <b>ibDatabase</b> and <b>cchDatabase</b> fields in section 2.2.6.4 of [MS-TDS].</p> <p>The value of this key MUST be a string that has a maximum length of 128 characters.</p> <p>The default value of this key is "".</p> <p>For more information about default databases, see [MSDN-SD].</p>
Initial File Name	Synonym of the <b>AttachDBFilename</b> key.
Integrated Security	<p>The value of this key MUST be "sspi", "true", "false", "yes", or "no".</p> <p>The value of "sspi", "true", or "yes" indicates that a user connects by using either Kerberos [RFC4120] or another platform-specific <b>authentication</b> process, such as NTLM [MSDN-NTLM]. <a href="#">&lt;11&gt;</a></p> <p>If the value of this key is "yes", "sspi", or "true", the <b>User ID</b> and <b>Password</b> keys MUST be ignored.</p> <p>A value of "yes" or "sspi" MUST be treated the same as a value of "true".</p> <p>A value of "no" MUST be treated the same as a value of "false".</p> <p>The default value of this key is "false".</p>
Language	Synonym of the <b>Current Language</b> key.
Load Balance Timeout	Synonym of the <b>Connection Lifetime</b> key.
Max Pool Size	<p>The maximum number of connections that are allowed in the pool.</p> <p><b>Max Pool Size</b> does not impose any restrictions other than those implied or explicitly stated in this section. Examples of such restrictions can be derived from limitations on available resources or of a targeted system.</p> <p>Valid values MUST be unsigned integers that are greater than or equal to 1. Values that are less than <b>Min Pool Size</b> MUST raise an error.</p> <p>The default value of this key is 100.</p>
Min Pool Size	<p>The minimum number of connections that are allowed in the pool.</p> <p>Valid values MUST be unsigned integers that are greater than or equal to 0. Zero (0) in this field means no minimum connections are initially opened.</p> <p>Values that are greater than <b>Max Pool Size</b> MUST raise an error.</p> <p>The default value of this key is 0.</p>
MultipleActiveResultSets <a href="#">&lt;12&gt;</a>	<p>When the value of this key is set to "true", the application MUST maintain <b>Multiple Active Result Sets (MARS)</b>. When the value of this key is set to "false", the application MUST process or cancel all result sets from one batch before it can execute any other batch on that connection.</p> <p>The value of this key MUST be "true", "false", "yes", or "no".</p> <p>A value of "yes" MUST be treated the same as a value of "true".</p> <p>A value of "no" MUST be treated the same as a value of "false".</p>

Keyword	Description
	The default value of this key is "false".
MultiSubnetFailover	The value of this key MUST be "true", "false", "yes", or "no".<13> A value of "yes" MUST be treated the same as a value of "true". A value of "no" MUST be treated the same as a value of "false". The default value of this key is "false".
Net	Synonym of the <b>Network Library</b> key.
Network	Synonym of the <b>Network Library</b> key.
Network Address	Synonym of the <b>Data Source</b> key.
Network Library	Specifies the network component used in communication between the client and the data source. The behavior is platform-dependent. The supported values for this key include the following. There are several of these named components (values),<14> each of which implements a specific protocol behavior. <ul style="list-style-type: none"> <li>▪ dbnmpntw (Named Pipes [MSDN-NETLIB])</li> <li>▪ dbmsrpcn (Multiprotocol [MSDN-NETLIB], Windows <b>RPC</b> [MSDN-NETLIB])</li> <li>▪ dbmsadsn (Apple Talk [MSDN-NETLIB])</li> <li>▪ dbmsgnet (VIA [MSDN-NETLIB])</li> <li>▪ dbmslpcn (Shared Memory [MSDN-NETLIB])</li> <li>▪ dbmsspxn (IPX/SPX [MSDN-NETLIB])</li> <li>▪ dbmssocn (TCP/IP [RFC793])</li> <li>▪ Dbmsvinn (Banyan Vines [MSDN-NETLIB])</li> </ul> The corresponding network library MUST be installed in the client system. If a network is not specified to connect to a local server, the shared memory library MUST be used. The default value of this key is "".
Packet Size	Sets the network packet size in bytes (as specified by the <b>PacketSize</b> field in section 2.2.6.4 of [MS-TDS]) to be used for data exchange between the data source object and the database. Valid values MUST be unsigned integers that range from greater than or equal to 512 to less than or equal to 32767. The default packet size is 8000 bytes.
Password	Specifies the password associated with <b>User ID</b> . The value of this key MUST be a string that has a maximum length of 128 characters. The default value of this key is "".
Persist Security Info	When the value of this key is set to "false", security-sensitive information, such as the password, MUST NOT be returned as part of the connection if the connection is open or has ever been in an open state. The value of this key MUST be "true", "false", "yes", or "no". A value of "yes" MUST be treated the same as a value of "true". A value of "no" MUST be treated the same as a value of "false".



Keyword	Description
	The default value of this key is "false".
PersistSecurityInfo	Synonym of the <b>Persist Security Info</b> key.
Pooling	<p>When the value of this key is set to "true", any newly created connection MUST be added to the pool when closed by the application. In a next attempt to open the same connection, that connection MUST be drawn from the pool.</p> <p>Connections are considered the same if they have the same connection string. Different connections MUST have different connection strings.</p> <p>Connection strings MUST be compared as is.</p> <p>The value of this key MUST be "true", "false", "yes", or "no".</p> <p>A value of "yes" MUST be treated the same as a value of "true".</p> <p>A value of "no" MUST be treated the same as a value of "false".</p> <p>The default value of this key is "true".</p>
PWD	Synonym of the <b>Password</b> key.
Replication	<p>When the value of this key is set to "true", <b>replication</b> MUST be supported using the connection.</p> <p>The value of this key MUST be "true", "false", "yes", or "no".</p> <p>A value of "yes" MUST be treated the same as a value of "true".</p> <p>A value of "no" MUST be treated the same as a value of "false".</p> <p>The default value of this key is "false".</p>
Server	Synonym of the <b>Data Source</b> key.
Timeout	Synonym of the <b>Connection Timeout</b> key.
Transaction Binding	<p>Controls a connection association with an enlisted transaction.</p> <p>The value of this key MUST be one of the following:</p> <ul style="list-style-type: none"> <li>▪ Transaction Binding=Implicit Unbind</li> <li>▪ Transaction Binding=Explicit Unbind</li> </ul> <p>The Implicit Unbind value MUST cause the connection to detach from the transaction when it ends. After the connection detaches and/or after the transaction ends, additional requests on the connection MUST be committed automatically.</p> <p>The Explicit Unbind value MUST cause the connection to remain attached to the transaction until the connection is closed or if an explicit call to the <b>SqlConnection.TransactionEnlist(null)</b> method is made.</p> <p>The default value of this key is none.</p>
Trusted Connection	Synonym of the <b>Integrated Security</b> key.
TrustServerCertificate	<p>When the value of this key is set to "true", or when the value of this key set to "false" and the <b>Encrypt</b> key is set to "false" and the <b>Authentication</b> key is not set, SqlClient bypasses the step of walking the <b>certificate chain</b> to validate trust. The channel MUST NOT be encrypted if <b>TrustServerCertificate</b> is set to "true" and <b>Encrypt</b> is set to "false".</p> <p>The value of this key MUST be "true", "false", "yes", or "no".</p> <p>A value of "yes" MUST be treated the same as a value of "true".</p> <p>A value of "no" MUST be treated the same as a value of "false".</p> <p>The default value of this key is "false".</p>

Keyword	Description
Type System Version	<p>A string value that indicates the type system that the .NET Framework application expects.&lt;15&gt;</p> <p>When the value of this key is set to "Latest", the latest version that can be handled by the client-server pair MUST be used. This MUST automatically move forward as the client and server components are upgraded.&lt;16&gt;</p> <p>The default value of this key is none.</p>
UID	Synonym of the <b>User ID</b> key.
User	Synonym of the <b>User ID</b> key.
User ID	<p>Specifies the user identification to be used when connecting to the data source.</p> <p>The value of this key MUST be a string that has a maximum length of 128 characters.</p> <p>The default value of this key is "".</p>
User Instance	<p>The value of this key MUST be "true", "false", "yes", or "no".&lt;17&gt;</p> <p>A value of "yes" MUST be treated the same as a value of "true".</p> <p>A value of "no" MUST be treated the same as a value of "false".</p> <p>The default value of this key is "false".</p>
Workstation ID	<p>Sets the workstation identifier as specified by the <b>ibHostName</b> and <b>cchHostName</b> fields in section 2.2.6.4 of [MS-TDS]. The default value is the name of the workstation that is running the ODBC application.</p> <p>The value of this key MUST be a string that has a maximum length of 128 characters.</p> <p>The default value of this key is none.</p>
WSID	Synonym of the <b>Workstation ID</b> key.

## 3 Structure Examples

The following section contains connection string examples that are based on the **SqlConnection** structure.

### 3.1 Trusted Connection

The **Trusted Connection** connection string is expressed as follows.

```
Authentication=Active Directory Integrated; Data Source=ServerName; Initial  
Catalog=DatabaseName;
```

"Authentication=Active Directory Integrated" specifies that a user account [<18>](#) is used to establish this connection.

"Data Source=ServerName" specifies that ServerName is the name of the server to which the connection is established.

"Initial Catalog=DatabaseName" specifies that DatabaseName is the name of the data source.

### 3.2 Standard Security Connection

The **Standard Security Connection** connection string is expressed as follows.

```
Data Source =ServerName;Initial Catalog=DatabaseName; Authentication=Sql Password; User  
ID=UserName; Password=UserPassword;
```

"User ID=UserName" specifies that UserName is the name of the user who establishes the connection.

"Password=UserPassword" specifies that UserPassword is the password of the user who establishes the connection.

"Authentication=Sql Password" specifies SQL Server authentication.

### 3.3 Named Instance

The named instance connection string is expressed as follows.

```
Data Source= ServerName\InstanceName;Initial Catalog=DatabaseName; Authentication=Active  
Directory Integrated
```

"Data Source=ServerName\InstanceName" specifies that the connection is being established to the named instance InstanceName on the server whose name is ServerName.

The LocalDB named instance connection string is expressed as follows.

```
Data Source= (localdb)\InstanceName;Initial Catalog=DatabaseName; Authentication=Active  
Directory Integrated
```

"Data Source=(localdb)\InstanceName" specifies that the connection is being established to the named instance InstanceName on the LocalDB server.

### 3.4 SQL Server Express LocalDB Default Instance

The SQL Server Express LocalDB default instance connection string is expressed as follows.

```
Data Source= (localdb)\v11.0;Initial Catalog=DatabaseName; Authentication=Active Directory  
Integrated
```

"Data Source=(localdb)\v11.0" specifies that the connection is being established to the default instance on the SQL Server Express LocalDB server.

### 3.5 Escaped Single Quote

The **Escaped Single Quote** connection string is expressed as follows.

```
Data Source=ServerName;DATABASE=DatabaseName; Application Name='John''s Application'
```

"Application Name='John''s Application'" specifies that "John's Application" is the name of the application.

## 4 Security

### 4.1 Security Considerations for Implementers

A connection string can contain **credential** information in clear text. .NET Framework applications should [take special care](#) when accessing credential information; whenever possible, .NET Framework applications should avoid passing the credential information in the connection string. Instead, it is recommended that applications use **Authentication=Active Directory Integrated** or **Integrated Security=SSPI** in the SqlConnection Connection String structure, or use SqlConnection APIs to specify credential information.

### 4.2 Index of Security Fields

The following security parameters for SqlConnection Connection String are described in section [2.2](#).

- Authentication
- Encrypt
- Integrated Security
- Password
- TrustServerCertificate
- User ID

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

This document specifies version-specific details in the Microsoft .NET Framework. For information about which versions of .NET Framework are available in each released Windows product or as supplemental software, see [.NET Framework](#).

- Microsoft .NET Framework 1.0
- Microsoft .NET Framework 1.1
- Microsoft .NET Framework 2.0
- Microsoft .NET Framework 3.5
- Microsoft .NET Framework 4.0
- Microsoft .NET Framework 4.5
- Microsoft .NET Framework 4.6
- 2007 Microsoft Office system
- Microsoft Office 2010 system
- Microsoft Office 2013 system
- Microsoft SQL Server 2000
- Microsoft SQL Server 2005
- Microsoft SQL Server 2008
- Microsoft SQL Server 2008 Express
- Microsoft SQL Server 2008 R2
- Microsoft SQL Server 2012
- Microsoft SQL Server 2014
- Microsoft SQL Server 2016 Community Technology Preview 2 (CTP2)
- Windows Vista operating system
- Windows Server 2008 operating system
- Windows 7 operating system
- Windows Server 2008 R2 operating system
- Windows Server 2012 operating system
- Windows 8 operating system
- Windows 8.1 operating system
- Windows Server 2012 R2 operating system
- Windows 10 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2](#): In .NET Framework 4.5 and .NET Framework 4.6, the **Asynchronous Processing** key is ignored.

[<2> Section 2.2](#): A file path that conforms to the format specified in [\[MSDN-FILE\]](#).

[<3> Section 2.2](#): Federated authentication is not supported by SQL Server.

[<4> Section 2.2](#): The SQL Server configuration determines whether SqlClient authenticates to the database directly by using either Kerberos or NTLM, or whether SqlClient initially contacts an STS to obtain an access token that subsequently is used to connect to the database.

[<5> Section 2.2](#): The implementation determines whether a server supports column encryption. Column encryption is not supported by SQL Server 2000, SQL Server 2005, SQL Server 2008, SQL Server 2008 Express, SQL Server 2008 R2, SQL Server 2012, SQL Server 2014, .NET Framework 1.0, .NET Framework 1.1, .NET Framework 2.0, .NET Framework 3.5, .NET Framework 4.0, or .NET Framework 4.5.

[<6> Section 2.2](#): The value of the **Data Source** key can be either the name of a server on the network or the name of a SQL Server Configuration Manager advanced server entry. To specify a named instance of SQL Server, the server name can be specified as ServerName\InstanceName. Otherwise, if InstanceName is omitted, SqlClient connects to the default server. "(Local)" is also a valid name representing a copy of SQL Server that is running on the same computer. SQL Server 2000 does not support multiple instances of SQL Server that run on the same computer.

[<7> Section 2.2](#): In Microsoft implementations, if the value of the **Network** key is specified as "DBNETLIB," the protocol prefixes "tcp:" and "np:" can still be used.

[<8> Section 2.2](#): Even if the **Encrypt** key is set to "false", SqlClient looks at [Software\Microsoft\MSSQLServer\Client\SuperSocketNetLib], and if the value of **Encrypt** is set to "true", the encryption is considered enabled.

[<9> Section 2.2](#): The default value is "true" if the platform is WIN32NT. Otherwise, the default value is "false".

[<10> Section 2.2](#): The **Failover Partner** key is not supported by .NET Framework 1.0 or .NET Framework 1.1.

[<11> Section 2.2](#): In Microsoft implementations, NTLM authentication [\[MSDN-NTLM\]](#) is used when the value of the **Integrated Security** key is "yes". In addition, depending on the server configuration, NTLM authentication might be used if the value of the **Authentication** key is "Active Directory Integrated".

[<12> Section 2.2](#): The **MultipleActiveResultSets** key is not supported by .NET Framework 1.0 or .NET Framework 1.1.

[<13> Section 2.2](#): When the value of the **MultiSubnetFailover** key is set to "true", SQL Server 2012, SQL Server 2014, and SQL Server 2016 CTP2 enable fast failover for all AlwaysOn availability groups and failover cluster instances.

<14> [Section 2.2](#): In Microsoft implementations, the behaviors of the values for the various components are described in the following table.

Value	Meaning
DBNMPNTW	The component DBNMPNTW implements the named pipes protocol <a href="#">[MSDN-NP]</a> .
DBMSSOCN	The component DBMSSOCN implements the TCP/IP protocol.
DBMSSPXN	The component DBMSSPXN implements the NWLink IPX/SPX protocol.
DBMSRPCN	The component DBMSRPCN implements the Multi-Protocol protocol.
DBMSVINN	The component DBMSVINN implements the Banyan Vines protocol.
DBMSADSN	The component DBMSADSN implements the ADSP protocol.
DBMSSHRN	The component DBMSSHRN implements the Shared Memory protocol.
DBMSLPCN	The component DBMSLPCN implements the Shared Memory protocol.
DBNETLIB	The default search order of network component can be used.

If the value specified is not listed above, or if the **Network** key is not specified, the default search order of network component can be used. For more information about the default search order of network component, see [\[MSKB-328383\]](#).

<15> [Section 2.2](#): The value is one of the following:

- **Type System Version**=SQL Server 2000
- **Type System Version**=SQL Server 2005
- **Type System Version**=SQL Server 2008 (Applicable to only .NET Framework 2.0 SP1, .NET Framework 3.5, .NET Framework 4.0, .NET Framework 4.5, and .NET Framework 4.6)
- **Type System Version**=SQL Server 2012 (Applicable to only .NET Framework 4.5 and .NET Framework 4.6)
- **Type System Version**=Latest

When the value of the **Type System Version** key is set to "SQL Server 2000", SQL Server 2000 is used.

The following conversions are performed when connecting to an instance of Microsoft SQL Server other than SQL Server 2000:

- XML to NTEXT
- UDT to VARBINARY
- VARCHAR(MAX) to TEXT
- NVARCHAR(MAX) to NTEXT

When the value of this key is set to "SQL Server 2005", SQL Server 2005 is used. No conversions are made for the version of the .NET Framework that is running in the context of the application.

<16> [Section 2.2](#): SQL Server 2000, SQL Server 2005, SQL Server 2008, and SQL Server 2008 R2 require that the latest version that can be handled by the client-server pair be used when the **Type System Version** key has a value of "Latest" set. SQL Server 2012, SQL Server 2014, and SQL Server 2016 CTP2 require that users provide the correct version number.



[<17> Section 2.2](#): The value for the **User Instance** key indicates whether to redirect the connection from the default instance of SQL Server 2008 Express to another connection that is running in the same context of the user.

[<18> Section 3.1](#): In Microsoft implementations, the user account is a Windows user account.

[<19> Section 4.1](#): Connection strings are stored "as is" in memory or in any other persistent media. The application should safeguard any credential information.

## 6 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">2.1</a> SqlConnection String	Added Authentication and Use Column Encryption keys.	Y	Content update.
<a href="#">2.2</a> Keys and Values	Added information about the Authentication and Column Encryption Setting keys.	Y	Content update.
<a href="#">3.1</a> Trusted Connection	Updated examples to use the new, recommended syntax (Authentication key).	Y	Content update.
<a href="#">3.2</a> Standard Security Connection	Updated examples to use the new, recommended syntax (Authentication key).	Y	Content update.
<a href="#">3.3</a> Named Instance	Updated examples to use the new, recommended syntax (Authentication key).	Y	Content update.
<a href="#">3.4</a> SQL Server Express LocalDB Default Instance	Updated example to use the new, recommended syntax (Authentication key).	Y	Content update.
<a href="#">4.2</a> Index of Security Fields	Added Authentication to the list of parameters.	Y	Content update.
<a href="#">5</a> Appendix A: Product Behavior	Added .NET Framework 4.6, SQL Server 2016 CTP2, and Windows 10 to the list of applicable products.	Y	Content update.

## 7 Index

### A

[Applicability](#) 8

### C

[Capability negotiation](#) 8  
[Change tracking](#) 26

### E

[Escaped Single Quote connection string](#) 20  
[Escaped Single Quote example](#) 20  
[Examples](#) 19  
    [Escaped Single Quote](#) 20  
    [Named Instance](#) 19  
    [SQL Server Express LocalDB Default Instance](#) 20  
    [Standard Security Connection](#) 19  
    [Trusted Connection](#) 19

### F

[Fields - security index](#) 21  
[Fields - vendor-extensible](#) 8

### G

[Glossary](#) 4

### I

[Implementer - security considerations](#) 21  
[Index of security fields](#) 21  
[Informative references](#) 7  
[Introduction](#) 4

### K

[Keys](#) 11

### L

[Localization](#) 8

### N

[Named instance connection string](#) 19  
[Named Instance example](#) 19  
[Normative references](#) 6

### O

[Overview](#) 7  
[Overview \(synopsis\)](#) 7

### P

[Product behavior](#) 22

### R

[References](#) 6  
    [informative](#) 7  
    [normative](#) 6  
[Relationship to other protocols](#) 8  
[Relationship to protocols and other structures](#) 8

### S

Security  
    [considerations for implementers](#) 21  
    [field index](#) 21  
    [implementer considerations](#) 21  
    [parameters](#) 21  
[SQL Server Express LocalDB default instance](#) 20  
[SQL Server Express LocalDB Default Instance example](#) 20  
[SqlClient connection string guidelines](#) 10  
[SqlClient connection string overview](#) 9  
[SqlClient connection string restrictions](#) 11  
[Standard Security Connection connection string](#) 19  
[Standard Security Connection example](#) 19

### T

[Tracking changes](#) 26  
[Trusted Connection connection string](#) 19  
[Trusted Connection example](#) 19

### V

[Values](#) 11  
[Vendor-extensible fields](#) 8  
[Versioning](#) 8

