

[MS-SSDPWP-Diff]:

Database Publishing Wizard Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, [IDL's](#)[IDL's](#), or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplq@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, [email](#)[email](#) addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
08/078/7/2009	0.1	Major	First release.
11/066/2009	0.1.1	Editorial	RevisedChanged language and editedformatting in the technical content.
03/053/5/2010	0.2	Minor	UpdatedClarified the meaning of the technical content.
044/21/2010	0.3	Minor	UpdatedClarified the meaning of the technical content.
06/046/4/2010	0.3.1	Editorial	RevisedChanged language and editedformatting in the technical content.
09/039/3/2010	0.3.1	No changeNone	No changes to the meaning, language, or formatting of the technical content.
02/092/9/2011	0.3.1	No changeNone	No changes to the meaning, language, or formatting of the technical content.
07/077/7/2011	0.3.1	No changeNone	No changes to the meaning, language, or formatting of the technical content.
11/033/2011	0.3.1	No changeNone	No changes to the meaning, language, or formatting of the technical content.
011/19/2012	0.3.1	No changeNone	No changes to the meaning, language, or formatting of the technical content.
022/23/2012	4.0	Major	Significantly changedUpdated and revised the technical content.
033/27/2012	4.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
055/24/2012	4.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
066/29/2012	4.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
077/16/2012	4.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
10/088/2012	5.0	Major	Significantly changedUpdated and revised the technical content.
10/23/2012	5.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
033/26/2013	5.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
066/11/2013	5.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
08/08/2013	5.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
12/05/2013	5.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
02/11/2014	6.0	Major	Significantly changed Updated and revised the technical content.
05/20/2014	6.0	No changeNone	No changes to the meaning, language, or formatting of the technical content.
5/10/2016	7.0	Major	Significantly changed the technical content.

Table of Contents

1	Introduction	6
1.1	Glossary.....	6
References		7
1.2	7	
1.2.1	Normative References	7
1.2.2	Informative References	7
1.3	Overview.....	8
1.4	Relationship to Other Protocols	8
1.5	Prerequisites/Preconditions.....	9
1.6	Applicability Statement	9
1.7	Versioning and Capability Negotiation	9
1.8	Vendor-Extensible Fields	9
1.9	Standards Assignments.....	9
2	Messages.....	10
2.1	Transport	10
2.2	Common Message Syntax	10
2.2.1	Namespaces.....	10
2.2.2	Messages.....	10
2.2.3	Elements	10
2.2.4	Complex Types.....	10
2.2.5	Simple Types	10
2.2.6	Attributes	11
2.2.7	Groups	11
2.2.8	Attribute Groups	11
2.3	Directory Service Schema Elements.....	11
3	Protocol Details	12
3.1	PublishServiceSoap Server Details.....	12
3.1.1	Abstract Data Model.....	12
3.1.2	Timers.....	12
3.1.3	Initialization	12
3.1.4	Message Processing Events and Sequencing Rules	13
3.1.4.1	BeginPublish.....	13
3.1.4.1.1	Messages	14
3.1.4.1.1.1	BeginPublishSoapIn.....	14
3.1.4.1.1.2	BeginPublishSoapOut.....	14
3.1.4.1.2	Elements	14
3.1.4.1.2.1	BeginPublish.....	14
3.1.4.1.2.2	BeginPublishResponse	15
3.1.4.2	CancelPublish	15
3.1.4.2.1	Messages	15
3.1.4.2.1.1	CancelPublishSoapIn	15
3.1.4.2.1.2	CancelPublishSoapOut	16
3.1.4.2.2	Elements	16
3.1.4.2.2.1	CancelPublish	16
3.1.4.2.2.2	CancelPublishResponse	16
3.1.4.3	EndPublish	16
3.1.4.3.1	Messages	16
3.1.4.3.1.1	EndPublishSoapIn	17

3.1.4.3.1.2	EndPublishSoapOut	17
3.1.4.3.2	Elements	17
3.1.4.3.2.1	EndPublish	17
3.1.4.3.2.2	EndPublishResponse	17
3.1.4.4	GetServiceOptions.....	17
3.1.4.4.1	Messages	18
3.1.4.4.1.1	GetServiceOptionsSoapIn.....	18
3.1.4.4.1.2	GetServiceOptionsSoapOut	18
3.1.4.4.2	Elements	18
3.1.4.4.2.1	GetServiceOptions	18
3.1.4.4.2.2	GetServiceOptionsResponse	18
3.1.4.5	PublishData	19
3.1.4.5.1	Messages	19
3.1.4.5.1.1	PublishDataSoapIn	19
3.1.4.5.1.2	PublishDataSoapOut	19
3.1.4.5.2	Elements	19
3.1.4.5.2.1	PublishData	19
3.1.4.5.2.2	PublishDataResponse	20
3.1.4.6	PublishScript	20
3.1.4.6.1	Messages	20
3.1.4.6.1.1	PublishScriptSoapIn	20
3.1.4.6.1.2	PublishScriptSoapOut	21
3.1.4.6.2	Elements	21
3.1.4.6.2.1	PublishScript	21
3.1.4.6.2.2	PublishScriptResponse	21
3.1.5	Timer Events.....	21
3.1.6	Other Local Events.....	21
4	Protocol Examples	22
5	Security	24
5.1	Security Considerations for Implementers	24
5.2	Index of Security Parameters.....	24
6	Appendix A: Full WSDL	25
7	Appendix B: Product Behavior	30
8	Change Tracking	31
9	Index.....	33

1 1—Introduction

The Database Publishing Wizard Protocol is a format that enables communication with an instance of Microsoft SQL Server by using open, industry-standard protocols. By using this format, a publishing session can be initiated, data can be published, and scripts can be executed against an instance of SQL Server.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative ~~and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms.~~. All other sections and examples in this specification are informative.

1.1 1.1—Glossary

The This document uses the following terms ~~are defined in [MS-GLOS]:~~:

Web Services Description Language (WSDL)
WSDL message
XML
XML namespace
XML schema

~~The following terms are specific to this document:~~

Web Services Description Language (WSDL): An XML format for describing network services as a set of endpoints that operate on messages that contain either document-oriented or procedure-oriented information. The operations and messages are described abstractly and are bound to a concrete network protocol and message format in order to define an endpoint. Related concrete endpoints are combined into abstract endpoints, which describe a network service. WSDL is extensible, which allows the description of endpoints and their messages regardless of the message formats or network protocols that are used.

WSDL message: An abstract, typed definition of the data that is communicated during a WSDL operation [WSDL]. Also, an element that describes the data being exchanged between web service providers and clients.

XML: The Extensible Markup Language, as described in [XML1.0].

XML document: A document object that is well formed, as described in [XML10/5], and might be valid. An XML document has a logical structure that is composed of declarations, elements, comments, character references, and processing instructions. It also has a physical structure that is composed of entities, starting with the root, or document, entity.

XML namespace: A collection of names that is used to identify elements, types, and attributes in XML documents identified in a URI reference [RFC3986]. A combination of XML namespace and local name allows XML documents to use elements, types, and attributes that have the same names but come from different sources. For more information, see [XMLNS-2ED].

XML schema: A description of a type of **XML document** that is typically expressed in terms of constraints on the structure and content of documents of that type, in addition to the basic syntax constraints that are imposed by **XML** itself. An XML schema provides a view of a document type at a relatively high level of abstraction.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as ~~described defined~~ in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2 References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2-1/2003] Gudgin, M., Hadley, M., Mendelsohn, N., et al., **Eds.**, "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[WSDL SOAP] Angelov, D., Ballinger, K., Butek, R., et al., "WSDL 1.1 Binding Extension for SOAP 1.2", W3C Member Submission, April 2006, <http://www.w3.org/Submission/2006/SUBM-wsdl11soap12-20060405/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., **Eds.**, "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLNS3] See **[XMLNS]**.

[XMLSCHEMA1] Thompson, H.**S.**, Beech, D., Maloney, M., and Mendelsohn, N., **Eds.**, "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmleschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., **Ed.** and Malhotra, A., **EdsEd.**, "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmleschema-2-20010502/>

1.2.2 Informative References

[DPS] Microsoft Corporation, "SQL Server Hosting Web Service (and toolkit): Database Publishing Services", <http://sqlhost.codeplex.com/Wiki/View.aspx?title=Database%20Publishing%20Services&referringTitle=Home>

[MS-GLOS] Microsoft Corporation, "Windows Protocols Master Glossary".

[MSDN-CRED] Microsoft Corporation, "Credentials (Database Engine)", <http://msdn.microsoft.com/en-us/library/ms161950.aspx>

[MSDN-Transact-SQLRef] Microsoft Corporation, "Transact-SQL Reference (Database Engine)", <http://msdn.microsoft.com/en-us/library/bb510741.aspx>

1.3 1.3—Overview

The Database Publishing Wizard Protocol enables a user to publish an existing database to a remote server via a web service. This enables database deployment in hosted scenarios without requiring direct access to the database server.

1.4 1.4—Relationship to Other Protocols

The Database Publishing Wizard Protocol uses SOAP over HTTP as shown in the following layering diagram.




Figure 14: SOAP over HTTP

The Database Publishing Wizard Protocol uses SOAP over HTTPS as shown in the following layering diagram.




Figure 22: SOAP over HTTPS

1.5 1.5—Prerequisites/Preconditions

Before using the Database Publishing Wizard Protocol, it is necessary to install and configure an instance of the Database Publishing Services web service. For more information about how to do this, see [DPS].

1.6 1.6—Applicability Statement

The Database Publishing Wizard Protocol is applicable whenever a user wants to deploy a database but the target instance of Microsoft SQL Server is not accessible by using the typical SQL Server client tools, such as SQL Server Management Studio, SQL Server Management Objects (SMO), or Microsoft ADO.NET. The Database Publishing Wizard Protocol allows the deployment to occur via a proxy web service that does have direct access to the target instance of SQL Server.

1.7 1.7—Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This protocol uses multiple transports with SOAP, as specified in section 2.1.
- **Protocol Versions:** This protocol has a separate **Web Services Description Language (WSDL)** port type for each version of the protocol. The operations that are available through each port are identical. The two ports support clients using SOAP 1.1 and SOAP 1.2, respectively.
- **Localization:** This protocol includes text strings in various messages. Localization considerations for such strings are specified in sections 2.2 and 3.1.4.
- **Capability Negotiation:** This protocol does explicit negotiation.

There is currently only one version of the protocol (version 1.1). However, clients may confirm that they are communicating with version 1.1 by invoking the GetServiceOptions method and then checking the **service_version** return value.

1.8 1.8—Vendor-Extensible Fields

This protocol does not include any vendor-extensible fields.

1.9 1.9—Standards Assignments

None.

2 Messages

2.1 Transport

2.1 Transport

The web service message protocols SOAP 1.1, as specified in [SOAP1.1], and SOAP 1.2, as specified in [SOAP1.2-1/2003], are supported.

2.1.2.2 Common Message Syntax

This section contains common definitions used by this protocol. The syntax of the definitions uses **XML schema** as defined in [XMLSCHEMA1] and [XMLSCHEMA2] and Web Services Description Language (WSDL) as defined in [WSDL].

2.1.2.2.1 2.2.1 Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms that are specified in [XMLNS], as listed in the following table. Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	http://schemas.xmlsoap.org/wsdl/soap	[SOAP1.1]
tns	http://schemas.microsoft.com/sqlserver/2006/12/publishing	Appendix A
s	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]
soap12	http://schemas.xmlsoap.org/wsdl/soap12/	[WSDLSOAP]
targetNamespace	http://schemas.microsoft.com/sqlserver/2006/12/publishing	Appendix A
wsdl	http://schemas.xmlsoap.org/wsdl	[WSDL]

2.1.2.2.2 2.2.2 Messages

This specification does not contain any common **WSDL messages**.

2.1.2.2.3 2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.1.2.2.4 2.2.4 Complex Types

This specification does not define any common XML schema complex type definitions.

2.1.2.2.5 2.2.5 Simple Types

This specification does not define any common XML schema simple type definitions.

2.1.6**2.2.6** **Attributes**

This specification does not define any common XML schema attribute definitions.

2.1.7**2.2.7** **Groups**

This specification does not define any common XML schema group definitions.

2.1.8**2.2.8** **Attribute Groups**

This specification does not define any common XML schema attribute group definitions.

2.2.3**2.3** **Directory Service Schema Elements**

None.

3 **3**—Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other states are required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

3.1 **3.1**—PublishServiceSoap Server Details

This section describes the server behavior of the Database Publishing Wizard Protocol. This port type supports the following WSDL operations:

- **BeginPublish**
- **CancelPublish**
- **EndPublish**
- **GetServiceOptions**
- **PublishData**
- **PublishScript**

3.1.1 **3.1.1**—Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

In the following sections:

- **"State"** refers to the condition that the database publishing wizard transitions into, in response to a request from the client. The [MS-SSDPWP] protocol itself is stateless.
- **"Argument"** refers to parameters and attributes that qualify an operation requested by the client.
- **If** the server responds with an error to the client while it is in a particular state, the server continues to remain in the same state without transitioning to a new state.
- **The *server'sserver's* initial state is "Not Publishing".**

3.1.2—Timers

3.1.2 Timers

None.

3.1.3 3.1.3 Initialization

The Database Publishing Wizard Protocol is initialized by invoking the **BeginPublish** operation with valid arguments to initiate a connection to an instance of SQL Server. When the **BeginPublish** operation is invoked, the server MUST connect to the specified instance of SQL Server to validate the arguments.

3.1.33.1.4 3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of WSDL operations as defined by this specification.

Operation	Description
BeginPublish	Sets the state to "Publish".
CancelPublish	Sets the state to "Not Publishing".
EndPublish	Sets the state to "Not Publishing".
GetServiceOptions	Returns an XML document that has pertinent hosting-provider-specific configuration values and other account metadata.
PublishData	Saves data to database tables. Can be invoked only if the state of the service is "Publish" (set by calling BeginPublish).
PublishScript	Executes the passed string as a Transact-SQL script against the database. Can be invoked only if the state of the service is "Publish" (set by calling BeginPublish).

3.1.4.1 BeginPublish

3.1.4.1 BeginPublish

```
<wsdl:operation name="BeginPublish">
  <wsdl:input message="tns:BeginPublishSoapIn" />
  <wsdl:output message="tns:BeginPublishSoapOut" />
</wsdl:operation>
```

The **BeginPublish** operation is used to transition the server into the "Publish" state. The connection information and user credentials that are necessary to open a connection to an instance of the server are passed in by using this operation. The **useTransactions** argument determines whether subsequent operations are performed transactionally.

BeginPublish MUST initiate a connection to the specified instance of the server by using the provided arguments.

The specific error returned to the client can vary as follows.

In the case of missing (empty string) arguments for the *serverName*, *databaseName*, *sqlUsername*, or *sqlPassword* parameters, an error in the following form is returned:

```
System.ArgumentException: Null values not allowed for parameters for BeginPublish.
```

In the case of invalid database credentials (a non-existent server, database, or username, or an invalid password), an error is returned. The error returned is in the following form:

```
Microsoft.SqlServer.Hosting.Service.SqlErrorException: An error occurred while trying to begin publish.
```

Invoking **BeginPublish** when not in the "Not Publishing" state MUST result in an error being returned to the client. The error returned is in the following form:

Microsoft.SqlServer.Hosting.Service.PublishOccurringException: There is a current valid publishing session occurring. You must close it before you can begin a new one.

3.1.3.1.13.1.4.1.1 3.1.4.1.1 Messages

The following WSDL message definitions are specific to this operation.

3.1.3.1.1+3.1.4.1.1.1 3.1.4.1.1.1 BeginPublishSoapIn

The **BeginPublishSoapIn** WSDL message has one parameter, *BeginPublish*. The *BeginPublish* element contains connection information for the instance of SQL Server and user authentication information.

```
<wsdl:message name="BeginPublishSoapIn">
  <wsdl:part name="parameters" element="tns:BeginPublish" />
</wsdl:message>
```

3.1.3.1.1.23.1.4.1.1.2 3.1.4.1.1.2 BeginPublishSoapOut

The **BeginPublishSoapOut** WSDL message has one parameter, *BeginPublishResponse*.

```
<wsdl:message name="BeginPublishSoapOut">
  <wsdl:part name="parameters" element="tns:BeginPublishResponse" />
</wsdl:message>
```

3.1.3.1.23.1.4.1.2 3.1.4.1.2 Elements

The following XML schema element definitions are specific to this operation.

3.1.3.1.2+3.1.4.1.2.1 3.1.4.1.2.1 BeginPublish

```
<s:element name="BeginPublish">
  <s:complexType>
    <s:sequence>
      <s:element name="serverName" type="s:string" minOccurs="0" maxOccurs="1"
        name="serverName"/>
      <s:element name="databaseName" type="s:string" minOccurs="0" maxOccurs="1"
        name="databaseName"/>
      <s:element name="sqlUsername" type="s:string" minOccurs="0" maxOccurs="1"
        name="sqlUsername"/>
      <s:element name="sqlPassword" type="s:string" minOccurs="0" maxOccurs="1"
        name="sqlPassword"/>
      <s:element name="useTransactions" type="s:boolean"
        minOccurs="1" maxOccurs="1" />
    </s:sequence>
  </s:complexType>
</s:element>
```

The **BeginPublish** element represents the target instance of SQL Server, user credentials, and desired transactional behavior of subsequent operations.

The **serverName** element represents the name of the target instance of SQL Server.

The **databaseName** element represents the name of the target database on the **serverName** instance of SQL Server.

The **sqlUsername** element represents the user name that is used to authenticate on the target instance of SQL Server.

The **sqlPassword** element represents the password that is used to authenticate on the target instance of SQL Server.

The **useTransactions** element represents the desired transactional behavior of subsequent server operations.

For more information about the credentials that are used to connect to SQL Server, see [MSDN-CRED].

3.1.3.1.2.23.1.4.1.2.2 3.1.4.1.2.2 BeginPublishResponse

The following code is the XSD for the **BeginPublish** operation response.

```
<s:element name="BeginPublishResponse">
  <s:complexType />
</s:element>
```

3.1.4.2 CancelPublish

3.1.4.2 CancelPublish

```
<wsdl:operation name="CancelPublish">
  <wsdl:input message="tns:CancelPublishSoapIn" />
  <wsdl:output message="tns:CancelPublishSoapOut" />
</wsdl:operation>
```

The **CancelPublish** operation is used to transition the server into the "Not Publishing" state. The connection to the instance of the server that was initialized by the **BeginPublish** operation is closed. In addition, if **BeginPublish** was invoked by using a value of true for the **useTransactions** argument, the transaction that covers all the changes made by the **PublishScript** and **PublishData** operations is rolled back.

Invoking **CancelPublish** when not in the "Publish" state MUST result in an error being returned to the client. The error returned is in the following form:

```
Microsoft.SqlServer.Hosting.Service.NotPublishingException: A valid publishing session must be started before it can be ended.
```

Invoking **CancelPublish** MUST release the connection to the target instance of the server.

3.1.3.1.33.1.4.2.1 3.1.4.2.1 Messages

The following WSDL message definitions are specific to this operation.

3.1.3.1.3.13.1.4.2.1.1 3.1.4.2.1.1 CancelPublishSoapIn

The **CancelPublishSoapIn** WSDL message has one parameter, *CancelPublish*.

```
<wsdl:message name="CancelPublishSoapIn">
  <wsdl:part name="parameters" element="tns:CancelPublish" />
</wsdl:message>
```

3.1.3.1.3.23.1.4.2.1.2 3.1.4.2.1.2 CancelPublishSoapOut

The **CancelPublishSoapOut** WSDL message has one parameter, *CancelPublishResponse*.

```
<wsdl:message name="CancelPublishSoapOut">
  <wsdl:part name="parameters" element="tns:CancelPublishResponse" />
</wsdl:message>
```

3.1.3.1.43.1.4.2.2 3.1.4.2.2 Elements

The following XML schema element definitions are specific to the **CancelPublish** operation.

3.1.3.1.4.13.1.4.2.2.1 3.1.4.2.2.1 CancelPublish

The following example shows the XSD for the **CancelPublish** operation request.

```
<s:element name="CancelPublish">
  <s:complexType />
</s:element>
```

3.1.3.1.4.23.1.4.2.2.2 3.1.4.2.2.2 CancelPublishResponse

The following example shows the XSD for the **CancelPublish** operation response.

```
<s:element name="CancelPublishResponse">
  <s:complexType />
</s:element>
```

3.1.4.3 EndPublish

3.1.4.3 EndPublish

```
<wsdl:operation name="EndPublish">
  <wsdl:input message="tns:EndPublishSoapIn" />
  <wsdl:output message="tns:EndPublishSoapOut" />
</wsdl:operation>
```

The **EndPublish** operation is used to transition the server into the "Not Publishing" state. The connection to the instance of the server that was initialized by the **BeginPublish** operation is closed. In addition, if **BeginPublish** was invoked by using a value of True for the **useTransactions** argument, the transaction that covers all the changes made by the **PublishScript** and **PublishData** operations is committed.

Invoking **EndPublish** when not in the "Publish" state MUST result in an error being returned to the client. The error returned is in the following form:

```
Microsoft.SqlServer.Hosting.Service.NotPublishingException: A valid publishing session must be started before it can be ended.
```

Invoking **EndPublish** MUST release the connection to the target instance of the server.

3.1.3.1.53.1.4.3.1 3.1.4.3.1 Messages

The following WSDL message definitions are specific to this operation.

3.1.3.1.5.13.1.4.3.1.1 **3.1.4.3.1.1** EndPublishSoapIn

The **EndPublishSoapIn** WSDL message has one parameter, *EndPublish*.

```
<wsdl:message name="EndPublishSoapIn">
  <wsdl:part name="parameters" element="tns:EndPublish" />
</wsdl:message>
```

3.1.3.1.5.23.1.4.3.1.2 **3.1.4.3.1.2** EndPublishSoapOut

The **EndPublishSoapOut** WSDL message has one parameter, *EndPublishResponse*.

```
<wsdl:message name="EndPublishSoapOut">
  <wsdl:part name="parameters" element="tns:EndPublishResponse" />
</wsdl:message>
```

3.1.3.1.63.1.4.3.2 **3.1.4.3.2** Elements

The following XML schema element definitions are specific to the EndPublish operation.

3.1.3.1.6.13.1.4.3.2.1 **3.1.4.3.2.1** EndPublish

The following example shows the XSD for the **EndPublish** operation request.

```
<s:element name="EndPublish">
  <s:complexType />
</s:element>
```

3.1.3.1.6.23.1.4.3.2.2 **3.1.4.3.2.2** EndPublishResponse

The following example shows the XSD for the **EndPublish** operation response.

```
<s:element name="EndPublishResponse">
  <s:complexType />
</s:element>
```

3.1.4.4 GetServiceOptions

3.1.4.4 GetServiceOptions

```
<wsdl:operation name="GetServiceOptions">
  <wsdl:input message="tns:GetServiceOptionsSoapIn" />
  <wsdl:output message="tns:GetServiceOptionsSoapOut" />
</wsdl:operation>
```

The **GetServiceOptions** operation returns an XML document that has pertinent hosting-provider-specific configuration values and other account values.

As an example of the **XML** that is valid to return, the default implementation of the Database Publishing Services web service returns the following.

```
<options>
  <max_request_length>4096</max_request_length>
  <service_version>1.1.0.0</service_version>
</options>
```

3.1.3.1.73.1.4.4.1 3.1.4.4.1 Messages

The following WSDL message definitions are specific to this operation.

3.1.3.1.7.13.1.4.4.1.1 3.1.4.4.1.1 GetServiceOptionsSoapIn

The **GetServiceOptionsSoapIn** WSDL message has one parameter, *GetServiceOptions*.

```
<wsdl:message name="GetServiceOptionsSoapIn">
  <wsdl:part name="parameters" element="tns:GetServiceOptions" />
</wsdl:message>
```

3.1.3.1.7.23.1.4.4.1.2 3.1.4.4.1.2 GetServiceOptionsSoapOut

The **GetServiceOptionsSoapOut** WSDL message has one parameter, *GetServiceOptionsResponse*.

```
<wsdl:message name="GetServiceOptionsSoapOut">
  <wsdl:part name="parameters" element="tns:GetServiceOptionsResponse" />
</wsdl:message>
```

3.1.3.1.83.1.4.4.2 3.1.4.4.2 Elements

The following XML schema element definitions are specific to this operation.

3.1.3.1.8.13.1.4.4.2.1 3.1.4.4.2.1 GetServiceOptions

The following example shows the XSD for the **GetServiceOptions** operation request.

```
<s:element name="GetServiceOptions">
  <s:complexType />
</s:element>
```

3.1.3.1.8.23.1.4.4.2.2 3.1.4.4.2.2 GetServiceOptionsResponse

The following example shows the XSD for the **GetServiceOptions** operation response.

```
<s:element name="GetServiceOptionsResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="GetServiceOptionsResult">
        <s:minOccurs value="0"/>
        <s:maxOccurs value="1"/>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>
```

```

        </s:element>
    </s:sequence>
</s:complexType>
</s:element>
```

The **GetServiceOptionsResult** element represents an XML document that contains pertinent hosting-provider-specific configuration values and other account metadata.

3.1.4.5 PublishData

3.1.4.5 PublishData

The following example shows the XSD for the **GetServiceOptions** operation request.

```

<wsdl:operation name="PublishData">
    <wsdl:input message="tns:PublishDataSoapIn" />
    <wsdl:output message="tns:PublishDataSoapOut" />
</wsdl:operation>
```

The **PublishData** operation saves the state in a **DataSet** class to database tables. **PublishData** can be invoked only if the service is in the "Publish" state (set by calling *BeginPublish*).

In the case of invalid database credentials or inputs (nonexistent server, database, username, or invalid password), an error is returned.

3.1.3.1.9.23.1.4.5.1.1 3.1.4.5.1.1 PublishDataSoapIn

The **PublishDataSoapIn** WSDL message has one parameter, *PublishData*.

```

<wsdl:message name="PublishDataSoapIn">
    <wsdl:part name="parameters" element="tns:PublishData" />
</wsdl:message>
```

3.1.3.1.9.23.1.4.5.1.2 3.1.4.5.1.2 PublishDataSoapOut

The **PublishDataSoapOut** WSDL message has one parameter, *PublishDataResponse*.

```

<wsdl:message name="PublishDataSoapOut">
    <wsdl:part name="parameters" element="tns:PublishDataResponse" />
</wsdl:message>
```

3.1.3.1.10.3.1.4.5.2 3.1.4.5.2 Elements

The following XML schema element definitions are specific to this operation.

3.1.3.1.10.13.1.4.5.2.1 3.1.4.5.2.1 PublishData

The following example shows the XSD for the **PublishData** operation request.

```

<s:element name="PublishData">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ds">
        <s:complexType>
          <s:sequence>
            <s:element ref="s:schema" />
            <s:any />
          </s:sequence>
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>

```

The **PublishData** element represents data that MUST be loaded into the target database.

The **ds** element represents an ADO.NET **DataSet** class serialized as XML.

3.1.3.1.10.23.1.4.5.2.2 3.1.4.5.2.2 PublishDataResponse

The following example shows the XSD for the **PublishData** operation response.

```

<s:element name="PublishDataResponse">
  <s:complexType />
</s:element>

```

3.1.4.6 PublishScript

3.1.4.6 PublishScript

The following example shows the XSD for the **PublishData** operation request.

```

<wsdl:operation name="PublishScript">
  <wsdl:input message="tns:PublishScriptSoapIn" />
  <wsdl:output message="tns:PublishScriptSoapOut" />
</wsdl:operation>

```

The **PublishScript** operation executes the passed-in string as a Transact-SQL script against the database. **PublishScript** can be invoked only if the service is in the "Publish" state (set by calling BeginPublish).

For more information about Transact-SQL, see [MSDN-Transact-SQLRef].

3.1.3.1.113.1.4.6.1 3.1.4.6.1 Messages

The following WSDL message definitions are specific to this operation.

3.1.3.1.11.13.1.4.6.1.1 3.1.4.6.1.1 PublishScriptSoapIn

The **PublishScriptSoapIn** WSDL message has one parameter, *PublishScript*.

```

<wsdl:message name="PublishScriptSoapIn">
  <wsdl:part name="parameters" element="tns:PublishScript" />

```

```
</wsdl:message>
```

3.1.3.1.11.23.1.4.6.1.2 3.1.4.6.1.2 PublishScriptSoapOut

The **PublishScriptSoapOut** WSDL message has one parameter, *PublishScriptResponse*.

```
<wsdl:message name="PublishScriptSoapOut">
  <wsdl:part name="parameters" element="tns:PublishScriptResponse" />
</wsdl:message>
```

3.1.3.1.123.1.4.6.2 3.1.4.6.2 Elements

The following XML schema element definitions are specific to this operation.

3.1.3.1.12.13.1.4.6.2.1 3.1.4.6.2.1 PublishScript

The following example shows the XSD for the **PublishScript** operation request.

```
<s:element name="PublishScript">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="script" type="s:string"
minOccurs="0" maxOccurs="1" />
    </s:sequence>
  </s:complexType>
</s:element>
```

The **PublishScript** element represents a Transact-SQL script that MUST be executed against the target database.

3.1.3.1.12.23.1.4.6.2.2 3.1.4.6.2.2 PublishScriptResponse

The following code shows the XSD for the **PublishScript** operation response.

```
<s:element name="PublishScriptResponse">
  <s:complexType />
</s:element>
```

The **PublishScriptResponse** is a response to the **PublishScript** request containing the Transact-SQL script that must be executed against a target database. The **PublishScriptSoapOut** WSDL message has one parameter, *PublishScriptResponse*.

3.1.5 Timer Events

3.1.5 Timer Events

None.

3.1.43.1.6 3.1.6 Other Local Events

None.

4 Protocol Examples

The following is an example of a procedure with which clients can use this protocol to create a simple database and then populate it with data.

First, the client begins by invoking the BeginPublish operation together with the valid server connection and user credentials, as shown in the following code example.

SOAP 1.1 BeginPublish Request

```
POST /Database%20Publishing%20Services%201.1/Publish/Service.asmx HTTP/1.1
Host: localhost
Content-Type: text/xml; charset=utf-8
Content-Length: length
SOAPAction: "http://schemas.microsoft.com/sqlserver/2006/12/publishing/BeginPublish"
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <BeginPublish
      xmlns="http://schemas.microsoft.com/sqlserver/2006/12/publishing">
      <serverName>myServer</serverName>
      <databaseName>myDatabase</databaseName>
      <sqlUsername>myUsername</sqlUsername>
      <sqlPassword>myPassword</sqlPassword>
      <useTransactions>true</useTransactions>
    </BeginPublish>
  </soap:Body>
</soap:Envelope>
```

SOAP 1.1 BeginPublish Response

```
HTTP/1.1 200 OK
Content-Type: text/xml; charset=utf-8
Content-Length: length
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <BeginPublishResponse
      xmlns="http://schemas.microsoft.com/sqlserver/2006/12/publishing" />
  </soap:Body>
</soap:Envelope>
```

Then, the client invokes the PublishScript operation with a Transact-SQL script, which creates the new database and the database objects (for example, tables, views, and stored procedures), as shown in the following code example.

SOAP 1.1 PublishScript Request

```
POST /Database%20Publishing%20Services%201.1/Publish/Service.asmx HTTP/1.1
Host: localhost
Content-Type: text/xml; charset=utf-8
Content-Length: length
SOAPAction: "http://schemas.microsoft.com/sqlserver/2006/12/publishing/PublishScript"
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
```

```

<PublishScript
xmlns="http://schemas.microsoft.com/sqlserver/2006/12/publishing">
<script>create table table1(id int primary key)</script>
</PublishScript>
</soap:Body>
</soap:Envelope>

```

SOAP 1.1 PublishScript Response

```

HTTP/1.1 200 OK
Content-Type: text/xml; charset=utf-8
Content-Length: length
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
<soap:Body>
<PublishScriptResponse
xmlns="http://schemas.microsoft.com/sqlserver/2006/12/publishing" />
</soap:Body>
</soap:Envelope>

```

Lastly, the client invokes the EndPublish operation to finish the publishing session and to release server resources, as shown in the following code example.

SOAP 1.1 EndPublish Request

```

POST /Database%20Publsihing%20Services%201.1/Publish/Service.asmx HTTP/1.1
Host: localhost
Content-Type: text/xml; charset=utf-8
Content-Length: length
SOAPAction: "http://schemas.microsoft.com/sqlserver/2006/12/publishing/EndPublish"
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
<soap:Body>
<EndPublish
xmlns="http://schemas.microsoft.com/sqlserver/2006/12/publishing" />
</soap:Body>
</soap:Envelope>

```

SOAP 1.1 EndPublish Response

```

HTTP/1.1 200 OK
Content-Type: text/xml; charset=utf-8
Content-Length: length
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
<soap:Body>
<EndPublishResponse
xmlns="http://schemas.microsoft.com/sqlserver/2006/12/publishing" />
</soap:Body>
</soap:Envelope>

```

5 Security

5.1 5.1—Security Considerations for Implementers

The use of this protocol requires passing server identification information and user authentication credentials (user name and password) to the **BeginPublish** method. Furthermore, operations that are performed by the **PublishScript** and **PublishData** methods are executed by using the information that was previously supplied to **BeginPublish**. Therefore, it is important to help guarantee the security of the data transmission by using HTTPS or by securing the service behind a firewall that requires authentication.

5.2 5.2—Index of Security Parameters

None.

6 Appendix A: Full WSDL

For ease of implementation, this section provides the full WSDL for the Database Publishing Wizard Protocol.

```
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
  xmlns:tm="http://microsoft.com/wsdl/mime/textMatching/"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:mime="http://schemas.xmlsoap.org/wsdl/mime/"
  xmlns:tns="http://schemas.microsoft.com/sqlserver/2006/12/publishing"
  xmlns:ss="http://www.w3.org/2001/XMLSchema"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
  xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
  targetNamespace="http://schemas.microsoft.com/sqlserver/2006/12/publishing"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:types>
      <s:schema elementFormDefault="qualified">
        targetNamespace="http://schemas.microsoft.com/sqlserver/2006/12/publishing">
          <s:element name="BeginPublish">
            <s:complexType>
              <s:sequence>
                <s:element minOccurs="0" maxOccurs="1" name="serverName" type="s:string">
                  <!--minOccurs="0" maxOccurs="1"-->
                <s:element minOccurs="0" maxOccurs="1" name="databaseName" type="s:string">
                  <!--minOccurs="0" maxOccurs="1"-->
                <s:element minOccurs="0" maxOccurs="1" name="sqlUsername" type="s:string">
                  <!--minOccurs="0" maxOccurs="1"-->
                <s:element minOccurs="0" maxOccurs="1" name="sqlPassword" type="s:string">
                  <!--minOccurs="0" maxOccurs="1"-->
                <s:element minOccurs="1" maxOccurs="1" name="useTransactions" type="s:boolean">
                  <!--minOccurs="1" maxOccurs="1"-->
                </s:sequence>
              </s:complexType>
            </s:element>
            <s:element name="BeginPublishResponse">
              <s:complexType />
            </s:element>
            <s:element name="PublishScript">
              <s:complexType>
                <s:sequence>
                  <s:element minOccurs="0" maxOccurs="1" name="script" type="s:string">
                    <!--minOccurs="0" maxOccurs="1"-->
                  </s:sequence>
                </s:complexType>
              </s:element>
              <s:element name="PublishScriptResponse">
                <s:complexType />
              </s:element>
              <s:element name="PublishData">
                <s:complexType>
                  <s:sequence>
                    <s:element name="ds" minOccurs="0" maxOccurs="1" name="ds"><!-->
                      <s:complexType>
                        <s:sequence>
                          <s:element ref="s:schema" />
                          <s:any />
                        </s:sequence>
                      </s:complexType>
                    </s:element>
                  </s:sequence>
                </s:complexType>
              </s:element>
              <s:element name="PublishDataResponse">
                <s:complexType />
              </s:element>
              <s:element name="EndPublish">
                <s:complexType />
              </s:element>
            </s:sequence>
          </s:complexType>
        </s:element>
      </s:schema>
    </wsdl:types>
  </wsdl:definitions>
```

```

        </s:element>
    <s:element name="EndPublishResponse">
        <s:complexType />
    </s:element>
    <s:element name="CancelPublish">
        <s:complexType />
    </s:element>
    <s:element name="CancelPublishResponse">
        <s:complexType />
    </s:element>
    <s:element name="GetServiceOptions">
        <s:complexType />
    </s:element>
    <s:element name="GetServiceOptionsResponse">
        <s:complexType>
            <s:sequence>
                <s:element minOccurs="0" maxOccurs="1"
name="GetServiceOptionsResult" minOccurs="0" maxOccurs="1">
                    <s:complexType mixed="true">
                        <s:sequence>
                            <s:any />
                        </s:sequence>
                    </s:complexType>
                </s:element>
            </s:sequence>
        </s:complexType>
    </s:element>
</s:schema>
</wsdl:types>
<wsdl:message name="BeginPublishSoapIn">
    <wsdl:part name="parameters" element="tns:BeginPublish" />
</wsdl:message>
<wsdl:message name="BeginPublishSoapOut">
    <wsdl:part name="parameters" element="tns:BeginPublishResponse" />
</wsdl:message>
<wsdl:message name="PublishScriptSoapIn">
    <wsdl:part name="parameters" element="tns:PublishScript" />
</wsdl:message>
<wsdl:message name="PublishScriptSoapOut">
    <wsdl:part name="parameters" element="tns:PublishScriptResponse" />
</wsdl:message>
<wsdl:message name="PublishDataSoapIn">
    <wsdl:part name="parameters" element="tns:PublishData" />
</wsdl:message>
<wsdl:message name="PublishDataSoapOut">
    <wsdl:part name="parameters" element="tns:PublishDataResponse" />
</wsdl:message>
<wsdl:message name="EndPublishSoapIn">
    <wsdl:part name="parameters" element="tns:EndPublish" />
</wsdl:message>
<wsdl:message name="EndPublishSoapOut">
    <wsdl:part name="parameters" element="tns:EndPublishResponse" />
</wsdl:message>
<wsdl:message name="CancelPublishSoapIn">
    <wsdl:part name="parameters" element="tns:CancelPublish" />
</wsdl:message>
<wsdl:message name="CancelPublishSoapOut">
    <wsdl:part name="parameters" element="tns:CancelPublishResponse" />
</wsdl:message>
<wsdl:message name="GetServiceOptionsSoapIn">
    <wsdl:part name="parameters" element="tns:GetServiceOptions" />
</wsdl:message>
<wsdl:message name="GetServiceOptionsSoapOut">
    <wsdl:part name="parameters" element="tns:GetServiceOptionsResponse" />
</wsdl:message>
<wsdl:portType name="PublishServiceSoap">
    <wsdl:operation name="BeginPublish">
        <wsdl:input message="tns:BeginPublishSoapIn" />
        <wsdl:output message="tns:BeginPublishSoapOut" />

```

```

    </wsdl:operation>
<wsdl:operation name="PublishScript">
    <wsdl:input message="tns:PublishScriptSoapIn" />
    <wsdl:output message="tns:PublishScriptSoapOut" />
</wsdl:operation>
<wsdl:operation name="PublishData">
    <wsdl:input message="tns:PublishDataSoapIn" />
    <wsdl:output message="tns:PublishDataSoapOut" />
</wsdl:operation>
<wsdl:operation name="EndPublish">
    <wsdl:input message="tns:EndPublishSoapIn" />
    <wsdl:output message="tns:EndPublishSoapOut" />
</wsdl:operation>
<wsdl:operation name="CancelPublish">
    <wsdl:input message="tns:CancelPublishSoapIn" />
    <wsdl:output message="tns:CancelPublishSoapOut" />
</wsdl:operation>
<wsdl:operation name="GetServiceOptions">
    <wsdl:input message="tns:GetServiceOptionsSoapIn" />
    <wsdl:output message="tns:GetServiceOptionsSoapOut" />
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="PublishServiceSoap" type="tns:PublishServiceSoap">
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
    <wsdl:operation name="BeginPublish">
        <soap:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/BeginPublish"
style="document" />
        <wsdl:input>
            <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="PublishScript">
        <soap:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/PublishScript"
style="document" />
        <wsdl:input>
            <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="PublishData">
        <soap:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/PublishData"
style="document" />
        <wsdl:input>
            <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="EndPublish">
        <soap:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/EndPublish"
style="document" />
        <wsdl:input>
            <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CancelPublish">

```

```

<soap:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/CancelPublish"
style="document" />
<wsdl:input>
<soap:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetServiceOptions">
<soap:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/GetServiceOptions"
style="document" />
<wsdl:input>
<soap:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
</wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:binding name="PublishServiceSoap12" type="tns:PublishServiceSoap">
<soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
<wsdl:operation name="BeginPublish">
<soap12:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/BeginPublish"
style="document" />
<wsdl:input>
<soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="PublishScript">
<soap12:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/PublishScript"
style="document" />
<wsdl:input>
<soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="PublishData">
<soap12:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/PublishData"
style="document" />
<wsdl:input>
<soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="EndPublish">
<soap12:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/EndPublish"
style="document" />
<wsdl:input>
<soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
</wsdl:operation name="CancelPublish">
```

```
<soap12:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/CancelPublish"
style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetServiceOptions">
    <soap12:operation soapAction=
"http://schemas.microsoft.com/sqlserver/2006/12/publishing/GetServiceOptions"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
<wsdl:service name="PublishService">
    <wsdl:port name="PublishServiceSoap" binding="tns:PublishServiceSoap">
        <soap:address location=
"http://localhost:44295/Database_Publsihing_Services_1.1/Publish/Service.asmx"
/>
        </wsdl:port>
    <wsdl:port name="PublishServiceSoap12" binding="tns:PublishServiceSoap12">
        <soap:address location=
"http://localhost:44295/Database_Publsihing_Services_1.1/Publish/Service.asmx"
/>
        </wsdl:port>
    </wsdl:service>
</wsdl:definitions>
```

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs[†].

- Microsoft SQL Server 2008
- Microsoft SQL Server 2008 R2
- Microsoft SQL Server 2012
- Microsoft SQL Server 2014
- [Microsoft SQL Server 2016](#)

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

8—Change Tracking

No table of This section identifies changes is available. The that were made to this document is either new or has had no changes since it's the last release. Changes are classified as New, Major, Minor, Editorial, or No change.

9—The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

<u>Section</u>	<u>Tracking number (if applicable) and description</u>	<u>Major change (Y or N)</u>	<u>Change type</u>
7 Appendix B: Product Behavior	Added SQL Server 2016 to the list of applicable products.	Y	Content update.

9 Index

A

Abstract data model

server 12

Applicability 9

Applicability statement 9~~8~~

Attribute groups 11

Attributes 11

B

BeginPublish element 14~~14~~

BeginPublish operation 13~~13~~

BeginPublishResponse element 15~~15~~

BeginPublishSoapIn message 14~~14~~

BeginPublishSoapOut message 14

~~14~~

C

CancelPublish element 16~~16~~

CancelPublish operation 15~~15~~

CancelPublishResponse element 16~~16~~

CancelPublishSoapIn message 15~~15~~

CancelPublishSoapOut message 16~~16~~

Capability negotiation 9

Change tracking 31~~33~~

Common message syntax 10~~10~~

Complex types 10

D

Data model - abstract

server 12

Directory service schema elements 11

~~11~~

E

Elements - directory service schema 11

EndPublish element 17~~17~~

EndPublish operation 16~~16~~

EndPublishResponse element 17~~17~~

EndPublishSoapIn message 17~~17~~

EndPublishSoapOut message 17

Events

local - server 21~~17~~

timer - server 21

F

Fields - vendor-extensible 9

Full WSDL 25

~~26~~

G

GetServiceOptions element 18~~18~~

GetServiceOptions operation 17~~17~~

GetServiceOptionsResponse element 18~~18~~

GetServiceOptionsSoapIn message 18~~18~~

GetServiceOptionsSoapOut message 18~~18~~

Glossary 6~~6~~

Groups 11

I

[Implementer - security considerations](#) 24
[Index of security parameters](#) 24
Informative references 7 [7](#)
[Initialization](#)
[server](#) 12
Introduction 6 [6](#)

L

[Local events](#)
[server](#) 21

M

[Message processing](#)
[server](#) 13
Messages 10 [10](#)
[attribute groups](#) 11
[attributes](#) 11
[complex types](#) 10
[elements](#) 10
[enumerated](#) 10
[groups](#) 11
[namespaces](#) 10
[simple types](#) 10
[syntax](#) 10
[transport](#) 10

N

[Namespaces](#) 10
Normative references 7

S

O

[Operations](#)
[BeginPublish](#) 13
[CancelPublish](#) 15
[EndPublish](#) 16
[GetServiceOptions](#) 17
[PublishData](#) 19
[PublishScript](#) 20
Overview 8 [7](#)
[Overview \(synopsis\)](#) 8

P

[Parameters - security index](#) 24
Preconditions 9 [8](#)
Prerequisites 9 [8](#)
Product behavior 30 [32](#)
Protocol [details](#) 12 [Details](#) 12
[overview](#) 12
Protocol examples 22 [22](#)
PublishData element 19 [20](#)
PublishData operation 19 [19](#)
PublishDataResponse element 20 [20](#)
PublishDataSoapIn message 19 [19](#)
PublishDataSoapOut message 19 [19](#)
PublishScript element 21 [21](#)
PublishScript operation 20 [20](#)

PublishScriptResponse element 21²¹

PublishScriptSoapIn message 20²⁰

PublishScriptSoapOut message 21²¹

PublishServiceSoap server details 12

12

R

References 7⁶

informative 7⁷

normative 7⁶

Relationship to other protocols 8

7

S

Schema elements - directory service 11

Security 24²⁵

implementer considerations 24

parameter index 24

Security considerations for implementers 24²⁵

Sequencing rules

server 13

Server

abstract data model 12

BeginPublish operation 13

CancelPublish operation 15

EndPublish operation 16

GetServiceOptions operation 17

initialization 12

local events 21

message processing 13

PublishData operation 19

PublishScript operation 20

sequencing rules 13

timer events 21

timers 12

Simple types 10

Standards assignments 9⁹

Syntax

messages - overview 10

T

Timer events

server 21

Timers

server 12

Tracking changes 31³³

Transport 10

Types

complex 10¹⁰

simple 10

V

Vendor-extensible fields 9⁹

Versioning 9

Versioning and capability negotiation 9⁸

W

WSDL 25